

T Series MIL Spec Ties

Features and Benefits

Available in a wide range of materials, these cable ties all feature internal serrations allowing for a positive hold onto cable, hose and pipe bundles. The design of the head guarantees a high tensile strength whilst allowing a very low insertion force, this, combined with the bent tail design of many of the ties, ensures a simple and quick installation. Whilst easily installed by hand, - manual and pneumatic (for high volume applications) tensioning tools are available to ensure a consistent and safe installation.

Application


For the routing, bundling and securing of cables, pipes and hoses.



T Series for bundling and securing of cables for a wide range of applications, available in various colours and materials.

Application Tool	Registration Numbers
MK3SP	1
MK3PNSP2, MK7P	2
MK7	3
MK7HT	4
MK20	5
MK6	6
MK9P, MK6PN	7
MK9	8
MK9HT	9
MK21	10
Autotool 2000	11

For more information please turn to page 389.




T18S – T150XL

Specifications please see table page 414 in Appendix.



Please Note for Product Specific Approvals please refer to Chapter 7.3



T18S – T150XL

Technical Table

Article-No.	Type	Length (L)	Width (W)	Bundle Ø max.	Min. Tensile Strength (N)	Material	Colour	Application Tool	Pack Cont.
Polyamide 6.6. UV Stabilised									
111-02860	T18S	83	2.3	16	80	PA66W	Black (BK)	1-3, 5	1000
111-01960	T18R	100	2.5	22	80	PA66W	Black (BK)	1-3, 5	100
111-02260	T18I	140	2.5	35	80	PA66W	Black (BK)	1-3, 5	100
111-02012	T18L	205	2.5	55	80	PA66W	Black (BK)	1-3, 5	100
111-02560	T25L	240	2.8	65	110	PA66W	Black (BK)	1-3, 5	100
111-02660	T25LL	330	2.8	95	110	PA66W	Black (BK)	1-3, 5	100
111-03030	T30R	150	3.5	35	135	PA66W	Black (BK)	1-3, 5	100
111-03460	T30L	190	3.5	50	135	PA66W	Black (BK)	1-3, 5	100
111-03570	T30LL	290	3.5	80	135	PA66W	Black (BK)	1-3, 5	100
111-03860	T40R	175	4.0	45	180	PA66W	Black (BK)	1-5	100
111-05860	T50S	150	4.6	35	225	PA66W	Black (BK)	1-10	100
111-04889	T50R	200	4.6	50	225	PA66W	Black (BK)	1-10	100
111-06206	T50M	245	4.6	65	225	PA66W	Black (BK)	1-10	100
111-05260	T50I	300	4.6	85	225	PA66W	Black (BK)	1-10	100
111-05440	T50L	390	4.6	110	225	PA66W	Black (BK)	1-10	100
111-06000	T50LL	445	4.6	130	225	PA66W	Black (BK)	1-10	100
111-05060	T80R	210	4.7	55	355	PA66W	Black (BK)	1-10	100
111-05460	T80L	390	4.7	110	355	PA66W	Black (BK)	1-10	100
111-12830	T120S	225	7.6	55	535	PA66W	Black (BK)	6-10	50
111-12230	T120I	300	7.6	80	535	PA66W	Black (BK)	6-10	100
111-12060	T120R(E)	390	7.6	105	535	PA66W	Black (BK)	6-10	100
111-12660	T120M	460	7.6	130	535	PA66W	Black (BK)	6-10	100
111-00171	T120XM	600	7.6	175	535	PA66W	Black (BK)	6-10	100
111-12430	T120L	760	7.6	225	535	PA66W	Black (BK)	6-10	50
111-15660	T150M	530	8.9	150	780	PA66W	Black (BK)	6-9	25
111-15460	T150L	820	8.8	245	780	PA66W	Black (BK)	6-9	25
111-15502	T150XL	1095	8.9	330	780	PA66W	Black (BK)	6-9	25
111-25100	T250X	370	12.5	100	1115	PA66W	Black (BK)	7-9	25

All Dimensions in mm. Subject to technical changes.

Specifications please see table page 414 in Appendix.



Please Note for Product Specific Approvals please refer to Chapter 7.3

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wire Identification](#) category:

Click to view products by [Hellermann](#) manufacturer:

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)