HellermannTyton

Specification Sheet

Part Number: TSR1I-6A



One Piece Surface Raceway, 3/4", 6.0 ft Long, PVC, Ivory, 120ft/Carton

Article Number 250-01602

Type TSR1-6A

Color Ivory (IV)

Features & Benefits

• Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance. • PVC construction is lightweight, durable and more affordable than metallic raceway systems. • Flexible hinge is designed to reduce stress cracking and discoloration from repeated opening and closing. • Foam tape backing with rubber based adhesive conforms to any flat surface to assist with temporary positioning and mounting. • Systems and fittings are available in white, office white and ivory to coordinate with a variety of décor. • Fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.

Quantity Per carton

_				-	_							
ם	rn	~ I	114	rt.	- 11	es	r	rı	n	tı	\mathbf{a}	'n
	v	u	и١	Ŀι	$\boldsymbol{\omega}$	CO	u		v	LI	u	

HellermannTyton surface raceway systems are the ideal solution for routing communication and power cables. No need to break into existing walls - raceway systems are designed to route cable along wall surfaces. Made of a PVC material, components are durable and affordable; and the one-piece construction and adhesive tape backing make positioning and mounting easy. HellermannTyton offers a low voltage TSR system and a power rated TSRP system that are available in three different diameters to accommodate different cable and wire bundle and conduit sizes. Both systems include a complete line of fittings and junction boxes that allow for clean and professional installations.

Short Description

One Piece Surface Raceway, 3/4", 6.0 ft Long, PVC, Ivory,

120ft/Carton

Global Part Name

TSR1-6A-PVC-BGE

Length L (Imperial)

6.0

Length L (Metric)

1.83

Width W (Imperial)

0.75

Width W (Metric)

19.05

Height H (Imperial)

.50

Height H (Metric)

12.70

Material

Polyvinylchloride (PVC)

Material Shortcut

PVC

Flammability UL 94 V0

Halogen Free No

Operating Temperature +122°F (+50°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Package Quantity (Imperial) 120

Package Quantity (Metric) 36.58

Customs Number 3925900000

© 2021 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hellermann manufacturer:

Other Similar products are found below:

T18RPOCKETPAC 380-03003 406064A TSR1I-21 TSR1I-29 TSR1I-33 TSR1I-36 105-4JW8 MS3109-12AU Q30LR-PA66-BK-C1 Q18I-PA66-NA-C1 Q18R-PA66-NA-C1 CTQM5-PA66-BK-C1 308-10600 T50IDH0C2 AS25 T18MR-NAT(100 PACK) T120L.NN2P MK7.9A 181-50840 621-10405 164-21008 TWT2 G51P-A-PE-NA E4500 GT.50X66P2 TSRI-JB2 111-01626 SBS4 NATURAL SBPEFR4-PE-BK-30M 308-30421 309-65129 309-65213 309-65298 309-65164 HIS-3-9/3-PEX-BU HIS-3 6/2 BRN HGDC1-3CC/7 HEGPA6612 GREY T50RS5.NB3P T150M-NAT HGDC1-3BW/3 HG1-3 HIS-3 3/1 BLU HGDC2-5BW/N HGDC2-5BW/L TSR1I-25 RSB3 RT250XL9X2 SLHD3X2G4