

Specification Sheet

Part Number: 111-01305

316 grade stainless steel offers excellent resistance to salt spray, corrosion, weather and chemical resistance.

Self locking, ball bearing mechanism for quick and easy installation, either by hand or by tensioning tool.

Fully enclosed head prevents dirt or grit from interfering with locking mechanism.

High tensile strength for maximum strength and safety on heavy duty applications.



Stainless Steel Tie, 43" Long, 922lb Tensile Strength, SS316, Metal, 25/pkg

Article Number 111-01305

Type MBT43UH

Color Metal (ML)

Quantity Per bag

_		
Prod	luct De	scription

HellermannTyton's stainless steel ties are designed with a ball bearing locking mechanism to assure high tensile strength and easy insertion when securing hoses, cables, pipes, and more. Stainless steel ties can be used in virtually any indoor, outdoor, or underground application. Grade 316 material is highly resistant to corrosion and widely used in marine environments where chemicals, salts, acids, and temperature extremes may affect the bundling application. MBT stainless steel ties in 316 stainless steel material are also available with a polyester protective coating. This coating creates a barrier and protectant from chemical reactions of dissimilar metals.

Short Description

Stainless Steel Tie, 43" Long, 922lb Tensile Strength, SS316, Metal,

25/pkg

922.0

Global Part Name

MBT43UH-SS316-ML

Minimum Tensile Strength (Imperial)

Minimum Tensile Strength (Metric) 4100.0

Length L (Imperial) 43.0

Length L (Metric) 1092.0

Identification Plate Position none

Releasable Closure No

Tie Closure ball bearing lock

Variant No Serration

Width W (Imperial) 0.63

Width W (Metric) 16.0 **Bundle Diameter Min (Imperial)** 0.47 **Bundle Diameter Min (Metric)** 12.0 **Bundle Diameter Max (Imperial)** 13.0 **Bundle Diameter Max (Metric)** 330.0 **Thickness T (Metric)** 0.27 **Material** Stainless Steel (SS316) **Material Shortcut** SS316 **Flammability** Non-burning **Halogen Free** Yes -112°F to +1000°F (-80°C to +538°C) **Operating Temperature** Reach Compliant (Article 33) Yes **ROHS Compliant** Yes

Package Quantity (Metric)	25			
Customs Number	732	6908695		
© 2021 HellermannTyton. All Rights R	eserved			
	ntact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Ties category:

Click to view products by HellermannTyton manufacturer:

Other Similar products are found below:

65034-C 65037-C 770-1751-10 REL50L0C2 20093-0 SF600-120X SJ-3463 SJ3518FR-1x50 SJ3526N-Beige-2"x50yd SJ3526N BLACK
58" X 50YD SJ3571 SJ-3571-1"x50yd-Black PLT2S-C4 34-455-C 3722 561-B110120 561-N3510 TYZ528M 34-463-C URT20S-M
06226 08350-0 08600-0 08376-0 10036-0 10037-0 10325-0 10362-0 10606-0 561-EZ250 561-EZ625 SJ3527N-Beige-2"x50yd SJ3527NLOOP-BLACK-1 SJ3572-2"x50yd-Black CF5625-000 V03HK 65004-C 65005-C 65007-C 65036-C 157-00039 770-1708 770-1753-10
65035-C 770-1752 SPNY-041-9 SF400-120X 3719 08582-0 08386-0