

Cable Tie locked by glass fibre pin

This cable tie is distinguished by its smooth strap and unique locking mechanism. The chamfered head of the KR-Series allows for a firm fit around the bundled element. Due to its special design KR-Series cable ties can be used as a safety method to bundle any cable and to also secure bellows on steering racks, water hoses or vacuum lines. The endless strap version is fairly flexible and can be cut to any length required. Separate heads are available to fix the strap.

Features and benefits

- Cable tie without serration to avoid any damage to cables
- Strap is locked into place with a glass-fibre reinforced pin
- Very secure and vibration resistant fixing
- Available in various materials, colours and almost every length
- Cable ties from PA12 are highly resistant to chemicals, impact and UV light
- KR-ties up to 426 mm are made as one piece
- For assembly a special KR-tool is needed




The KR-Series has been repeatedly proven in high vibration applications.




Specific part numbers according to EN45545 available on request.



Material specification please see page 26.




The unlocked head of a KR-tie.



The cable tie (red) is locked into place with the pin.

KR-Series, 1-Piece



Cable tie KR-Series

| TYPE | Width (W) | Length (L) | Bundle Ø max. | N | Material | Colour | Pack Cont. | Tools | Article-No. |
|--------|-----------|------------|---------------|-----|----------|--------------|------------|-------|-------------|
| KR6/35 | 6.1 | 360.0 | 93.0 | 490 | PA66 | Natural (NA) | 50 pcs. | 13 | 121-63519 |
| | 6.1 | 360.0 | 93.0 | 490 | PA66HS | Natural (NA) | 50 pcs. | 13 | 121-63555 |
| | 6.1 | 360.0 | 93.0 | 490 | PA66W | Black (BK) | 50 pcs. | 13 | 121-63560 |
| KR8/21 | 8.0 | 210.0 | 47.0 | 785 | PA66HS | Natural (NA) | 50 pcs. | 13-14 | 121-82155 |
| | 8.0 | 210.0 | 47.0 | 785 | PA66 | Natural (NA) | 50 pcs. | 13-14 | 121-82119 |
| | 8.0 | 210.0 | 47.0 | 785 | PA66W | Black (BK) | 50 pcs. | 13-14 | 121-82160 |

All dimensions in mm. Subject to technical changes.

Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available.

Recommended Tools


| | | |
|--|-------|---------|
| | 13 | 14 |
| | KR6/8 | KR8PNSE |
| | 559 | 559 |

For more information on toolings please refer to the Application Tooling chapter.

EN 45545-2




For product specific approvals and specifications please refer to the Appendix.



Cable Tie locked by glass fibre pin

KR-Series, 1-Piece



Cable tie KR-Series

| TYPE | Width (W) | Length (L) | Bundle Ø max. | N | Material | Colour | Pack Cont. | Tools | Article-No. |
|--------|-----------|------------|---------------|-----|----------|--------------|------------|-------|-------------|
| KR8/33 | 8.0 | 337.0 | 86.0 | 390 | PA12 | Black (BK) | 50 pcs. | 13-14 | 121-83380 |
| | 8.0 | 337.0 | 86.0 | 785 | PA66 | Natural (NA) | 50 pcs. | 13-14 | 121-83319 |
| | 8.0 | 337.0 | 86.0 | 785 | PA46 | Grey (GY) | 50 pcs. | 13-14 | 121-83378 |
| | 8.0 | 337.0 | 86.0 | 785 | PA66HS | Natural (NA) | 50 pcs. | 13-14 | 121-83355 |
| | 8.0 | 337.0 | 86.0 | 785 | PA66W | Black (BK) | 50 pcs. | 13-14 | 121-83360 |
| KR8/43 | 8.0 | 426.0 | 105.0 | 785 | PA66HS | Black (BK) | 50 pcs. | 13-14 | 121-74360 |
| | 8.0 | 426.0 | 105.0 | 785 | PA66HS | Natural (NA) | 50 pcs. | 13-14 | 121-74359 |


All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available.

EN 45545-2



For product specific approvals and specifications please refer to the Appendix.

KR-Series, ultrasonic welded




Cable tie KR-Series, ultrasonic welded

i Other dimensions are available on request.

| TYPE | Width (W) | Length (L) | Bundle Ø max. | N | Material | Colour | Pack Cont. | Tools | Article-No. |
|--------|-----------|------------|---------------|-----|----------|--------------|------------|-------|-------------|
| KR8/50 | 8.0 | 500.0 | 152.0 | 785 | PA66 | Natural (NA) | 50 pcs. | 13-14 | 121-05019 |
| KR8/60 | 8.0 | 600.0 | 184.0 | 785 | PA66W | Black (BK) | 50 pcs. | 13-14 | 121-06060 |

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available.

KR-Series, endless



Cable tie KR8S1

Double-head KR8C5

| TYPE | Width (W) | Length (L) | N | Material | Colour | Pack Cont. | Tools | Article-No. |
|--------|-----------|------------|-----|----------|--------------|------------|-------|-------------|
| KR8/S1 | 8.0 | 50.0 m | 785 | PA66HS | Natural (NA) | 50.0 m | 13-14 | 121-98151 |
| | 8.0 | 50.0 m | 785 | PA66W | Black (BK) | 50.0 m | 13-14 | 121-98160 |
| KR8/C5 | 11.7 | 38.0 | - | PA66HS | Natural (NA) | 200 pcs. | 13-14 | 121-58551 |
| | 11.7 | 38.0 | - | PA66W | Black (BK) | 200 pcs. | 13-14 | 121-58560 |

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available.

Material Specification Overview

| MATERIAL | Material Shortcut | Operating Temperature | Colour** | Flammability | Material Properties* | Material Specifications |
|---|--------------------|---|--------------------------|--------------|--|-------------------------|
| Aluminium-alloy | AL | -40 °C to +180 °C | Natural (NA) | | <ul style="list-style-type: none"> Corrosion resistant Antimagnetic | RoHS |
| Chloroprene | CR | -20 °C to +80 °C | Black (BK) | | <ul style="list-style-type: none"> Weather-resistant High yield strength | RoHS |
| Ethylene Tetrafluoroethylene (Tefzel®) | E/TFE | -80 °C to +170 °C | Blue (BU) | UL 94 V0 | <ul style="list-style-type: none"> Resistance to radioactivity UV-resistant, not moisture sensitive Good chemical resistance to: acids, bases, oxidizing agents | RoHS |
| Polyacetal | POM | -40 °C to +90 °C, (+110 °C, 500 h) | Natural (NA) | UL 94 HB | <ul style="list-style-type: none"> Limited brittleness sensitivity Flexible at low temperature Not moisture sensitive Robust on impacts | RoHS |
| Polyamide 11 | PA11 | -40 °C to +85 °C, (+105 °C, 500 h) | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Bio-plastic, derived from vegetable oil Strong impact resistance at low temperature Very low moisture absorption Weather-resistant Good chemical resistant | HF RoHS |
| Polyamide 12 | PA12 | -40 °C to +85 °C, (+105 °C, 500 h) | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Good chemical resistance to: acids, bases, oxidizing agents UV-resistant | HF RoHS |
| Polyamide 4.6 | PA46 | -40 °C to +150 °C (5000 h), +195 °C (500 h) | Natural (NA), Grey (GY) | UL 94 V2 | <ul style="list-style-type: none"> Resistance to high temperatures Very moisture sensitive Low smoke sensitiv | HF LFH RoHS |
| Polyamide 6 | PA6 | -40 °C to +80 °C | Black (BK) | UL 94 V2 | <ul style="list-style-type: none"> High yield strength | RoHS |
| Polyamide 6, high impact modified | PA6HIR | -40 °C to +80 °C | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Limited brittleness sensitivity Higher flexibility at low temperature | RoHS |
| Polyamide 6.6 | PA66 | -40 °C to +85 °C, (+105 °C, 500 h) | Black (BK), Natural (NA) | UL 94 V2 | <ul style="list-style-type: none"> High yield strength | HF RoHS |
| Polyamide 6.6, glass-fibre reinforced | PA66GF13, PA66GF15 | -40 °C to +105 °C | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Good resistance to: lubricants, vehicle fuel, salt water and a lot of solvent | HF RoHS |
| Polyamide 6.6, heat and UV stabilised | PA66HSW | -40 °C to +105 °C | Black (BK) | UL 94 V2 | <ul style="list-style-type: none"> High yield strength Modified elevated max. temperature UV-resistant | HF RoHS |
| Polyamide 6.6, heat stabilised | PA66HS | -40 °C to +105 °C | Black (BK), Natural (NA) | UL 94 V2 | <ul style="list-style-type: none"> High yield strength Modified elevated max. temperature | HF RoHS |
| Polyamide 6.6, high impact modified | PA66HIR | -40 °C to +80 °C, (+105 °C, 500 h) | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Limited brittleness sensitivity Higher flexibility at low temperature | RoHS |
| Polyamide 6.6, high impact modified, heat and UV stabilised | PA66HIRHSW | -40 °C to +110 °C | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Limited brittleness sensitivity Higher flexibility at low temperature Modified elevated max. temperature High yield strength, UV-resistant | RoHS |
| Polyamide 6.6, high impact modified, heat stabilised | PA66HIRHS | -40 °C to +105 °C | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Limited brittleness sensitivity Higher flexibility at low temperature Modified elevated max. temperature | RoHS |
| Polyamide 6.6, high impact modified, ScanBlack | PA66HIR(S) | -40 °C to +80 °C, (+105 °C, 500 h) | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Limited brittleness sensitivity Higher flexibility at low temperature | RoHS |
| Polyamide 6.6, UV-resistant | PA66W | -40 °C to +85 °C, (+105 °C, 500 h) | Black (BK) | UL 94 V2 | <ul style="list-style-type: none"> High yield strength UV-resistant | HF RoHS |

| MATERIAL | Material Shortcut | Operating Temperature | Colour** | Flammability | Material Properties* | Material Specifications |
|---|-------------------|---------------------------------------|-----------------------------|---------------------|--|--|
| Polyamide 6.6, with metal particles | PA66MP | -40 °C to +85 °C, (+105 °C, 500 h) | Blue (BU) | UL 94 HB | <ul style="list-style-type: none"> High yield strength Metal and X-Ray detectable | HF RoHS |
| Polyamide 6.6, with metal particles | PA66MP+ | -40 °C to +85 °C | Blue (BU) | not flame retardant | <ul style="list-style-type: none"> High yield strength Metal and x-ray detectable | HF RoHS |
| Polyamide 6.6 V0 | PA66V0 | -40 °C to +85 °C | White (WH) | UL 94 V0 | <ul style="list-style-type: none"> High yield strength Low smoke emission | HF LFH RoHS |
| Polyester | SP | -50 °C to +150 °C | Black (BK) | halogen free | <ul style="list-style-type: none"> UV-resistant Good chemical resistance to: most acids, alkalis and oils | HF LFH RoHS |
| Polyetheretherketone | PEEK | -55 °C to +240 °C | Beige (BGE) | UL 94 V0 | <ul style="list-style-type: none"> Resistance to radioactivity Not moisture sensitive Good chemical resistance to: acids, bases, oxidizing agents | HF LFH RoHS |
| Polyethylene | PE | -40 °C to +50 °C | Black (BK), Grey (GY) | UL 94 HB | <ul style="list-style-type: none"> Low moisture absorption Good chemical resistance to: most acids, alcohol and oils | HF RoHS |
| Polyolefin | PO | -40 °C to +90 °C | Black (BK) | UL 94 V0 | <ul style="list-style-type: none"> Low smoke emissions | HF LFH RoHS |
| Polypropylene | PP | -40 °C to +115 °C | Black (BK), Natural (NA) | UL 94 HB | <ul style="list-style-type: none"> Floats in water Moderate yield strength Good chemical resistance to: organic acids | HF RoHS |
| Polypropylene, Ethylene-Propylene- Dien-Terpolymere- rubber free of Nitrosamine | PP, EPDM | -20 °C to +95 °C | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Good resistance to high temperatures Good chemical and abrasion resistance | HF RoHS |
| Polypropylene with metal particles | PPMP | -40 °C to +115 °C | Blue (BU) | UL 94 HB | <ul style="list-style-type: none"> Metal and X-Ray detectable Heat resistant Moderate yield strength Good chemical resistance | RoHS |
| Polypropylene with metal particles | PPMP+ | -40 °C to +85 °C | Blue (BU) | not flame retardant | <ul style="list-style-type: none"> High yield strength Metal and x-ray detectable | HF RoHS |
| Polyvinylchloride | PVC | -10 °C to +70 °C | Black (BK), Natural (NA) | UL 94 V0 | <ul style="list-style-type: none"> Low moisture absorption Good chemical resistance to: acids, ethanol and oil | RoHS |
| Stainless Steel | SS304, SS316 | -80 °C to +538 °C | Natural (NA) | non-burning | <ul style="list-style-type: none"> Corrosion resistant Antimagnetic Weather resistant Outstanding chemical resistance | HF LFH RoHS |
| Thermoplastic Polyurethane | TPU | -40 °C to +85 °C | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> High elastic Good chemical resistance to: acids, bases and oxidizing agents | HF RoHS |

Tefzel® is a registered trademark of DuPont. General linguistic usage for cable ties made from raw material E/TFE is Tefzel®-Tie. In addition to Tefzel® from DuPont HellermannTyton is also using equivalent E/TFE raw material from other suppliers. *These details are only rough guide values. They should not be regarded as a material specification and are no substitute for a suitability test. Please see our datasheets for further details.

**More colours on request.



N = Minimum Loop Tensile Strength for Cable Ties (Newton)

HF = Halogenfree

LFH = Limited Fire Hazard

RoHS = Restriction of Hazardous Substances

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Cable Ties](#) category:

Click to view products by [HellermannTyton](#) manufacturer:

Other Similar products are found below :

[65034-C](#) [65037-C](#) [770-1751-10](#) [REL50L0C2](#) [20093-0](#) [SF600-120X](#) [SJ-3463](#) [SJ3518FR-1x50](#) [SJ3526N-Beige-2"x50yd](#) [SJ3571](#) [PLT2S-C4](#)
[34-455-C](#) [3722](#) [561-B110120](#) [561-N3510](#) [TYZ528M](#) [34-463-C](#) [URT20S-M](#) [06226](#) [08350-0](#) [08600-0](#) [08376-0](#) [10036-0](#) [10037-0](#) [10325-0](#)
[10362-0](#) [10606-0](#) [1122-4JW8](#) [561-EZ250](#) [561-EZ625](#) [SJ3527N-Beige-2"x50yd](#) [SJ3527N-LOOP-BLACK-1](#) [SJ3572-2"x50yd-Black](#) [CF5625-](#)
[000](#) [V03HK](#) [65004-C](#) [65005-C](#) [65007-C](#) [65036-C](#) [157-00039](#) [770-1708](#) [770-1753-10](#) [65035-C](#) [770-1752](#) [SPNY-041-9](#) [SF400-120X](#) [3719](#)
[08582-0](#) [08386-0](#) [10431-0](#)