

## Specification Sheet

Part Number: 150-28140



Mount design applies quickly and easily to .2" (5mm) studs.  
Unique latch style allows for easy re-entry to bundles.

Design gives low insertion force and high extraction force.

**Article Number** 150-28140

**Type** FBB140

**Color** Black (BK)

**Quantity Per** bag

**Product Description** Ladder Stud Mounts can be used in a wide variety of applications where .2" diameter bolts are used, and cables need to be bundled and secured. The unique latch style allows for easy re-entry to bundles.

**Short Description** Ladder Stud Mount, 4.3" Length, Stud Diameter .2", Max Bundle Diameter 0.91", PA66, Black, 500/pkg

**Global Part Name** FBB140-PA66-BK

|                                       |                  |
|---------------------------------------|------------------|
| <b>Length L (Imperial)</b>            | 5.7              |
| <b>Length L (Metric)</b>              | 142              |
| <b>Fixation Method</b>                | Weld Stud Fixing |
| <b>Identification Plate Position</b>  | none             |
| <b>Releasable Closure</b>             | Yes              |
| <b>Tie Closure</b>                    | ladder style     |
| <b>Variant</b>                        | No Serration     |
| <b>Width W (Imperial)</b>             | 0.4              |
| <b>Width W (Metric)</b>               | 10.0             |
| <b>Bundle Diameter Min (Imperial)</b> | 0.24             |
| <b>Bundle Diameter Min (Metric)</b>   | 6.0              |
| <b>Bundle Diameter Max (Imperial)</b> | 1.5              |
| <b>Bundle Diameter Max (Metric)</b>   | 38.0             |
| <b>Height H (Imperial)</b>            | 0.06             |
| <b>Height H (Metric)</b>              | 1.4              |
| <b>Stud Diameter (Metric)</b>         | 5.0 mm           |

|                                     |                                  |
|-------------------------------------|----------------------------------|
| <b>Stud Diameter (Imperial)</b>     | 0.2                              |
| <b>Material</b>                     | Polyamide 6.6 (PA66)             |
| <b>Material Shortcut</b>            | PA66                             |
| <b>Flammability</b>                 | UL 94 V-2                        |
| <b>Operating Temperature</b>        | -40°F to +185°F (-40°C to +85°C) |
| <b>Reach Compliant (Article 33)</b> | Yes                              |
| <b>ROHS Compliant</b>               | Yes                              |
| <b>Package Quantity (Imperial)</b>  | 500                              |
| <b>Package Quantity (Metric)</b>    | 500                              |
| <b>Customs Number</b>               | 3926909988                       |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Cable Tie Mounts](#) category:*

*Click to view products by [HellermannTyton](#) manufacturer:*

Other Similar products are found below :

[3-350087-0](#) [CTB75X75BKA-C](#) [561-EZAB580T](#) [561-EZS375B40](#) [561-TA250125](#) [08443-0](#) [10035-0](#) [561-TA00600](#) [1689174-1](#) [08445-0](#)  
[10351-0](#) [561-TA250125B](#) [20015-0](#) [10350-0](#) [10029-0](#) [08484-0](#) [08446-0](#) [08318-0](#) [PAM075NY-A-C](#) [MTH1-3](#) [10044](#) [151-01802](#) [151-11319](#)  
[151-11819](#) [PLWP1SB-D](#) [PLWP1M-C](#) [PLWP2SA-D](#) [PLWP2SB-D](#) [PLWP2S-C](#) [PLWP1S-D](#) [PLWP1M-D](#) [TA1S8-C](#) [ABM3H-A-L](#) [ABM3H-](#)  
[AT-T0](#) [EMS-A-C0](#) [EMSK3-1-3-0](#) [10079](#) [10030](#) [151-10930](#) [151-10920](#) [3590](#) [151-28320](#) [151-28349](#) [151-28530](#) [151-10914](#) [151-10904](#) [151-](#)  
[10916](#) [151-10906](#) [06297](#) [CTB75X75NTA-C](#)