

## Specification Sheet

Part Number: 150-55610



Fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation. Fir Tree design provides low extraction and high extraction force.

1-Piece Cable Tie/Fir Tree Mount with Disc, 4.3"L, .19"-.20" Mounting Hole, PA66, Black, 500/pkg

**Article Number** 150-55610

**Type** T18RDP5

**Color** Black (BK)

**Quantity Per** pcs.

**Product Description** Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. This is sold as an assembly with the cable tie.

**Short Description** 1-Piece Cable Tie/Fir Tree Mount with Disc, 4.3"L, .19"-.20" Mounting Hole, PA66, Black, 500/pkg

**Global Part Name** T18RDP5-PA66-BK

<b>Minimum Tensile Strength (Imperial)</b>	18.0
<b>Minimum Tensile Strength (Metric)</b>	80
<b>Length L (Imperial)</b>	4.3
<b>Length L (Metric)</b>	110.0
<b>Fixation Method</b>	Fir tree for round holes
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.1
<b>Width W (Metric)</b>	2.5
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	0.8
<b>Bundle Diameter Max (Metric)</b>	20.0
<b>Thickness T (Imperial)</b>	0.043

<b>Thickness T (Metric)</b>	1.1
<b>Panel Thickness Min (Imperial)</b>	0.12
<b>Panel Thickness Max (Imperial)</b>	0.02
<b>Panel Thickness Min (Metric)</b>	3.0
<b>Panel Thickness Max (Metric)</b>	4.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.19 - 0.2
<b>Mounting Hole Diameter D (Metric)</b>	4.9 - 5.1 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.19
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.197
<b>Mounting Hole Diameter D Max (Metric)</b>	5.1
<b>Disc Diameter (Metric)</b>	13.0
<b>Disc Diameter (Imperial)</b>	0.5

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL 94 V-2

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 500

**Package Quantity (Metric)** 500

**Customs Number** 3926909988

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Cable Tie Mounts](#) category:*

*Click to view products by [HellermannTyton](#) manufacturer:*

Other Similar products are found below :

[3-350087-0](#) [CTB75X75BKA-C](#) [561-EZAB580T](#) [561-EZS375B40](#) [561-TA250125](#) [08443-0](#) [10035-0](#) [561-TA00600](#) [1689174-1](#) [08445-0](#)  
[10351-0](#) [561-TA250125B](#) [20015-0](#) [10350-0](#) [10029-0](#) [08484-0](#) [08446-0](#) [08318-0](#) [PAM075NY-A-C](#) [MTH1-3](#) [10044](#) [151-11319](#) [151-11819](#)  
[PLWP1SB-D](#) [PLWP1M-C](#) [PLWP2SA-D](#) [PLWP2SB-D](#) [PLWP2S-C](#) [PLWP1S-D](#) [PLWP1M-D](#) [TA1S8-C](#) [ABM3H-A-L](#) [ABM3H-AT-T0](#)  
[EMS-A-C0](#) [EMSK3-1-3-0](#) [10079](#) [10030](#) [151-10930](#) [151-10920](#) [3590](#) [151-28320](#) [151-28349](#) [151-28530](#) [151-10914](#) [151-10904](#) [151-10916](#)  
[151-10906](#) [06297](#) [CTB75X75NTA-C](#) [792](#)