HellermannTyton

Specification Sheet

Part Number: 156-00538



Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.

Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

Article Number 156-00538

Type T50REC4B

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's Two Piece Edge Clip with Cable Tie Assemblies

are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the

integrated metal clamp that holds the edge clip in place.

Short Description 2-Piece Cable Tie & Edge Clip, 8.0" Long, EC4B, 1–3 mm Panel,

50lb, PA66HS/PA66HIRHSUV, Black, 500/pkg

Global Part Name T50REC4B-PA66HS/PA66HIRHS-BK

Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8.0
Length L (Metric)	203.2
Fixation Method	EdgeClip, top, assembled, 2 piece
Identification Plate Position	none
Releasable Closure	No
Variant	Inside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.20
Bundle Diameter Min (Metric)	5.0
Bundle Diameter Max (Imperial)	2.0
Bundle Diameter Max (Metric)	50.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.2

Height H (Imperial)	0.05
Height H (Metric)	1.20
Panel Thickness Min (Imperial)	0.04
Panel Thickness Max (Imperial)	0.12
Panel Thickness Min (Metric)	1.0
Panel Thickness Max (Metric)	3.0
Material	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS PA66HS
Material Shortcut Material Cable Tie	PA66HIRHS PA66HS Polyamide 6.6 heat stabilized (PA66HS)
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Material Cable Tie Flammability	Polyamide 6.6 heat stabilized (PA66HS) UL 94 HB -40°F to +221°F (-40°C to +105°C) -40°F to +230°F (-40°C to
Material Cable Tie Flammability Operating Temperature	Polyamide 6.6 heat stabilized (PA66HS) UL 94 HB -40°F to +221°F (-40°C to +105°C) -40°F to +230°F (-40°C to +110°C)
Material Cable Tie Flammability Operating Temperature	Polyamide 6.6 heat stabilized (PA66HS) UL 94 HB -40°F to +221°F (-40°C to +105°C) -40°F to +230°F (-40°C to +110°C)

Customs Number	3926	5909988		
© 2022 HellermannTyton. All Rights Reso		RoHS/WEEE Compliance	Disclaimer	Terms and Conditions

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Ties category:

Click to view products by HellermannTyton manufacturer:

Other Similar products are found below:

65034-C 65037-C 770-1751-10 REL50L0C2 20093-0 SF600-120X SJ-3463 SJ3518FR-1x50 SJ3526N-Beige-2"x50yd SJ3526N BLACK
58" X 50YD SJ3571 SJ-3571-1"x50yd-Black PLT2S-C4 34-455-C 3722 561-B110120 561-N3510 TYZ528M 34-463-C URT20S-M
06226 08350-0 08600-0 08376-0 10036-0 10037-0 10325-0 10362-0 10606-0 561-EZ250 561-EZ625 SJ3527N-Beige-2"x50yd SJ3527NLOOP-BLACK-1 SJ3572-2"x50yd-Black CF5625-000 V03HK 65004-C 65005-C 65007-C 65036-C 157-00039 770-1708 770-1753-10
65035-C 770-1752 SPNY-041-9 SF400-120X 3719 08582-0 08386-0