

## Specification Sheet

Part Number: 157-00017



Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.

Initial fir tree serves as a locating feature for assistance in blind assembly applications.

Disc feature provides anti-rattle protection in high vibration applications.

1-Piece Cable Tie/Fir Tree Mount with Disc, 6.7"L, .27"-.28" Mounting Hole, PA66, Black, 100/pkg

**Article Number** 157-00017

**Type** OS170-FT7

**Color** Black (BK)

**Quantity Per** bag

**Product Description** Fir tree mounts, with cable ties, provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.

**Short Description** 1-Piece Cable Tie/Fir Tree Mount with Disc, 6.7"L, .27"-.28" Mounting Hole, PA66, Black, 100/pkg

**Global Part Name** OS170-FT7-PA66-BK

**Minimum Tensile Strength (Imperial)** 30.0

**Minimum Tensile Strength (Metric)** 147

**Length L (Imperial)** 6.7

**Length L (Metric)** 170.0

**Fixation Method** Fir tree for round holes

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Width W (Imperial)** 0.21

**Width W (Metric)** 5.3

**Bundle Diameter Min (Imperial)** 0.06

**Bundle Diameter Min (Metric)** 1.6

**Bundle Diameter Max (Imperial)** 1.18

**Bundle Diameter Max (Metric)** 30.0

**Thickness T (Imperial)** 0.055

<b>Thickness T (Metric)</b>	1.4
<b>Panel Thickness Max (Imperial)</b>	0.18
<b>Panel Thickness Min (Metric)</b>	0.6
<b>Panel Thickness Max (Metric)</b>	4.50
<b>Mounting Hole Diameter D (Imperial)</b>	0.27 - 0.28
<b>Mounting Hole Diameter D (Metric)</b>	6.8 - 7.2 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	7.2
<b>Disc Diameter (Metric)</b>	16.0
<b>Disc Diameter (Imperial)</b>	0.63
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V-2
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes

**Package Quantity (Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 3926909988

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Cable Ties](#) category:*

*Click to view products by [HellermannTyton](#) manufacturer:*

Other Similar products are found below :

[65034-C](#) [65037-C](#) [770-1751-10](#) [REL50L0C2](#) [20093-0](#) [SF600-120X](#) [SJ-3463](#) [SJ3518FR-1x50](#) [SJ3526N-Beige-2"x50yd](#) [SJ3526N BLACK](#)  
[58" X 50YD](#) [SJ3571](#) [SJ-3571-1"x50yd-Black](#) [PLT2S-C4](#) [34-455-C](#) [3722](#) [561-B110120](#) [561-N3510](#) [TYZ528M](#) [34-463-C](#) [URT20S-M](#)  
[06226](#) [08350-0](#) [08600-0](#) [08376-0](#) [10036-0](#) [10037-0](#) [10325-0](#) [10362-0](#) [10606-0](#) [561-EZ250](#) [561-EZ625](#) [SJ3527N-Beige-2"x50yd](#) [SJ3527N-](#)  
[LOOP-BLACK-1](#) [SJ3572-2"x50yd-Black](#) [CF5625-000](#) [V03HK](#) [65004-C](#) [65005-C](#) [65007-C](#) [65036-C](#) [157-00039](#) [770-1708](#) [770-1753-10](#)  
[65035-C](#) [770-1752](#) [SPNY-041-9](#) [SF400-120X](#) [3719](#) [08582-0](#) [08386-0](#)