



HelaGuard Accessories

- **A90FM 90° Elbow**

Internal and external thread, nickel plated brass.


Features and Benefits

- IP68 when used with sealing washers



Helaguard A90FM 90° Elbow.

MATERIAL	Nickel Plated Brass (NPB)
Operating Temperature	-100 °C to +300 °C



Helaguard 90° threaded elbow

TYPE	External Thread Size (metric)	Internal Thread Size (metric)	Min. Bore Size (B)	Height (H)	Width (W)	External Thread Length (ETL)	Internal Thread Length (ITL)	Pack Cont.	Colour	Article-No.
A90FM-M16	M16	M16	12.0	38.0	31.0	10	11	10 pcs.	Metal (ML)	166-50001
A90FM-M20	M20	M20	15.8	46.0	35.0	13	13	10 pcs.	Metal (ML)	166-50002
A90FM-M25	M25	M25	20.4	55.8	43.8	14	16	10 pcs.	Metal (ML)	166-50003
A90FM-M32	M32	M32	27.0	66.6	53.6	15	16	2 pcs.	Metal (ML)	166-50004
A90FM-M40	M40	M40	34.6	80.4	67.0	18	17	1 pcs.	Metal (ML)	166-50005
A90FM-M50	M50	M50	44.6	99.0	80.5	18	18	1 pcs.	Metal (ML)	166-50006

All dimensions in mm. Subject to technical changes.

Minimum Order Quantity (MOQ) may differ from package content.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Conduit Fittings & Accessories](#) category:

Click to view products by [HellermannTyton](#) manufacturer:

Other Similar products are found below :

[M3231GAB](#) [M3231GAC](#) [M3231GAE](#) [M3231GL](#) [M3231GN](#) [M3231GT](#) [VC-937-16/RED](#) [VC-1125-16/RED](#) [DM0240-1/2A](#) [3408B](#) [G6002](#)
[M4340GAE](#) [C2016-P](#) [C2012-P](#) [3407B](#) [1660-P](#) [561-87BG11BLK](#) [561-75BG11B](#) [1.511.1601.14](#) [1.533.1201.50](#) [1.533.1601.51](#) [1.533.2001.51](#)
[1.533.4001.50](#) [1.533.5001.50](#) [BVNV-P428](#) [BVBV-P366](#) [2276](#) [2663-P](#) [3405B](#) [C2070-P](#) [3582V](#) [2643-P](#) [4975](#) [2644-P](#) [2955](#) [M50](#) [2404-P](#)
[C2008-P](#) [2723-P](#) [2291](#) [2133-P](#) [3048F](#) [VC12516](#) [RC156-0500](#) [DM0523-1/2A](#) [1035A](#) [DMS0250-1A](#) [DMS0313-1A](#) [1040A](#) [1050A](#) [R1/8A](#)