



HelaGuard Accessories


- **ALS Plated Steel Locknuts**

The ALS hexagonal locknut is used to secure fitting.



HelaGuard ALS Plated Steel Locknuts.

MATERIAL	Galvanised Steel (GS)
Operating Temperature	-100 °C to +300 °C



HelaGuard locknut

TYPE	Thread Size	A/F Nut (A/F3)	Across Corners (A/C)	Thickness (T)	Pack Cont.	Colour	Article-No.
ALS-M16	M16	24	27	3	10 pcs.	Metal (ML)	166-50119
ALS-M20	M20	25	28	3	10 pcs.	Metal (ML)	166-50120
ALS-M25	M25	33	38	3	10 pcs.	Metal (ML)	166-50121
ALS-M32	M32	41	47	3	2 pcs.	Metal (ML)	166-50122
ALS-M40	M40	50	58	4	1 pcs.	Metal (ML)	166-50123
ALS-M50	M50	63	72	4	1 pcs.	Metal (ML)	166-50124
ALS-M63	M63	80	92	5	1 pcs.	Metal (ML)	166-50125

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Conduit Fittings & Accessories](#) category:

Click to view products by [HellermannTyton](#) manufacturer:

Other Similar products are found below :

[790-3006](#) [790-3150](#) [RE42](#) [LT20090](#) [LTB15045](#) [LTB20045](#) [LTB3890](#) [CGE195](#) [790-3154](#) [790-3008](#) [790-3014](#) [790-3020](#) [790-3152](#) [790-3156](#) [790-3166](#) [790-3002](#) [790-3162](#) [C2016-P](#) [C2012-P](#) [561-87BG11BLK](#) [1.511.1601.50](#) [55502675](#) [2676](#) [302-TB](#) [655241-000](#) [C17](#) [262-420](#) [TMC165-BR](#) [RBDP-BLA-20D236U](#) [RBDP-BLA-30D346U](#) [SPL25/075/M](#) [CN21](#) [SRN21](#) [3405B](#) [4975](#) [VC12516](#) [RC156-0500](#) [DM0523-1/2A](#) [1035A](#) [DMS0250-1A](#) [DMS0313-1A](#) [1040A](#) [1050A](#) [R1/8A](#) [DMPC0490-1/2A](#) [DMPC0521-1/2A](#) [DMPC0552-1/2A](#) [1070A](#) [R1/2A](#) [E1-7/8B](#)