



## HelaGuard Accessories


### • ALSS Stainless Steel Locknuts

The ALSS hexagonal locknut is used to secure fitting.



HelaGuard ALSS Stainless Steel Locknuts.

<b>MATERIAL</b>	Stainless Steel (SS316)
<b>Operating Temperature</b>	-100 °C to +400 °C



HelaGuard locknut

TYPE	Thread Size	A/F Nut (A/F3)	Across Corners (A/C)	Thickness (T)	Pack Cont.	Colour	Article-No.
ALSS-M16	M16	20	23	3.5	10 pcs.	Metal (ML)	166-50126
ALSS-M20	M20	24	28	3.5	10 pcs.	Metal (ML)	166-50127
ALSS-M25	M25	30	34	3.5	10 pcs.	Metal (ML)	166-50128
ALSS-M32	M32	38	43	4.5	2 pcs.	Metal (ML)	166-50129
ALSS-M40	M40	48	53	5.0	1 pcs.	Metal (ML)	166-50130
ALSS-M50	M50	60	65	6.0	1 pcs.	Metal (ML)	166-50131
ALSS-M63	M63	70	76	6.5	1 pcs.	Metal (ML)	166-50132

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Conduit Fittings & Accessories](#) category:*

*Click to view products by [HellermannTyton](#) manufacturer:*

Other Similar products are found below :

[790-3006](#) [790-3150](#) [RE42](#) [LT20090](#) [LTB15045](#) [LTB20045](#) [LTB3890](#) [CGE195](#) [790-3154](#) [790-3008](#) [790-3014](#) [790-3020](#) [790-3152](#) [790-3156](#) [790-3166](#) [790-3002](#) [790-3162](#) [C2016-P](#) [C2012-P](#) [561-87BG11BLK](#) [1.511.1601.50](#) [55502675](#) [2676](#) [302-TB](#) [655241-000](#) [C17](#) [262-420](#) [TMC165-BR](#) [RBDP-BLA-20D236U](#) [RBDP-BLA-30D346U](#) [SPL25/075/M](#) [CN21](#) [SRN21](#) [3405B](#) [4975](#) [VC12516](#) [RC156-0500](#) [DM0523-1/2A](#) [1035A](#) [DMS0250-1A](#) [DMS0313-1A](#) [1040A](#) [1050A](#) [R1/8A](#) [DMPC0490-1/2A](#) [DMPC0521-1/2A](#) [DMPC0552-1/2A](#) [1070A](#) [R1/2A](#) [E1-7/8B](#)