HellermannTyton

Specification Sheet

Part Number: 166-90209



Very high impact strength; recovers completely if crushed and provides excellent fatigue life.

Highly UV resistant; suitable for use in outdoor applications.

Offered in fine or course corrugated pitch.

Offered with or without slit; slit options offer easy access during installation and maintenance.

HelaGuard Non-Metallic Conduit, Std. Weight, 0.50" Dia, Nylon PA12, Black, 100 ft/Std. Reel

Article Number	166-90209
Туре	HG-HI0500
Color	Black (BK)
Quantity Per	reel
Product Description	A standard weight corrugated conduit made of PA12 nylon that offers superior impact resistance, making it ideal for protecting wire and cable bundles in conditions with continual movement or bending. This material is highly resistant to UV light, solvents and oils. Combine with HelaGuard Non-Metallic Fittings to achieve IP66 or greater protection against water, wind and dirt.
Short Description	HelaGuard Non-Metallic Conduit, Std. Weight, 0.50" Dia, Nylon PA12, Black, 100 ft/Std. Reel

Global Part Name

Length L (Imperial)	100.0
Length L (Metric)	30.5
Inner Diameter D (Imperial)	0.66
Inner Diameter D (Metric)	16.7
Outside Diameter OD (Imperial)	0.84
Outside Diameter OD (Metric)	21.2
Nominal Diameter (Imperial)	0.5
Nominal Diameter (Metric)	21
Material	Polyamide 12 (PA12)
Material Shortcut	PA12
Flammability	Self-extinguishing according to EN IEC 61386
Halogen Free	Yes
Operating Temperature	-58°F to +230°F (-50°C to +110°C)

Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	30.5
Customs Number	3926909988

© 2021 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Spiral Wraps, Sleeves, Tubing & Conduit category:

Click to view products by HellermannTyton manufacturer:

Other Similar products are found below :

601203-000 CTA-0053 8426-11 8445-7.5 8450 120-104-24 120-113-16B 120-116-1-1-09BE 120-116-1-1-09BF 120-116-1-1-09BP 120-116-1-1-12BE 120-116-1-1-12BP 120-116-1-1-20BP 120-116-1-1-32BE 120-117-40 120-123-06 120-123-10 120-123-14 120-123-16 120-125-12BL 120-125-12R 120-125-16 120-125-16R 120-125-16Y 120-125-20R 120-125-24Y 120-125-28 120-125-28R 120-125-32 120-125-32R 120-125-40 120-125-56 120-126-09 120-126-09BL 120-126-12 120-126-12BL 120-126-14 120-126-16 120-126-16BL 120-126-20 120-126-20BL 120-126-20R 120-126-24 120-126-28 120-126-32 120-126-40BL 120-126-52 120-126-52BL 120-104-12 120-104-20