HellermannTyton

Specification Sheet

Part Number: 167-00217

Living hinge allows harness serviceability and reduces assembly time. Internal ribs affix to exterior of tubing which prevents slipping during tension or movement.

Snap-on connection makes installations quick and easy and increases efficiencies in harness assembly.

Junction point outlets offer additional areas to branch off wires and prevents wires from sliding or accidental removal from tubing.

Improves aesthics of assembled wire harness.

No tools required to disassemble.



Hinged Convoluted Tubing Endclamp Fitting, 0.44", PP, Black, 5000/pkg

Article Number	167-00217

Type CTHC-EC4

Color Black (BK)

Quantity Per carton

Convoluted Loom fittings are single piece hinged connectors that simply snap-on over slit and unslit loom tubing to secure wire branchouts or, connect different tubing diameters. The unique wrap around design makes installation easier and more efficient, while the unique junction points make easy branchouts that keep wires from sliding out of the tubing and eliminates need for secondary taping operation. The polypropylene material creates a sleek assembly and improves the appearance of the entire wiring assembly.

Short Description

Hinged Convoluted Tubing Endclamp Fitting, 0.44", PP, Black,

5000/pkg

Global Part Name

CTHC-EC4-PP-BK

Variant

Clamps

Diameter D (Imperial)

0.44

Diameter D (Metric)

11.2

Material

Polypropylene (PP)

Material Shortcut

PP

Flammability

UL 94 HB

Halogen Free

Yes

Operating Temperature

-4°F to +194°F (-20°C to +90°C)

ROHS Compliant

Yes

Package Quantity (Imperial) 5000

Package Quantity (Metric) 5000

Customs Number 3926909988

© 2022 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Spiral Wraps, Sleeves, Tubing & Conduit category:

Click to view products by HellermannTyton manufacturer:

Other Similar products are found below:

601203-000 CTA-0053 8426-11 8445-7.5 8450 120-104-24 120-113-16B 120-116-1-1-09BE 120-116-1-1-09BF 120-116-1-1-09BP 120
116-1-1-12BE 120-116-1-1-12BP 120-116-1-1-20BP 120-116-1-1-32BE 120-117-40 120-123-06 120-123-10 120-123-14 120-123-16 120
125-12BL 120-125-12R 120-125-16 120-125-16R 120-125-16Y 120-125-20R 120-125-24Y 120-125-28 120-125-28R 120-125-32 120
125-32R 120-125-40 120-125-56 120-126-09 120-126-09BL 120-126-12 120-126-12BL 120-126-14 120-126-16 120-126-16BL 120-126
20 120-126-20BL 120-126-20R 120-126-24 120-126-28 120-126-32 120-126-40BL 120-126-52 120-126-52BL 120-104-12 120-104-20