



Heat shrinkable tubing 2:1 - flexible and coloured

HFT-A - self extinguishing

This high performance thin wall tubing is used extensively for electrical and mechanical protection. It is also well proven for sleeve marking to identify wiring circuits.

Features and benefits

- Flexible heat shrink tubing
- Fast shrinking, easy handling, good mechanical strength
- Wide range of colours
- Internal diameters up to 101.6 mm (4 inches)
- UL-224 ,CSA listed and VG approved



HFT-A conforms to major standards (VG) used in all Defence industries.



Standard sizes available in colours black, red, blue, yellow, white and green-yellow.

MATERIAL	Polyolefin, cross-linked (PO-X)
Shrink Ratio	2:1
Operating Temperature	-55 °C to +135 °C
Min. Shrink Temperature	+100 °C
Longitudinal change after shrinkage	+5 %/-10 %
Dielectric Strength	20 kV/mm according to IEC 684 P2
Flammability	self-extinguishing, UL224 VW-1

RoHS ✓




Heat Shrinkable Tubing 2:1

TYPE	Supplied Ø D min.	Size (imperial)	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Designation as per VG-Norm	Tools	Article-No.
HFT-A-1.2/0.6	1.2	3/64 "	0.6	0.40	400 m	Black (BK)	VG 95343 T05 A 001 A	30-32	305-01200
	1.2	3/64 "	0.6	0.40	400 m	Blue (BU)	VG 95343 T05 A 001 G	30-32	305-01206
	1.2	3/64 "	0.6	0.40	400 m	Red (RD)	VG 95343 T05 A 001 C	30-32	305-01202
	1.2	3/64 "	0.6	0.40	400 m	White (WH)	VG 95343 T05 A 001 L	30-32	305-01209
	1.2	3/64 "	0.6	0.40	400 m	Yellow (YE)	VG 95343 T05 A 001 E	30-32	305-01204
HFT-A-1.6/0.8	1.6	1/16 "	0.8	0.40	400 m	Black (BK)	VG 95343 T05 A 002 A	30-32	305-01600
	1.6	1/16 "	0.8	0.40	400 m	Blue (BU)	VG 95343 T05 A 002 G	30-32	305-01606
	1.6	1/16 "	0.8	0.40	400 m	Red (RD)	VG 95343 T05 A 002 C	30-32	305-01602
	1.6	1/16 "	0.8	0.40	400 m	White (WH)	VG 95343 T05 A 002 L	30-32	305-01609
	1.6	1/16 "	0.8	0.40	400 m	Yellow (YE)	VG 95343 T05 A 002 E	30-32	305-01604
HFT-A-2.4/1.2	2.4	3/32 "	1.2	0.50	100 m	Blue (BU)	VG 95343 T05 A 003 G	30-32	305-02406
	2.4	3/32 "	1.2	0.50	100 m	Red (RD)	VG 95343 T05 A 003 C	30-32	305-02402
	2.4	3/32 "	1.2	0.50	100 m	White (WH)	VG 95343 T05 A 003 L	30-32	305-02409
	2.4	3/32 "	1.2	0.50	100 m	Yellow (YE)	VG 95343 T05 A 003 E	30-32	305-02404
	2.4	3/32 "	1.2	0.50	400 m	Black (BK)	VG 95343 T05 A 003 A	30-32	305-02400

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.



Heat shrinkable tubing 2:1 - flexible and coloured

HFT-A - self extinguishing



TYPE	Supplied Ø D min.	Size (imperial)	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Designation as per VG-Norm	Tools	Article-No.
HFT-A-3.2/1.6	3.2	1/8 "	1.6	0.50	100 m	Blue (BU)	VG 95343 T05 A 004 G	30-32	305-03206
	3.2	1/8 "	1.6	0.50	100 m	Green-Yellow (GNYE)	VG 95343 T05 A 004 N	30-32	305-03245
	3.2	1/8 "	1.6	0.50	100 m	Red (RD)	VG 95343 T05 A 004 C	30-32	305-03202
	3.2	1/8 "	1.6	0.50	100 m	White (WH)	VG 95343 T05 A 004 L	30-32	305-03209
	3.2	1/8 "	1.6	0.50	100 m	Yellow (YE)	VG 95343 T05 A 004 E	30-32	305-03204
	3.2	1/8 "	1.6	0.50	400 m	Black (BK)	VG 95343 T05 A 004 A	30-32	305-03200
HFT-A-4.8/2.4	4.8	3/16 "	2.4	0.50	75 m	Blue (BU)	VG 95343 T05 A 005 G	30-32	305-04806
	4.8	3/16 "	2.4	0.50	75 m	Green-Yellow (GNYE)	VG 95343 T05 A 005 N	30-32	305-04845
	4.8	3/16 "	2.4	0.50	75 m	Red (RD)	VG 95343 T05 A 005 C	30-32	305-04802
	4.8	3/16 "	2.4	0.50	75 m	White (WH)	VG 95343 T05 A 005 L	30-32	305-04809
	4.8	3/16 "	2.4	0.50	75 m	Yellow (YE)	VG 95343 T05 A 005 E	30-32	305-04804
	4.8	3/16 "	2.4	0.50	300 m	Black (BK)	VG 95343 T05 A 005 A	30-32	305-04800
HFT-A-6.4/3.2	6.4	1/4 "	3.2	0.60	75 m	Blue (BU)	VG 95343 T05 A 006 G	30-32	305-06406
	6.4	1/4 "	3.2	0.60	75 m	Green-Yellow (GNYE)	VG 95343 T05 A 006 N	30-32	305-06445
	6.4	1/4 "	3.2	0.60	75 m	Red (RD)	VG 95343 T05 A 006 C	30-32	305-06402
	6.4	1/4 "	3.2	0.60	75 m	White (WH)	VG 95343 T05 A 006 L	30-32	305-06409
	6.4	1/4 "	3.2	0.60	75 m	Yellow (YE)	VG 95343 T05 A 006 E	30-32	305-06404
	6.4	1/4 "	3.2	0.60	300 m	Black (BK)	VG 95343 T05 A 006 A	30-32	305-06400
HFT-A-9.5/4.8	9.5	3/8 "	4.8	0.60	50 m	Blue (BU)	VG 95343 T05 A 007 G	30-32	305-09506
	9.5	3/8 "	4.8	0.60	50 m	Green-Yellow (GNYE)	VG 95343 T05 A 007 N	30-32	305-09545
	9.5	3/8 "	4.8	0.60	50 m	Red (RD)	VG 95343 T05 A 007 C	30-32	305-09502
	9.5	3/8 "	4.8	0.60	50 m	White (WH)	VG 95343 T05 A 007 L	30-32	305-09509
	9.5	3/8 "	4.8	0.60	50 m	Yellow (YE)	VG 95343 T05 A 007 E	30-32	305-09504
	9.5	3/8 "	4.8	0.60	150 m	Black (BK)	VG 95343 T05 A 007 A	30-32	305-09500
HFT-A-12.7/6.4	12.7	1/2 "	6.4	0.60	50 m	Blue (BU)	VG 95343 T05 A 008 G	30-32	305-12706
	12.7	1/2 "	6.4	0.60	50 m	Green-Yellow (GNYE)	VG 95343 T05 A 008 N	30-32	305-12745
	12.7	1/2 "	6.4	0.60	50 m	Red (RD)	VG 95343 T05 A 008 C	30-32	305-12702
	12.7	1/2 "	6.4	0.60	50 m	White (WH)	VG 95343 T05 A 008 L	30-32	305-12709
	12.7	1/2 "	6.4	0.60	50 m	Yellow (YE)	VG 95343 T05 A 008 E	30-32	305-12704
	12.7	1/2 "	6.4	0.60	100 m	Black (BK)	VG 95343 T05 A 008 A	30-32	305-12700

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.



Heat shrinkable tubing 2:1 - flexible and coloured

HFT-A - self extinguishing



TYPE	Supplied Ø D min.	Size (imperial)	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Designation as per VG-Norm	Tools	Article-No.
HFT-A-19.0/9.5	19.0	3/4 "	9.5	0.80	25 m	Blue (BU)	VG 95343 T05 A 009 G	30-32	305-19006
	19.0	3/4 "	9.5	0.80	25 m	Green-Yellow (GNYE)	VG 95343 T05 A 009 N	30-32	305-19045
	19.0	3/4 "	9.5	0.80	25 m	Red (RD)	VG 95343 T05 A 009 C	30-32	305-19002
	19.0	3/4 "	9.5	0.80	25 m	White (WH)	VG 95343 T05 A 009 L	30-32	305-19009
	19.0	3/4 "	9.5	0.80	25 m	Yellow (YE)	VG 95343 T05 A 009 E	30-32	305-19004
	19.0	3/4 "	9.5	0.80	50 m	Black (BK)	VG 95343 T05 A 009 A	30-32	305-19000
HFT-A-25.4/12.7	25.4	1 "	12.7	0.90	25 m	Blue (BU)	VG 95343 T05 A 010 G	30-32	305-25406
	25.4	1 "	12.7	0.90	25 m	Green-Yellow (GNYE)	VG 95343 T05 A 010 N	30-32	305-25445
	25.4	1 "	12.7	0.90	25 m	Red (RD)	VG 95343 T05 A 010 C	30-32	305-25402
	25.4	1 "	12.7	0.90	25 m	White (WH)	VG 95343 T05 A 010 L	30-32	305-25409
	25.4	1 "	12.7	0.90	25 m	Yellow (YE)	VG 95343 T05 A 010 E	30-32	305-25404
	25.4	1 "	12.7	0.90	50 m	Black (BK)	VG 95343 T05 A 010 A	30-32	305-25400
HFT-A-38.0/19.0	38.0	1-1/2 "	19.0	1.00	50 m	Black (BK)	VG 95343 T05 A 011 A	30-32	305-38100
	38.0	1-1/2 "	19.0	1.00	50 m	Blue (BU)	VG 95343 T05 A 011 G	30-32	305-38106
	38.0	1-1/2 "	19.0	1.00	50 m	Green-Yellow (GNYE)	VG 95343 T05 A 011 N	30-32	305-38145
	38.0	1-1/2 "	19.0	1.00	50 m	Red (RD)	VG 95343 T05 A 011 C	30-32	305-38102
	38.0	1-1/2 "	19.0	1.00	50 m	White (WH)	VG 95343 T05 A 011 L	30-32	305-38109
	38.0	1-1/2 "	19.0	1.00	50 m	Yellow (YE)	VG 95343 T05 A 011 E	30-32	305-38104
HFT-A-50.8/25.4	50.8	2 "	25.4	1.10	35 m	Black (BK)	VG 95343 T05 A 012 A	30-32	305-50800
	50.8	2 "	25.4	1.10	35 m	Blue (BU)	VG 95343 T05 A 012 G	30-32	305-50806
	50.8	2 "	25.4	1.10	35 m	Red (RD)	VG 95343 T05 A 012 C	30-32	305-50802
	50.8	2 "	25.4	1.10	35 m	White (WH)	VG 95343 T05 A 012 L	30-32	305-50809
	50.8	2 "	25.4	1.10	35 m	Yellow (YE)	VG 95343 T05 A 012 E	30-32	305-50804
HFT-A-76.0/38.0	76.0	3 "	38.0	1.30	25 m	Black (BK)	VG 95343 T05 A 013 A	-	305-76200
	76.0	3 "	38.0	1.30	25 m	Blue (BU)	VG 95343 T05 A 013 G	-	305-76206
	76.0	3 "	38.0	1.30	25 m	Red (RD)	VG 95343 T05 A 013 C	-	305-76202
	76.0	3 "	38.0	1.30	25 m	White (WH)	VG 95343 T05 A 013 L	-	305-76209
	76.0	3 "	38.0	1.30	25 m	Yellow (YE)	VG 95343 T05 A 013 E	-	305-76204
HFT-A-101.6/50.8	101.6	4 "	50.8	1.40	25 m	Black (BK)	VG 95343 T05 A 014 A	-	305-91600
	101.6	4 "	50.8	1.40	25 m	Blue (BU)	VG 95343 T05 A 014 G	-	305-91606
	101.6	4 "	50.8	1.40	25 m	Red (RD)	VG 95343 T05 A 014 C	-	305-91602
	101.6	4 "	50.8	1.40	25 m	White (WH)	VG 95343 T05 A 014 L	-	305-91609
	101.6	4 "	50.8	1.40	25 m	Yellow (YE)	VG 95343 T05 A 014 E	-	305-91604

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:

Click to view products by [HellermannTyton](#) manufacturer:

Other Similar products are found below :

[5685710001](#) [CR9960-000](#) [5734012004](#) [607381P039](#) [611112-000](#) [6284592002](#) [CX4711-000](#) [CZ1420-000](#) [D-306-38](#) [770-006S302](#) [770-010Y106W1](#) [770-018S103](#) [770-018S202W1](#) [770-018S205W1](#) [770-020S704W1](#) [770-020S705](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [790-3012](#) [MHHT-4-15K2-G-104](#) [8003012003](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#) [MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-3/32-6-SP](#) [MIL-LT-3/4-4-STK](#) [MIL-LT-3/4-6-SP](#) [839602-000](#) [8423-6](#) [FP301-116-48"-Clear](#) [FP301-12-6"-Clear](#) [FP301-1/4-48"-White-Hdr](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-Hdr](#) [FP301-34-48"-Green-Hdr](#) [912229N002](#) [R280637030](#) [HDCW-5515-1000](#) [HDT-0300-48A-BLACK](#) [HDT-0400-48A-Black](#) [HDT-0800-48A-RED](#) [HDT1100-48A-BLK](#) [HDT1500-48A-BLK](#) [HDT-2000-48A-Black](#) [RHW-70/20-1200/ADH-0](#) [DWP-125-0.450-4-55MM-CS879](#)