



Heat shrinkable tubing 3:1 - Flame retardant

TA37 - thin wall adhesive lined

TA37 shrink tubing has a low smoke index and excellent flame retardant properties to meet strict fire security standards in electrical insulation.

Features and benefits

- Thin wall adhesive lined heat shrink tubing
- Halogen Free
- Flame Retarded
- Combination of these three (halogen free, adhesive lined and flame retarded) product properties is unique




TA37 - adhesive lined tubing for safety sensitive areas.

MATERIAL	Polyolefin, cross-linked (PO-X)
Shrink Ratio	3:1
Operating Temperature	-40 °C to +105 °C
Min. Shrink Temperature	+150 °C
Softening Point Adhesive	+85 °C
Longitudinal change after shrinkage	-15 % max.
Flammability	self-extinguishing



Mainly used in railway applications.



Heat Shrinkable Tubing 3:1 with adhesive



One Step to the Web!

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Length (L)	Colour	Tools	Article-No.
TA37 3-1	3.0	1.0	0.95	1.2 m	Black (BK)	30-32	315-13000
TA37 4.5-1.5	4.5	1.5	1.10	1.2 m	Black (BK)	30-32	315-13001
TA37 6-2	6.0	2.0	1.20	1.2 m	Black (BK)	30-32	315-13002
TA37 9-3	9.0	3.0	1.30	1.2 m	Black (BK)	30-32	315-13003
TA37 12-4	12.0	4.0	1.40	1.2 m	Black (BK)	30-32	315-13004
TA37 19-6	19.0	6.0	1.80	1.2 m	Black (BK)	30-32	315-13005
TA37 24-8	24.0	8.0	2.50	1.2 m	Black (BK)	30-32	315-13006
TA37 40-13	40.0	13.0	2.50	1.2 m	Black (BK)	30-32	315-13007
TA37 50-19	50.0	19.0	4.00	1.2 m	Black (BK)	30-32	315-13008
TA37 75-25	75.0	25.0	3.00	1.2 m	Black (BK)	-	315-13009
TA37 120-45	120.0	45.0	4.00	1.2 m	Black (BK)	-	315-13011

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

EN 45545-2

For product specific approvals and specifications please refer to the Appendix.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:

Click to view products by [HellermannTyton](#) manufacturer:

Other Similar products are found below :

[5685710001](#) [CR9960-000](#) [5734012004](#) [607381P039](#) [611112-000](#) [6284592002](#) [CX4711-000](#) [CZ1420-000](#) [D-306-38](#) [770-006S302](#) [770-010Y106W1](#) [770-018S103](#) [770-018S202W1](#) [770-018S205W1](#) [770-020S704W1](#) [770-020S705](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [790-3012](#) [MHHT-4-15K2-G-104](#) [8003012003](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#) [MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-3/32-6-SP](#) [MIL-LT-3/4-4-STK](#) [MIL-LT-3/4-6-SP](#) [839602-000](#) [8423-6](#) [FP301-116-48"-Clear](#) [FP301-12-6"-Clear](#) [FP301-1/4-48"-White-Hdr](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-Hdr](#) [FP301-34-48"-Green-Hdr](#) [912229N002](#) [R280637030](#) [HDCW-5515-1000](#) [HDT-0300-48A-BLACK](#) [HDT-0400-48A-Black](#) [HDT-0800-48A-RED](#) [HDT1100-48A-BLK](#) [HDT1500-48A-BLK](#) [HDT-2000-48A-Black](#) [RHW-70/20-1200/ADH-0](#) [DWP-125-0.450-4-55MM-CS879](#)