



Heat shrinkable tubing adhesive lined - 1.2 m lengths

TA32/TA42 is designed for environmental sealing and electrical insulation of wire splices, terminations and components.

Features and benefits

- Thin wall adhesive-lined heat shrink tubing
- Highly flame retardant
- Outer wall conforms to UL224
- High shrink ratio



TA32 and TA42 are UL224 listed adhesive lined tubing. Available in 3:1 and 4:1 shrink ratio.



Cut lengths available on request. Please contact us!

MATERIAL	Polyolefin, cross-linked (PO-X)
Operating Temperature	-55 °C to +125 °C
Min. Shrink Temperature	+110 °C
Softening Point Adhesive	+110 °C
Longitudinal change after shrinkage	-15 % max.
Dielectric Strength	15 kV/mm according to IEC 684 P2
Flammability	UL224 VW-1

TA32 - thin wall, 3:1 shrink ratio



Heat Shrinkable Tubing 3:1 with adhesive



TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Length (L)	Colour	Shrink Ratio	Tools	Article-No.
TA32-3/1	3.2	0.6	0.95	1.2 m	Black (BK)	3:1	30-32	318-30300
TA32 4.5/1.5	4.5	1.5	1.10	1.2 m	Black (BK)	3:1	30-32	318-30450
TA32-6/2	6.0	2.0	1.20	1.2 m	Black (BK)	3:1	30-32	318-30600
TA32-9/3	9.0	3.0	1.30	1.2 m	Black (BK)	3:1	30-32	318-30900
TA32-12/4	12.0	4.0	1.40	1.2 m	Black (BK)	3:1	30-32	318-31200
TA32-19/6	19.0	6.0	1.80	1.2 m	Black (BK)	3:1	30-32	318-31900
TA32-24/8	24.0	8.0	2.50	1.2 m	Black (BK)	3:1	30-32	318-32400
TA32-40/13	40.0	13.0	2.50	1.2 m	Black (BK)	3:1	30-32	318-34000

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

Recommended Tools			
	30	31	32
	H5002	H5004	E4500
	568	568	567

For more information on toolings please refer to the Application Tooling chapter.



For product specific approvals and specifications please refer to the Appendix.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:

Click to view products by [HellermannTyton](#) manufacturer:

Other Similar products are found below :

[5685710001](#) [CR9960-000](#) [5734012004](#) [607381P039](#) [611112-000](#) [6284592002](#) [CX4711-000](#) [CZ1420-000](#) [D-306-38](#) [770-006S302](#) [770-010Y106W1](#) [770-018S103](#) [770-018S202W1](#) [770-018S205W1](#) [770-020S704W1](#) [770-020S705](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [790-3012](#) [MHHT-4-15K2-G-104](#) [8003012003](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#) [MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-3/32-6-SP](#) [MIL-LT-3/4-4-STK](#) [MIL-LT-3/4-6-SP](#) [839602-000](#) [8423-6](#) [FP301-116-48"-Clear](#) [FP301-12-6"-Clear](#) [FP301-1/4-48"-White-Hdr](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-Hdr](#) [FP301-34-48"-Green-Hdr](#) [912229N002](#) [R280637030](#) [HDCW-5515-1000](#) [HDT-0300-48A-BLACK](#) [HDT-0400-48A-Black](#) [HDT-0800-48A-RED](#) [HDT1100-48A-BLK](#) [HDT1500-48A-BLK](#) [HDT-2000-48A-Black](#) [RHW-70/20-1200/ADH-0](#) [DWP-125-0.450-4-55MM-CS879](#)