## HellermannTyton



## Technical Data

HA47-HT - thick wall adhesive lined high temperature Heat Shrinkable Tubing up to 4:1 - 1 m lengths 08.03.2021

HA47-HT 16/4		
Article Number 321-25001		ld
Material:	Polyolefin, chemically cross-linked (PO-X)	
Colour:	Black (BK)	
Supplied Ø D min.:	16.0 mm	
Recov. Ø d max.:	4.0 mm	
Wall (WT):	2.4 mm	
Shrink Ratio:	up to 4:1	
Longitudinal Change After Shrinkage:	+/-10 % max	
Min. Shrink Temperature - °C:	+120 °C	
		Test Method
Operating Temperature - °C:	-55 °C to +110 °C	
Dielectric Strength:	20 kV/mm	ASTM D2671
Tensile Strength:	14 MPa	
Elongation at break:	400%	

## RoHS

We assume no responsibility that the Product will be used for the intended purpose, this is beyond our control. It's up to the customer to check the suitability for a specific application by means of tests. Technical changes and errors reserved

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Shrink Tubing and Sleeves category:

Click to view products by HellermannTyton manufacturer:

Other Similar products are found below :

 5685710001
 CR9960-000
 5734012004
 607381P039
 611112-000
 6284592002
 CX4711-000
 CZ1420-000
 D-306-38
 770-006S302
 770 

 010Y106W1
 770-018S103
 770-018S202W1
 770-018S205W1
 770-020S705
 MFP-1/4"-Clear
 MFP-3/64"-Clear
 790-3012

 MHHT-4-15K2-G-104
 8003012003
 MIL-LT-1/2-4-SP
 MIL-LT-1/2-9-STK
 MIL-LT-1/2-2-STK
 MIL-LT-3/-0-SP
 MIL-LT-3/32-0-SP

 MIL-LT-3/32-6-SP
 MIL-LT-3/4-4-STK
 MIL-LT-3/4-6-SP
 839602-000
 8423-6
 FP301-116-48"-Clear
 FP301-12-6"-Clear
 FP301-1/4-48" 

 White-Hdr
 FP301-18-48"-Black-Hdr
 FP301-1/8-6"-Black
 FP301-18-6"-Black-Bulk
 FP301-316-48"-Blue-Hdr
 912229N002
 R280637030

 HDCW-5515-1000
 HDT-0300-48A-BLACK
 HDT-0400-48A-Black
 HDT-0800-48A-RED
 HDT1100-48A-BLK
 HDT1500-48A-BLK
 HDT-2000-48A-BLK
 HDT-2000/ADH-0
 DWP-125-0.450-4-55MM-CS879
 156082-000