



Technical Data

08.03.2021

HA47-HT - thick wall adhesive lined high temperature Heat Shrinkable Tubing up to 4:1 - 1 m lengths

HA47-HT 48/12

Article Number 321-25004

Material: Polyolefin, chemically cross-linked (PO-X)

Colour: Black (BK)

Supplied Ø D min.:

Recov. Ø d max.:

12.0 mm

Wall (WT):

4.1 mm

Shrink Ratio:

Longitudinal Change After Shrinkage:

4**-10 % max

Min. Shrink Temperature - °C:

+120 °C

Test Method

Operating Temperature - °C: -55 °C to +110 °C

Dielectric Strength: 20 kV/mm ASTM D2671

Tensile Strength: 14 MPa Elongation at break: 400%

RoHS

We assume no responsibility that the Product will be used for the intended purpose, this is beyond our control. It's up to the customer to check the suitability for a specific application by means of tests. Technical changes and errors reserved

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Shrink Tubing and Sleeves category:

Click to view products by HellermannTyton manufacturer:

Other Similar products are found below:

5685710001 CR9960-000 5734012004 607381P039 611112-000 6284592002 CX4711-000 CZ1420-000 D-306-38 770-006S302 770-010Y106W1 770-018S103 770-018S202W1 770-018S205W1 770-020S704W1 770-020S705 MFP-1/4"-Clear MFP-3/64"-Clear 790-3012 MHHT-4-15K2-G-104 8003012003 MIL-LT-1-1/2-4-SP MIL-LT-1-1/2-9-STK MIL-LT-1/2-2-STK MIL-LT-3-0-SP MIL-LT-3/32-0-SP MIL-LT-3/32-6-SP MIL-LT-3/4-4-STK MIL-LT-3/4-6-SP 839602-000 8423-6 FP301-116-48"-Clear FP301-12-6"-Clear FP301-1/4-48"-White-Hdr FP301-18-48"-Black-Hdr FP301-1/8-6"-Black FP301-18-6"-Black-Bulk FP301-316-48"-Blue-Hdr 912229N002 R280637030 HDCW-5515-1000 HDT-0300-48A-BLACK HDT-0400-48A-Black HDT-0800-48A-RED HDT1100-48A-BLK HDT1500-48A-BLK HDT-2000-48A-Black RHW-70/20-1200/ADH-0 DWP-125-0.450-4-55MM-CS879 156082-000