



### Shrinkable markers "Continuous Tube", thermal transfer

#### THTT – 2:1 Aerospace High Temperature

THTT is a 2:1 high temperature, flame retardant heat shrink marker supplied in continuous tube and on convenient reels that allows printing on both sides if required. The printed marker is ideal for use in applications where high temperature and exposure to aggressive solutions are found. The tubing has been especially prepared so that the print performance is excellent at all times using HellermannTyton's printer range. A standard heat gun with reflector is used to shrink the sleeves onto the wire or cable to achieve a permanent mark. In addition it is possible to either perforate the tubing at pre-determined lengths or fully sever the markers.

The material is also especially formulated to be printable with laser beam printers.

#### Features and benefits

- Shrink ratio 2:1
- PVDFX high temperature tube
- Thermal transfer or laser beam printable
- Available in white and black as standard
- Good mechanical strength and highly flexible
- Delivery in convenient storage boxes



THTT - High temperature tube in black and white.

<b>MATERIAL</b>	Polyvinylidene Fluoride cross-linked (PVDFX)
<b>Operating Temperature</b>	-55 °C to +225 °C
<b>Min. Shrink Temperature</b>	+120 °C
<b>Shrink Ratio</b>	2:1
<b>Recommended Ribbon Type</b>	TTRHT
<b>Thermal Transfer Printer</b>	TT430, TT4030, TrakMark DS



For size matrix please refer to page 439.




TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Pack Cont.	Colour	Article-No.
THTT24BK	2.4	1.2	0.41	110 m	Black (BK)	551-41109
THTT24WH	2.4	1.2	0.41	110 m	White (WH)	551-41100
THTT32BK	3.2	1.6	0.27	110 m	Black (BK)	551-41110
THTT32WH	3.2	1.6	0.27	110 m	White (WH)	551-41101
THTT48BK	4.8	2.4	0.27	110 m	Black (BK)	551-41111
THTT48WH	4.8	2.4	0.27	110 m	White (WH)	551-41102
THTT64BK	6.4	3.2	0.33	110 m	Black (BK)	551-41112
THTT64WH	6.4	3.2	0.33	110 m	White (WH)	551-41103
THTT95BK	9.5	4.8	0.33	72 m	Black (BK)	551-41113
THTT95WH	9.5	4.8	0.33	72 m	White (WH)	551-41104
THTT127BK	12.7	6.4	0.33	54 m	Black (BK)	551-41114

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.



### Shrinkable markers "Continuous Tube", thermal transfer

**THTT – 2:1 Aerospace High Temperature**



TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Pack Cont.	Colour	Article-No.
THTT127WH	12.7	6.4	0.33	54 m	White (WH)	551-41105
THTT190BK	19.0	9.5	0.43	26 m	Black (BK)	551-41115
THTT190WH	19.0	9.5	0.43	26 m	White (WH)	551-41106
THTT254BK	25.4	12.7	0.48	26 m	Black (BK)	551-41116
THTT254WH	25.4	12.7	0.48	26 m	White (WH)	551-41107
THTT381BK	38.1	19.1	0.50	10 m	Black (BK)	551-41117
THTT381WH	38.1	19.1	0.50	10 m	White (WH)	551-41108

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Labels & Markers](#) category:*

*Click to view products by [HellermannTyton](#) manufacturer:*

Other Similar products are found below :

[89078GBEST](#) [89080GBEPR](#) [PCL025-4](#) [5761-2SF](#) [CS1836-000](#) [CS8626-000](#) [CU6337-000](#) [CU6343-000](#) [CWD01-0](#) [CWD012-0](#) [CWD012-7](#)  
[CWD015-3](#) [CWD015-7](#) [CWD02-0](#) [CWD02-3](#) [CWD02-4](#) [CWD02-6](#) [CWD02-8](#) [CWD02-A](#) [CWD02-D](#) [CWD02-H](#) [CWD02-K](#) [CWD02-L](#)  
[CWD02-M](#) [CWD02-P](#) [CWD02-Q](#) [CWD02-R](#) [CWD02-U](#) [CWD02-W](#) [CWD02-Y](#) [CWD03-+](#) [CWD03-0](#) [CWD03-P](#) [CWD06-0](#) [CWD06-8](#)  
[CWD06-9](#) [CWD06-L](#) [CWD06-N](#) [CWD09-0](#) [CWD09-5](#) [CWD09-7](#) [6806810001](#) [CY8610-000](#) [D04690-000](#) [7-1768041-1](#) [726631-1](#) [739253-000](#) [F24597-000](#) [750-1412](#) [F83400-000](#)