

Shrinkable markers "Ladder Style", thermal transfer

TLFX DS – 2:1 Rail Limited Fire Hazard "Ladder Style"

TLFX DS is a halogen free European rail approved 2:1 heat shrink marker material supplied pre-cut and formatted into a convenient "ladder" system. Special material properties show low smoke propagation, density and toxicity. This pre-cut format not only allows printing on both sides of the marker but the user can also easily choose and pick each required marker. Special material properties show low smoke propagation, density and toxicity. The tubing has been especially prepared so that the print performance is excellent at all times using HellermannTyton's printer range.

Features and benefits

- Shrink ratio 2:1
- Halogen Free
- Low smoke propagation, density and toxicity
- High Oxygen Index value (35.4%)
- 50 mm, 25 mm and 16 mm pre-cut marker options as standard, other lengths available on request
- Available in yellow or white
- Cable range 38.1 mm to 1.2 mm
- Delivery in convenient storage boxes



Shrinkable rail approved markers TLFX DS.

| | |
|---------------------------------|---------------------------------|
| MATERIAL | Polyolefin, cross-linked (PO-X) |
| Operating Temperature | -55 °C to +105 °C |
| Min. Shrink Temperature | +100 °C |
| Shrink Ratio | 2:1 |
| Recommended Ribbon Type | TTDTHOUT |
| Thermal Transfer Printer | TT430, TT4030, TrakMark DS |




One Step to the Web!

HF ✓

LFH ✓

RoHS ✓



For size matrix please refer to page 439.

| TYPE | Supplied Ø D min. | Recov. Ø d max. | Length (L) | Wall (WT) | Pack Cont. | Colour | Article-No. |
|-----------------|-------------------|-----------------|------------|-----------|-------------|-------------|-------------|
| TLFX24DS-2x25WH | 2.4 | 1.2 | 25.0 | 0.52 | 10,000 pcs. | White (WH) | 553-60020 |
| TLFX24DS-2x25YE | 2.4 | 1.2 | 25.0 | 0.52 | 10,000 pcs. | Yellow (YE) | 553-60029 |
| TLFX24DS-1x50WH | 2.4 | 1.2 | 50.0 | 0.52 | 5,000 pcs. | White (WH) | 553-60000 |
| TLFX24DS-1x50YE | 2.4 | 1.2 | 50.0 | 0.52 | 5,000 pcs. | Yellow (YE) | 553-60010 |
| TLFX32DS-2x25WH | 3.2 | 1.6 | 25.0 | 0.64 | 10,000 pcs. | White (WH) | 553-60021 |
| TLFX32DS-2x25YE | 3.2 | 1.6 | 25.0 | 0.64 | 10,000 pcs. | Yellow (YE) | 553-60030 |
| TLFX32DS-1x50WH | 3.2 | 1.6 | 50.0 | 0.64 | 5,000 pcs. | White (WH) | 553-60001 |
| TLFX32DS-1x50YE | 3.2 | 1.6 | 50.0 | 0.64 | 5,000 pcs. | Yellow (YE) | 553-60011 |
| TLFX48DS-2x25WH | 4.8 | 2.4 | 25.0 | 0.64 | 10,000 pcs. | White (WH) | 553-60022 |
| TLFX48DS-2x25YE | 4.8 | 2.4 | 25.0 | 0.64 | 10,000 pcs. | Yellow (YE) | 553-60031 |
| TLFX48DS-1x50WH | 4.8 | 2.4 | 50.0 | 0.64 | 5,000 pcs. | White (WH) | 553-60002 |

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

EN 45545-2

ASTM


NF F

UNI CEI

For product specific approvals and specifications please refer to the Appendix.

Shrinkable markers "Ladder Style", thermal transfer

TLFX DS – 2:1 Rail Limited Fire Hazard "Ladder Style"



| TYPE | Supplied Ø D min. | Recov. Ø d max. | Length (L) | Wall (WT) | Pack Cont. | Colour | Article-No. |
|------------------|----------------------|--------------------|---------------|--------------|---------------|-------------|-------------|
| TLFX48DS-1x50YE | 4.8 | 2.4 | 50.0 | 0.64 | 5,000 pcs. | Yellow (YE) | 553-60012 |
| TLFX64DS-2x25WH | 6.4 | 3.2 | 25.0 | 0.73 | 6,000 pcs. | White (WH) | 553-60023 |
| TLFX64DS-2x25YE | 6.4 | 3.2 | 25.0 | 0.73 | 6,000 pcs. | Yellow (YE) | 553-60032 |
| TLFX64DS-1x50WH | 6.4 | 3.2 | 50.0 | 0.73 | 3,000 pcs. | White (WH) | 553-60003 |
| TLFX64DS-1x50YE | 6.4 | 3.2 | 50.0 | 0.73 | 3,000 pcs. | Yellow (YE) | 553-60013 |
| TLFX95DS-2x25WH | 9.5 | 4.8 | 25.0 | 0.70 | 5,000 pcs. | White (WH) | 553-60024 |
| TLFX95DS-2x25YE | 9.5 | 4.8 | 25.0 | 0.70 | 5,000 pcs. | Yellow (YE) | 553-60033 |
| TLFX95DS-1x50WH | 9.5 | 4.8 | 50.0 | 0.70 | 2,500 pcs. | White (WH) | 553-60004 |
| TLFX95DS-1x50YE | 9.5 | 4.8 | 50.0 | 0.70 | 2,500 pcs. | Yellow (YE) | 553-60014 |
| TLFX127DS-2x25WH | 12.7 | 6.4 | 25.0 | 0.70 | 3,000 pcs. | White (WH) | 553-60025 |
| TLFX127DS-2x25YE | 12.7 | 6.4 | 25.0 | 0.70 | 3,000 pcs. | Yellow (YE) | 553-60034 |
| TLFX127DS-1x50WH | 12.7 | 6.4 | 50.0 | 0.70 | 1,500 pcs. | White (WH) | 553-60005 |
| TLFX127DS-1x50YE | 12.7 | 6.4 | 50.0 | 0.70 | 1,500 pcs. | Yellow (YE) | 553-60015 |
| TLFX190DS-2x25WH | 19.0 | 9.5 | 25.0 | 0.78 | 3,000 pcs. | White (WH) | 553-60026 |
| TLFX190DS-2x25YE | 19.0 | 9.5 | 25.0 | 0.78 | 3,000 pcs. | Yellow (YE) | 553-60035 |
| TLFX190DS-1x50WH | 19.0 | 9.5 | 50.0 | 0.78 | 1,500 pcs. | White (WH) | 553-60006 |
| TLFX190DS-1x50YE | 19.0 | 9.5 | 50.0 | 0.78 | 1,500 pcs. | Yellow (YE) | 553-60016 |
| TLFX254DS-2x25WH | 25.4 | 12.7 | 25.0 | 0.93 | 2,000 pcs. | White (WH) | 553-60027 |
| TLFX254DS-2x25YE | 25.4 | 12.7 | 25.0 | 0.93 | 2,000 pcs. | Yellow (YE) | 553-60036 |
| TLFX254DS-1x50WH | 25.4 | 12.7 | 50.0 | 0.93 | 1,000 pcs. | White (WH) | 553-60007 |
| TLFX254DS-1x50YE | 25.4 | 12.7 | 50.0 | 0.93 | 1,000 pcs. | Yellow (YE) | 553-60017 |
| TLFX381DS-2x25WH | 38.1 | 19.1 | 25.0 | 0.98 | 1,000 pcs. | White (WH) | 553-60028 |
| TLFX381DS-2x25YE | 38.1 | 19.1 | 25.0 | 0.98 | 1,000 pcs. | Yellow (YE) | 553-60037 |
| TLFX381DS-1x50WH | 38.1 | 19.1 | 50.0 | 0.98 | 500 pcs. | White (WH) | 553-60008 |
| TLFX381DS-1x50YE | 38.1 | 19.1 | 50.0 | 0.98 | 500 pcs. | Yellow (YE) | 553-60018 |

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

EN 45545-2

ASTM

NF F

UNI CEI

For product specific approvals and specifications please refer to the Appendix.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wire Labels & Markers](#) category:

Click to view products by [HellermannTyton](#) manufacturer:

Other Similar products are found below :

[89078GBEST](#) [89080GBEPR](#) [PCL025-4](#) [5761-2SF](#) [CS1836-000](#) [CS8626-000](#) [CU6337-000](#) [CU6343-000](#) [CWD01-0](#) [CWD012-0](#) [CWD012-7](#)
[CWD015-3](#) [CWD015-7](#) [CWD02-0](#) [CWD02-3](#) [CWD02-4](#) [CWD02-6](#) [CWD02-8](#) [CWD02-A](#) [CWD02-D](#) [CWD02-H](#) [CWD02-K](#) [CWD02-L](#)
[CWD02-M](#) [CWD02-P](#) [CWD02-Q](#) [CWD02-R](#) [CWD02-U](#) [CWD02-W](#) [CWD02-Y](#) [CWD03-+](#) [CWD03-0](#) [CWD03-P](#) [CWD06-0](#) [CWD06-8](#)
[CWD06-9](#) [CWD06-L](#) [CWD06-N](#) [CWD09-0](#) [CWD09-5](#) [CWD09-7](#) [6806810001](#) [CY8610-000](#) [D04690-000](#) [7-1768041-1](#) [726631-1](#) [739253-](#)
[000](#) [F24597-000](#) [750-1412](#) [F83400-000](#)