

## **Specification Sheet**

Part Number: 596-00885

Made with UV-stable inks and materials for durability and weather resistance.

Reflective properties to meet applicable NEC code requirements for reflective identification.

SOLAR PV SYSTEM EQUIPPED WITH RAPID SHUTDOWN

TURN RAPID SHUTDOWN SWITCH TO THE "OFF" POSITION TO SHUT DOWN PV SYSTEM AND REDUCE SHOCK HAZARD IN THE ARRAY



Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Solar Label, Reflective, SOLAR PV SYSTEM...SHUTDOWN, 6.0" x 4.0", VL, Yellow, 50/roll

Article Number 596-00885

Type RSDYL17

Color Yellow (YE)

Quantity Per roll

**Product Description** 

HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code (NEC) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description	Solar Label, Reflective, SOLAR PV SYSTEMSHUTDOWN, 6.0" x 4.0", VL, Yellow, 50/roll
Global Part Name	RSDYL17-505/281-YE
Technical Description	Pre-Printed Solar Label, Reflective-2017 Code, Rapid Shutdown Label - Roof Safe, 6.0" X 4.0", Vinyl, Yellow, 50/RL
Length L (Imperial)	4
Length L (Metric)	101.6
Width W (Imperial)	6.0
Width W (Metric)	152.4
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	4.0
Height H (Metric)	101.60

Material Type 505/281, UV-stabilized reflective vinyl with clear polyester laminate (505/281)

Material Shortcut 505/281

Adhesive Acrylic **Halogen Free** No **Adhesive Operating Temperature** -40°F to +302°F (-40°C to +150°C) **Operating Temperature** -40°F to +174°F (-40°C to +79°C) **Reach Compliant (Article 33)** Yes **ROHS Compliant** Yes Certification/Specification NEC2017 NEC2020 Warranty (US) Yes **UL Recognized (US)** Yes **Package Quantity (Imperial)** 50 Package Quantity (Metric) 50 **Customs Number** 3919102055 1 Labels per Column

Labels per Row

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Labels and Industrial Warning Signs category:

Click to view products by HellermannTyton manufacturer:

Other Similar products are found below:

ESSW30-025 FTP-020P0704 QC101 QC105 QCC613 QCC615 132465 142810 15288 15425 18511 HTS795-1 30288 1768021-2 18432 1878679-3 2-1878614-6 PTL-31-427-YL 30239 QC154 QCC612 30545 35070 WM-15-PK WM-20-PK 5-1768021-6 06770 111852 111932 KMT-02513V-9 8-1768039-4 1878983-4 B422 25X85MM PAXLBK10 LAT-52-361-1 PTL-20-486 PTL-38-486 13903 11237 18389 18341 18603 29904 18519 18524 115110 11199 18542 62351 90731