


Specification Sheet

Part Number: FSU10-E



Single-part insert creates smooth entry / exit point for wire and cables.

HelaGuard Metallic Conduit End Cap Insert, Flexible 0.25" (10mm) Dia, NPB Metal, 10/pkg

Article Number	166-90841
Type	FSU10-E
Color	Metal (ML)
Quantity Per	pack
Product Description	Nickel-plated brass end cap insert creates a smooth bore exit, protecting cables from damage. Twist-in ferrule serves as grounding core for spiral-constructed metallic conduit. Use with FSU, LFHU, FPU, SSU and FU-X series metallic conduit.
Short Description	HelaGuard Metallic Conduit End Cap Insert, Flexible 0.25" (10mm) Dia, NPB Metal, 10/pkg
Global Part Name	FSU10-E-NPB/PVC-ML

Length L (Imperial) 0.64

Length L (Metric) 16.3

Height H (Imperial) 0.54

Height H (Metric) 13.8

Nominal Diameter (Imperial) 0.25

Nominal Diameter (Metric) 10

Material Nickel Plated Brass (NPB) Polyvinylchloride (PVC)

Material Shortcut PVC NPB

Operating Temperature -148°F to +572°F (-100°C to +300°C)

Package Quantity (Imperial) 10

Package Quantity (Metric) 10

Customs Number 7415290000

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Conduit Fittings & Accessories](#) category:

Click to view products by [HellermannTyton](#) manufacturer:

Other Similar products are found below :

[M3231GAB](#) [M3231GAC](#) [M3231GAE](#) [M3231GL](#) [M3231GT](#) [VC-937-16/RED](#) [VC-562-16/RED](#) [VC-1125-16/RED](#) [DM0240-1/2A](#) [3408B](#)
[G6002](#) [M4340GAE](#) [C2016-P](#) [C2012-P](#) [3407B](#) [561-87BG11BLK](#) [561-75BG11B](#) [1.533.1201.50](#) [1.533.1601.51](#) [1.533.2001.51](#) [1.533.4001.50](#)
[1.533.5001.50](#) [BVNV-P428](#) [BVBV-P366](#) [VC-687-16/RED](#) [2276](#) [2663-P](#) [3405B](#) [C2070-P](#) [3582V](#) [2643-P](#) [4975](#) [2644-P](#) [2955](#) [M50](#) [2404-P](#)
[C2008-P](#) [2723-P](#) [2291](#) [2133-P](#) [3048F](#) [VC12516](#) [RC156-0500](#) [DM0523-1/2A](#) [1035A](#) [DMS0250-1A](#) [DMS0313-1A](#) [1040A](#) [1050A](#) [R1/8A](#)
[DMPC0490-1/2A](#)