

## Specification Sheet

Part Number: MB3A10M4


For use with HellermannTyton T18 - T30 cable ties to provide stability when securing bundles.

4-way opening allows cable ties to be installed parallel or perpendicular to bundles.

The rubber-based adhesive is an economical choice ideal for indoor applications, with a static load weight of 0.6 lb.

Two predrilled holes extend mounting options and solutions.

Extended adhesive liner is easy to remove quickly.



Rubber Adhesive Cable Tie Mount, 0.75" x 0.75", Use With T18-T30 Cable Tie, PA66, White, 1000/pkg

**Article Number** 151-28721

**Type** MB3A

**Color** White (WH)

**Quantity Per** bag

**Product Description** MB3A adhesive mounts are for use with HellermannTyton T18 - T30 Series cable ties to provide stability when securing bundles. The rubber adhesive-backed mounts can be used to secure a bundle and have two predrilled holes to extend mounting options.

|  |   |
|--|---|
| <b>Short Description</b>                     | Rubber Adhesive Cable Tie Mount, 0.75" x 0.75", Use With T18-T30 Cable Tie, PA66, White, 1000/pkg |
| <b>Global Part Name</b>                      | MB3A-PA66-WH  |
| <b>Length L (Imperial)</b>                   | 0.75  |
| <b>Length L (Metric)</b>                     | 19.0  |
| <b>Fixation Method</b>                       | Screw Mounting and Adhesive   |
| <b>Width W (Imperial)</b>                    | 0.75  |
| <b>Width W (Metric)</b>                      | 19.0  |
| <b>Cable Ties</b>                            | T18 - T30   |
| <b>Height H (Imperial)</b>                   | .18   |
| <b>Height H (Metric)</b>                     | 4.6   |
| <b>Cable Tie Width Max (Imperial)</b>        | 0.14  |
| <b>Cable Tie Width Max (Metric)</b>          | 3.6   |
| <b>Mounting Hole Diameter D (Imperial)</b>   | 0.12  |
| <b>Mounting Hole Diameter D (Metric)</b>     | 3.0 mm  |
| <b>Mounting Hole Diameter D Max (Metric)</b> | 3.0   |

|   |   |
|---|---|
| <b>Mounting Hole Centers (Imperial)</b> | 0.52  |
| <b>Material</b>                         | Polyamide 6.6 (PA66)                            |
| <b>Material Shortcut</b>                | PA66  |
| <b>Adhesive</b>                         | Synthetic rubber with base of polyethylene foam |
| <b>Flammability</b>                     | UL 94 V-2 (excluding adhesive)                  |
| <b>Adhesive Operating Temperature</b>   | 0°F to +150°F (-18 °C to +66 °C)                |
| <b>Operating Temperature</b>            | -40°F to +185°F (-40°C to +85°C)                |
| <b>ROHS Compliant</b>                   | Yes   |
| <b>Package Quantity (Imperial)</b>      | 1000  |
| <b>Package Quantity (Metric)</b>        | 1000  |
| <b>Customs Number</b>                   | 3926909988                                      |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Cable Tie Mounts](#) category:*

*Click to view products by [HellermannTyton](#) manufacturer:*

Other Similar products are found below :

[3-350087-0](#) [CTB75X75BKA-C](#) [561-EZAB580T](#) [561-EZS375B40](#) [561-TA250125](#) [08443-0](#) [10035-0](#) [561-TA00600](#) [1689174-1](#) [08445-0](#)  
[10351-0](#) [561-TA250125B](#) [20015-0](#) [10350-0](#) [10029-0](#) [08484-0](#) [08446-0](#) [08318-0](#) [PAM075NY-A-C](#) [MTH1-3](#) [10044](#) [151-01802](#) [151-11319](#)  
[151-11819](#) [PLWP1SB-D](#) [PLWP1M-C](#) [PLWP2SA-D](#) [PLWP2SB-D](#) [PLWP2S-C](#) [PLWP1S-D](#) [PLWP1M-D](#) [TA1S8-C](#) [ABM3H-A-L](#) [ABM3H-](#)  
[AT-T0](#) [EMS-A-C0](#) [EMSK3-1-3-0](#) [10079](#) [10030](#) [151-10930](#) [151-10920](#) [3590](#) [151-28320](#) [151-28349](#) [151-28530](#) [151-10914](#) [151-10904](#) [151-](#)  
[10916](#) [151-10906](#) [06297](#) [CTB75X75NTA-C](#)