

## Specification Sheet

Part Number: T18R0UVM4



UV stabilized cable ties contain an inhibitor which prolongs the life of the tie in UV exposures.

Inside serrations allow for strong grip on cables and wire bundles.

Head design provides high tensile strength with very low insertion force.

Bent tail ensures a quick and simple installation.

UV Resistant Cable Tie, 4" Long, UL Rated, 18lb Tensile Strength, PA66UV, Black, 1000/pkg

**Article Number** 111-01915

**Type** T18R

**Color** Black (BK)

**Quantity Per** bag

**Product Description** Used in the solar industry and other applications, HellermannTyton offers cable ties made of UV stabilized PA66UV material. This material provides additional protection against UV radiation for long-term outdoor use and is available in various styles, tensile strengths, and bundle diameters. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

|  |   |
|--|---|
| <b>Short Description</b>                   | UV Resistant Cable Tie, 4" Long, UL Rated, 18lb Tensile Strength, PA66UV, Black, 1000/pkg |
| <b>Global Part Name</b>                    | T18R-PA66UV-BK  |
| <b>Minimum Tensile Strength (Imperial)</b> | 18.0  |
| <b>Minimum Tensile Strength (Metric)</b>   | 80.0  |
| <b>Length L (Imperial)</b>                 | 3.94  |
| <b>Length L (Metric)</b>                   | 100.0   |
| <b>Identification Plate Position</b>       | none  |
| <b>Releasable Closure</b>                  | No  |
| <b>Tie Closure</b>                         | plastic pawl  |
| <b>Variant</b>                             | Inside Serrated   |
| <b>Width W (Imperial)</b>                  | 0.10  |
| <b>Width W (Metric)</b>                    | 2.5   |
| <b>Bundle Diameter Min (Imperial)</b>      | 0.06  |
| <b>Bundle Diameter Min (Metric)</b>        | 1.5   |
| <b>Bundle Diameter Max (Imperial)</b>      | 0.87  |

|                                      |  |
|--------------------------------------|--|
| <b>Bundle Diameter Max (Metric)</b>  | 22.0   |
| <b>Thickness T (Metric)</b>          | 1.0  |
| <b>Height H (Metric)</b>             | 3.7  |
| <b>Material</b>                      | Polyamide 6.6 UV-resistant (PA66UV)  |
| <b>Material Shortcut</b>             | PA66UV   |
| <b>Flammability</b>                  | UL 94 V-2  |
| <b>Halogen Free</b>                  | Yes  |
| <b>Operating Temperature</b>         | -40°F to +185°F (-40°C to +85°C)   |
| <b>ROHS Compliant</b>                | Yes  |
| <b>Certification/Specification</b>   | UL-ZODZ2.E64139 CAGE Code 53421 Bundesamt für Wehrtechnik   VG 95387 Part 4 Edition: 2008-12 |
| <b>UL Recognized (US)</b>            | Yes  |
| <b>UL Recognized (US and Canada)</b> | Yes  |
| <b>Package Quantity (Imperial)</b>   | 1000   |
| <b>Package Quantity (Metric)</b>     | 1000   |

**Customs Number**

3926909988

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Cable Ties](#) category:*

*Click to view products by [HellermannTyton](#) manufacturer:*

Other Similar products are found below :

[65034-C](#) [65037-C](#) [770-1751-10](#) [REL50L0C2](#) [20093-0](#) [SF600-120X](#) [SJ-3463](#) [SJ3518FR-1x50](#) [SJ3526N-Beige-2"x50yd](#) [SJ3526N BLACK](#)  
[58" X 50YD](#) [SJ3571](#) [SJ-3571-1"x50yd-Black](#) [PLT2S-C4](#) [34-455-C](#) [3722](#) [561-B110120](#) [561-N3510](#) [TYZ528M](#) [34-463-C](#) [URT20S-M](#)  
[06226](#) [08350-0](#) [08600-0](#) [08376-0](#) [10036-0](#) [10037-0](#) [10325-0](#) [10362-0](#) [10606-0](#) [561-EZ250](#) [561-EZ625](#) [SJ3527N-Beige-2"x50yd](#) [SJ3527N-](#)  
[LOOP-BLACK-1](#) [SJ3572-2"x50yd-Black](#) [CF5625-000](#) [V03HK](#) [65004-C](#) [65005-C](#) [65007-C](#) [65036-C](#) [157-00039](#) [770-1708](#) [770-1753-10](#)  
[65035-C](#) [770-1752](#) [SPNY-041-9](#) [SF400-120X](#) [3719](#) [08582-0](#) [08386-0](#)