

## Specification Sheet

Part Number: T50R9C2

Engineered and manufactured for maximum performance and quality. Made from 100% high-quality plastic to ensure efficient recycling.

Inside serration for a strong grip onto bundles.

Easy application either manually or with a tensioning tool.

Bent tail allows for simpler insertion.



Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66, Natural, 100/pkg

**Article Number** 112-05019

**Type** T50R

**Color** Natural (NA)

**Quantity Per** bag

**Product Description** T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66, Natural, 100/pkg

|  |                 |
|--|-----------------|
| <b>Global Part Name</b>                    | T50R-PA66-NA    |
| <b>Minimum Tensile Strength (Imperial)</b> | 50.0            |
| <b>Minimum Tensile Strength (Metric)</b>   | 225.0           |
| <b>Length L (Imperial)</b>                 | 8.0             |
| <b>Length L (Metric)</b>                   | 202.0           |
| <b>Identification Plate Position</b>       | none            |
| <b>Releasable Closure</b>                  | No              |
| <b>Tie Closure</b>                         | plastic pawl    |
| <b>Variant</b>                             | Inside Serrated |
| <b>Width W (Imperial)</b>                  | 0.18            |
| <b>Width W (Metric)</b>                    | 4.6             |
| <b>Bundle Diameter Min (Imperial)</b>      | 0.06            |
| <b>Bundle Diameter Min (Metric)</b>        | 1.5             |
| <b>Bundle Diameter Max (Imperial)</b>      | 1.97            |
| <b>Bundle Diameter Max (Metric)</b>        | 50.0            |
| <b>Thickness T (Imperial)</b>              | 0.05            |

|                                      |   |
|--------------------------------------|---|
| <b>Thickness T (Metric)</b>          | 1.2   |
| <b>Material</b>                      | Polyamide 6.6 (PA66)  |
| <b>Material Shortcut</b>             | PA66  |
| <b>Flammability</b>                  | UL 94 V-2   |
| <b>Halogen Free</b>                  | Yes   |
| <b>Operating Temperature</b>         | -40°F to +185°F (-40°C to +85°C)  |
| <b>Reach Compliant (Article 33)</b>  | Yes   |
| <b>ROHS Compliant</b>                | Yes   |
| <b>Certification/Specification</b>   | BACS38K Bundesamt für Wehrtechnik   VG 95387 Part 4 Edition:<br>2008-12 CAGE Code 53421 |
| <b>UL Recognized (US)</b>            | Yes   |
| <b>UL Listed (US and Canada)</b>     | Yes   |
| <b>UL Recognized (US and Canada)</b> | Yes   |
| <b>UL Listed (US)</b>                | Yes   |
| <b>Package Quantity (Imperial)</b>   | 100   |

**Package Quantity (Metric)**

100

**Customs Number**

3926909988

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Cable Ties](#) category:*

*Click to view products by [HellermannTyton](#) manufacturer:*

Other Similar products are found below :

[65034-C](#) [65037-C](#) [770-1751-10](#) [REL50L0C2](#) [20093-0](#) [SF600-120X](#) [SJ-3463](#) [SJ3518FR-1x50](#) [SJ3526N-Beige-2"x50yd](#) [SJ3526N BLACK](#)  
[58" X 50YD](#) [SJ3571](#) [SJ-3571-1"x50yd-Black](#) [PLT2S-C4](#) [34-455-C](#) [3722](#) [561-B110120](#) [561-N3510](#) [TYZ528M](#) [34-463-C](#) [URT20S-M](#)  
[06226](#) [08350-0](#) [08600-0](#) [08376-0](#) [10036-0](#) [10037-0](#) [10325-0](#) [10362-0](#) [10606-0](#) [561-EZ250](#) [561-EZ625](#) [SJ3527N-Beige-2"x50yd](#) [SJ3527N-](#)  
[LOOP-BLACK-1](#) [SJ3572-2"x50yd-Black](#) [CF5625-000](#) [V03HK](#) [65004-C](#) [65005-C](#) [65007-C](#) [65036-C](#) [157-00039](#) [770-1708](#) [770-1753-10](#)  
[65035-C](#) [770-1752](#) [SPNY-041-9](#) [SF400-120X](#) [3719](#) [08582-0](#) [08386-0](#)