# HellermannTyton

# Specification Sheet

Part Number: TAG50L-105

Laser printable self-laminating polyester has a smooth surface, allowing for the highest resolution and print contrast.
The material is 1.0 mil thick, allowing it to conform around wires and cable.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Lasertags are not affected by the high heat required in a laser printer.

Laser Print Label, Self-Laminating, 1.0" x .96" x 3.16", 21 Per Sheet, PET, White, 1000/pkg

| | |
|---|---|
| **Article Number** | 594-50105 |
| **Type** | TAG50L |
| **Color** | White (WH) |
| **Quantity Per** | pack |
| **Product Description** | HellermannTyton's self-laminating labels are used for marking wires and cable. The clear tail overlaps and protects the printed information from abrasion, chemicals and solvents and resists UV exposure. When printed using a laser printer, clear marking and high high-contrast imaging against the wire make this the perfect choice for durable identification. |

| | |
|---|---|
| **Short Description** | Laser Print Label, Self-Laminating, 1.0" x .96" x 3.16", 21 Per Sheet, PET, White, 1000/pkg |
| **Global Part Name** | TAG50L-105-WH |
| **Width W (Imperial)** | 1.0 |
| **Width W (Metric)** | 25.4 |
| **Bundle Diameter Min (Imperial)** | 0.39 |
| **Bundle Diameter Min (Metric)** | 10.10 |
| **Bundle Diameter Max (Imperial)** | 0.79 |
| **Bundle Diameter Max (Metric)** | 20.20 |
| **Thickness T (Metric)** | 35.0 |
| **Width of Liner (Metric)** | 215.00 |
| **Width of Liner (Imperial)** | 8.5 |
| **Outside Diameter Max (Imperial)** | 0.39 |
| **Outside Diameter Min (Metric)** | 10.1 |
| **Outside Diameter Min (Imperial)** | 0.79 |
| **Outside Diameter Max (Metric)** | 20.20 |

| | |
|---|---|
| **Material** | Type 105, Polyester, white (105) |
| **Material Shortcut** | 105 |
| **Adhesive** | Acrylic |
| **Halogen Free** | No |
| **Adhesive Operating Temperature** | -40°F to +302°F (-40°C to +150°C) |
| **Operating Temperature** | -40°F to +300°F (-40°C to +149°C) |
| **Reach Compliant (Article 33)** | Yes |
| **ROHS Compliant** | Yes |
| **Package Quantity (Imperial)** | 1000 |
| **Package Quantity (Metric)** | 1000 |
| **Customs Number** | 3919905060 |
| **Labels per Column** | 3 |
| **Labels per Row** | 8 |

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for* Wire Labels & Markers *category:*

*Click to view products by* HellermannTyton *manufacturer:*

Other Similar products are found below :

89078GBEST  89082GBESR  89082GBEST  PCL025-4  5761-2SF  58400  586R734H02  M1.040.0000.6  CRS-CM5M  CRS-M18M  CS1836-000  CS8626-000  CU6337-000  CU6342-000  CU6343-000  CWD01-0  CWD012-0  CWD012-7  CWD015-3  CWD015-7  CWD02-0  CWD02-3  CWD02-4  CWD02-6  CWD02-8  CWD02-A  CWD02-D  CWD02-H  CWD02-K  CWD02-L  CWD02-M  CWD02-P  CWD02-Q  CWD02-R  CWD02-U  CWD02-W  CWD02-Y  CWD03-+  CWD03-0  CWD03-P  CWD06-0  CWD06-8  CWD06-9  CWD06-L  CWD06-N  CWD09-0  CWD09-5  CWD09-7  6806810001  CZ2857-000