

F-CY-JZ

flexible, Cu-screened, EMC-preferred type, meter marking



Technical data

- Special-PVC control cable adapted to DIN VDE 0285-525-2-51 / DIN EN 50525-2-51
- **Temperature range**
flexing -10°C to +80°C
fixed installation -40°C to +80°C
- **Nominal voltage**
U₀/U 300/500 V
- **Test voltage**
core/core 4000 V
core/screen 2000 V
- **Breakdown voltage**
min. 8000 V
- **Insulation resistance**
min. 20 MOhm x km
- **Mutual capacitance**
acc. to different cross sections
0,5 up to 2,5 mm²:
core/core approx. 150 nF/km
core/screen approx. 270 nF/km
- **Coupling resistance**
max. 250 Ohm/km
- **Minimum bending radius**
flexing 10x cable Ø
fixed installation 5x cable Ø
- **Radiation resistance**
up to 80x10⁶ cJ/kg (up to 80 Mrad)

Cable structure

- Bare copper conductor, to DIN VDE 0295 cl.5, fine wire, BS 6360 cl.5, IEC 60228 cl.5
- Core insulation of special PVC compound type Z 7225
- Core identification to DIN VDE 0293 black cores with continuous white numbering
- GN-YE conductor, 3 cores and above in the outer layer
- Cores stranded in layers with optimal lay length
- Foil separator
- Tinned copper braided screening, approx. 85% coverage
- Outer sheath of special PVC compound type TM2 to DIN VDE 0207-363-4-1/DIN EN 50363-4-1
- Sheath colour: grey (RAL 7001)
- With meter marking

Properties

- Extensively oil resistant, oil-/chemical resistance see "Technical Informations"
- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers

Tests

- PVC self-extinguishing and flame retardant acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1-2 (equivalent DIN VDE 0472 part 804 test method B)

Note

- G = with GN-YE conductor
x = without GN-YE conductor (OZ)
- Please note "cleanroom qualified" when ordering.
- AWG sizes are approximate equivalent values. The actual cross section is in mm².
- Unscreened analogue type:
JZ-500

Application

For use as a data cable in control circuits, in tool-making and machine industries as well as a signal cable in computer systems and electronics. The more usual PVC inner sheath has been replaced in these cables by a stabilising foil separator, thus reducing the total diameter of the cables considerably and thereby reducing the bending radius, total weight etc. The high covering percentage of the copper screening offers interference-free signal transfer etc. The dense screening assures disturbance-free transmission of all signals and impulses. An ideal disturbance-free control cable for the above application.

EMC = Electromagnetic compatibility

To optimize the EMC features we recommend a large round contact of the copper braiding on both ends.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
16320	2 x 0,5	5,7	35,0	45,0	20
16321	3 G 0,5	6,0	42,0	55,0	20
16322	4 G 0,5	6,5	47,0	61,0	20
16323	5 G 0,5	6,9	56,0	74,0	20
16324	6 G 0,5	7,6	67,0	89,0	20
16325	7 G 0,5	7,6	69,0	98,0	20
16326	8 G 0,5	8,4	80,0	117,0	20
16327	10 G 0,5	9,5	94,0	135,0	20
16328	12 G 0,5	9,8	108,0	157,0	20
16329	14 G 0,5	10,4	116,0	190,0	20
16330	16 G 0,5	10,9	129,0	210,0	20
16331	18 G 0,5	11,4	145,0	217,0	20
16332	20 G 0,5	12,2	172,0	240,0	20

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
16333	21 G 0,5	12,2	188,0	250,0	20
16334	24 G 0,5	13,7	235,0	300,0	20
16335	25 G 0,5	13,7	240,0	314,0	20
16336	30 G 0,5	14,4	295,0	360,0	20
16337	32 G 0,5	15,1	301,0	425,0	20
16165	34 G 0,5	15,6	312,0	433,0	20
16338	36 G 0,5	15,6	318,0	446,0	20
16339	40 G 0,5	16,4	343,0	475,0	20
16490	41 G 0,5	17,0	348,0	486,0	20
16340	50 G 0,5	18,5	406,0	573,0	20
16341	61 G 0,5	19,6	508,0	653,0	20
16342	80 G 0,5	22,5	680,0	784,0	20
16343	100 G 0,5	25,0	804,0	995,0	20

Continuation ▶

F-CY-JZ

flexible, Cu-screened, EMC-preferred type, meter marking



Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.	Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
16344	2 x 0,75	6,2	40,0	59,0	19	16394	3 G 1,5	7,7	80,0	100,0	16
16345	3 G 0,75	6,6	52,0	66,0	19	16395	4 G 1,5	8,3	97,0	126,0	16
16346	4 G 0,75	7,1	60,0	77,0	19	16396	5 G 1,5	9,2	119,0	160,0	16
16347	5 G 0,75	7,8	71,0	93,0	19	16397	7 G 1,5	9,9	147,0	208,0	16
16348	6 G 0,75	8,4	80,0	113,0	19	16398	8 G 1,5	11,2	170,0	244,0	16
16349	7 G 0,75	8,4	91,0	130,0	19	16399	10 G 1,5	12,7	193,0	315,0	16
16350	8 G 0,75	9,5	110,0	145,0	19	16400	12 G 1,5	13,5	267,0	338,0	16
16351	10 G 0,75	10,7	137,0	180,0	19	16401	14 G 1,5	14,1	283,0	383,0	16
16353	12 G 0,75	11,1	142,0	202,0	19	16402	16 G 1,5	15,0	315,0	424,0	16
16354	14 G 0,75	11,5	180,0	225,0	19	16403	18 G 1,5	15,7	374,0	479,0	16
16355	16 G 0,75	12,3	200,0	275,0	19	16449	19 G 1,5	15,7	386,0	508,0	16
16356	18 G 0,75	12,9	212,0	292,0	19	16404	20 G 1,5	16,7	396,0	545,0	16
16447	19 G 0,75	12,9	230,0	308,0	19	16405	21 G 1,5	16,7	425,0	560,0	16
16357	20 G 0,75	13,9	238,0	320,0	19	16406	24 G 1,5	18,5	458,0	690,0	16
16358	21 G 0,75	13,9	246,0	378,0	19	16407	25 G 1,5	18,5	526,0	705,0	16
16359	24 G 0,75	15,4	270,0	435,0	19	16450	27 G 1,5	19,1	531,0	774,0	16
16360	25 G 0,75	15,4	281,0	415,0	19	16408	28 G 1,5	19,7	541,0	810,0	16
16361	27 G 0,75	15,7	304,0	435,0	19	16409	30 G 1,5	19,7	555,0	830,0	16
16362	30 G 0,75	16,4	320,0	450,0	19	16410	35 G 1,5	21,3	645,0	890,0	16
16363	32 G 0,75	17,0	342,0	484,0	19	16451	37 G 1,5	21,3	674,0	945,0	16
16166	34 G 0,75	17,8	345,0	502,0	19	16411	40 G 1,5	22,3	725,0	1060,0	16
16364	36 G 0,75	17,8	350,0	535,0	19	16493	41 G 1,5	23,1	801,0	1071,0	16
16448	37 G 0,75	17,8	361,0	592,0	19	16412	50 G 1,5	25,5	885,0	1290,0	16
16365	40 G 0,75	18,4	369,0	610,0	19	16413	61 G 1,5	27,1	1100,0	1705,0	16
16491	41 G 0,75	19,3	400,0	622,0	19	16414	80 G 1,5	31,1	1324,0	2010,0	16
16366	50 G 0,75	21,0	461,0	777,0	19	16415	100 G 1,5	34,5	1641,0	2505,0	16
16367	61 G 0,75	22,3	540,0	900,0	19	16416	2 x 2,5	8,5	96,0	130,0	14
16368	80 G 0,75	25,7	711,0	1210,0	19	16417	3 G 2,5	9,2	144,0	167,0	14
16369	100 G 0,75	28,5	900,0	1445,0	19	16418	4 G 2,5	10,0	148,0	195,0	14
16370	2 x 1	6,5	50,0	65,0	18	16419	5 G 2,5	11,0	181,0	223,0	14
16371	3 G 1	6,9	60,0	80,0	18	16420	7 G 2,5	12,1	255,0	344,0	14
16372	4 G 1	7,6	71,0	98,0	18	16421	10 G 2,5	15,7	340,0	460,0	14
16373	5 G 1	8,2	88,0	127,0	18	16438	12 G 2,5	16,4	441,0	570,0	14
16374	6 G 1	9,0	97,0	144,0	18	16452	18 G 2,5	19,3	570,0	681,0	14
16375	7 G 1	9,0	111,0	158,0	18	16422	2 x 4	10,5	120,0	185,0	12
16376	8 G 1	10,0	127,0	197,0	18	16423	3 G 4	11,1	174,0	240,0	12
16377	10 G 1	11,3	150,0	232,0	18	16424	4 G 4	12,3	230,0	310,0	12
16378	12 G 1	11,9	184,0	260,0	18	16425	5 G 4	13,8	273,0	385,0	12
16379	14 G 1	12,4	196,0	302,0	18	16426	7 G 4	15,1	316,0	500,0	12
16380	16 G 1	13,0	209,0	346,0	18	16427	2 x 6	11,9	173,0	268,0	10
16381	18 G 1	14,0	260,0	380,0	18	16428	3 G 6	12,6	240,0	330,0	10
16352	19 G 1	14,0	280,0	412,0	18	16429	4 G 6	14,2	305,0	415,0	10
16382	20 G 1	14,9	317,0	440,0	18	16430	5 G 6	15,6	439,0	509,0	10
16383	24 G 1	16,5	320,0	493,0	18	16431	7 G 6	17,1	505,0	672,0	10
16384	25 G 1	16,5	349,0	534,0	18	16432	2 x 10	15,3	255,0	425,0	8
16439	27 G 1	16,9	400,0	562,0	18	16433	3 G 10	16,5	350,0	500,0	8
16385	28 G 1	17,6	408,0	595,0	18	16434	4 G 10	18,2	535,0	783,0	8
16386	30 G 1	17,6	441,0	616,0	18	16435	5 G 10	20,0	592,0	856,0	8
16387	34 G 1	19,0	486,0	741,0	18	16436	7 G 10	22,1	810,0	1305,0	8
16446	37 G 1	19,0	519,0	790,0	18	16458	3 G 16	19,0	585,0	795,0	6
16388	40 G 1	19,7	510,0	835,0	18	16440	4 G 16	21,0	740,0	880,0	6
16492	41 G 1	20,6	531,0	843,0	18	16437	5 G 16	23,1	895,0	1295,0	6
16389	50 G 1	22,4	625,0	1025,0	18	16441	4 G 25	26,4	1140,0	1570,0	4
16390	61 G 1	23,8	702,0	1205,0	18	16442	5 G 25	29,0	1380,0	1965,0	4
16391	80 G 1	27,4	920,0	1445,0	18	16443	4 G 35	29,0	1576,0	2070,0	2
16392	100 G 1	30,6	1120,0	1613,0	18	16444	5 G 35	32,3	1930,0	2690,0	2
16393	2 x 1,5	7,1	63,0	88,0	16	16445	4 G 50	34,8	2155,0	3015,0	1

Dimensions and specifications may be changed without prior notice. (RA01)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ribbon Cables / IDC Cables](#) category:

Click to view products by [Helukabel](#) manufacturer:

Other Similar products are found below :

[FSK-12A](#) [AWG28-10G](#) [EHJ3C](#) [EHJ4C](#) [FSP-25A](#) [cab-LVDV-DAT-34-15](#) [49635-C62-S2](#) [1-3636-600-5204](#) [92315-1408](#) [426171120-3](#) [2-1589735-3](#) [JSM015PP2DCC23N](#) [92301-0283](#) [ACL-eSSI-2](#) [92301-0718](#) [MMSDT-06-20-S-05.5-D-K-LDX](#) [IDD-04-G](#) [NM-2J2-051-PS1-JJAB](#) [1700/26SF \(100FT\)](#) [1700/34SF \(100FT\)](#) [3801/09 \(100FT\)](#) [DS1058-08M28-30.5](#) [DS1058-30M28-30.5](#) [0015712](#) [0015905](#) [S30109](#)
[11203](#) [11223](#) [11243](#) [11262](#) [0037147](#) [0022512](#) [0022412](#) [0022416](#) [0022421](#) [0022632](#) [0022602](#) [0022502](#) [0022603](#) [0022403](#) [0022604](#)
[0022404](#) [0022605](#) [0022505](#) [0022405](#) [0022607](#) [0022608](#) [0022508](#) [0022408](#) [0011022](#)