

MULTIFLEX 512®-PUR UL/CSA

for extreme mechanical stress



HELUKABEL® MULTIFLEX 512®-PUR UL/CSA 12G1,5 QMM 1000 V E170315 CE

TECHNICAL DATA

PUR drag chain cable acc. to UL-Std. 758 (AWM) Style 21209, CSA-Std. C22.2 No. 210 - AWM I/II A/B

Temperature range	flexible -30°C to +90°C fixed -40°C to +90°C
Permissible operating temperature of the conductor	+90°C
Nominal voltage	UL (AWM) AC 1000 V
Test voltage core/core	3000 V
Minimum bending radius	flexible 5x Outer-Ø fixed 3x Outer-Ø

CABLE STRUCTURE

- Copper wire bare, extra finely stranded acc. to DIN VDE 0295 Class 6 / IEC 60228 Class 6
- Core insulation: Special-PP
- Core identification acc. to DIN VDE 0293-334, black cores with consecutive labeling in white digits
- Protective conductor: starting with 3 cores, G = with protective conductor GN-YE, in the outer layer, x = without protective conductor
- Cores stranded in layers with optimally matched lay lengths
- Fleece wrapping over each stranding layer, from 4 mm² without fleece wrapping
- Outer sheath: Special grade of full polyurethane acc. to DIN VDE 0207-363-10-2 / DIN EN 50363-10-2 (compound type TMPU), UL-Std. 758 (AWM) Style 21209
- Sheath colour: grey (RAL 7001)
- Length marking: in metres

PROPERTIES

- resistant to: oil, UV radiation, ozone, oxygen, weathering effects, hydrolysis, microbes, coolants, hydraulic fluids, acids, alkalis, greases, seawater and wastewater, drilling fluids, drilling mud
- highly abrasion-resistant, notch-resistant, tear-resistant, cut-resistant, wear-resistant, low adhesion
- for outdoor use
- suitable for use in drag chains

- halogen-free
- the materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers

TESTS

- flame-retardant acc. to DIN VDE 0482-332-1-2 / DIN EN 60332-1-2 / IEC 60332-1-2, UL VW-1, CSA FT1
- oil-resistant acc. to DIN VDE 0473-811-404 / DIN EN 60811-404 / IEC 60811-404
- drilling mud resistant acc. to NEK TS 606
- UV-resistant acc. to DIN EN ISO 4892-2
- weather-resistant acc. to DIN EN ISO 4892-2
- Alternate bending test: tested on approx. 10 million cycles
- Certifications: DNV GL

APPLICATION

Industrial application: UL/CSA approved drag chain cable for use in machine and tool manufacturing, in robotics and in other constantly moving machine parts; for permanently flexible applications moving freely without tensile stress and without movement control in dry, damp and wet rooms as well as outdoors. A slippery PP core insulation, cut-resistance and a low-adhesion PUR outer sheath guarantee an optimum durability and excellent cost-efficiency. Oil and gas sector: for use as control and instrumentation cables on drilling platforms and ships, in land drilling as well as in chemical and petrochemical plants; resistant to drilling mud according to NEK TS 606 and thus ideal for high-performance applications such as pumping stations, compressors, generators and emergency power supply systems.

NOTES

- the conductor is metrically (mm²) constructed, AWG numbers are approximated, and are for reference only
- for use in energy supply systems:
 - 1) the assembly instructions must be observed
 - 2) for further application parameters, please refer to the selection tables
 - 3) for special applications, we recommend contacting us and using our data entry form for energy supply systems

Part no.	No. cores x cross-sec. mm²	AWG, approx.	Outer Ø mm, approx.	Cu-weight kg/km	Weight kg/km, approx.
21559	2 x 0.5	20	5.9	10.8	38.0
21560	3 G 0.5	20	6.2	16.1	46.0
21561	4 G 0.5	20	6.7	21.5	59.0
21562	5 G 0.5	20	7.2	27.0	68.0
21563	7 G 0.5	20	8.3	37.6	88.0
21564	12 G 0.5	20	9.7	64.5	131.0
21565	18 G 0.5	20	11.2	97.0	197.0
21566	20 G 0.5	20	11.8	107.5	260.0
21567	25 G 0.5	20	13.6	134.5	282.0
21568	30 G 0.5	20	13.9	161.3	315.0
21569	36 G 0.5	20	15.1	193.5	374.0
21570	2 x 0.75	19	6.6	14.4	47.0

Part no.	No. cores x cross-sec. mm²	AWG, approx.	Outer Ø mm, approx.	Cu-weight kg/km	Weight kg/km, approx.
21571	3 G 0.75	19	7.0	21.6	58.0
21572	4 G 0.75	19	7.5	29.0	69.0
21573	5 G 0.75	19	8.1	36.0	85.0
21574	7 G 0.75	19	9.4	50.0	118.0
21575	12 G 0.75	19	11.2	86.0	183.0
21576	18 G 0.75	19	13.0	130.0	270.0
21577	20 G 0.75	19	13.8	144.0	290.0
21523	21 G 0.75	19	14.7	151.0	302.0
21578	25 G 0.75	19	16.3	180.0	374.0
21579	30 G 0.75	19	16.5	216.0	420.0
21580	36 G 0.75	19	18.0	259.0	498.0
21581	2 x 1	18	6.9	19.2	55.0

MULTIFLEX 512®-PUR UL/CSA

for extreme mechanical stress



Part no.	No. cores x cross-sec. mm ²	AWG, approx.	Outer Ø mm, approx.	Cu-weight kg/km	Weight kg/km, approx.
21582	3 G 1	18	7.3	29.0	70.0
21583	4 G 1	18	7.9	38.0	86.0
21584	5 G 1	18	8.5	48.0	102.0
21585	7 G 1	18	10.0	67.0	143.0
21586	12 G 1	18	11.8	115.0	225.0
21587	18 G 1	18	13.9	173.0	334.0
21588	20 G 1	18	14.9	192.0	370.0
21589	25 G 1	18	17.2	240.0	460.0
21590	30 G 1	18	17.7	288.0	530.0
21591	36 G 1	18	19.2	346.0	625.0
21592	41 G 1	18	20.9	410.0	779.0
21593	50 G 1	18	22.8	498.0	953.0
21594	65 G 1	18	26.0	650.0	1205.0
21595	2 x 1.5	16	7.7	29.0	70.0
21596	3 G 1.5	16	8.2	43.0	90.0
21597	4 G 1.5	16	8.9	58.0	106.0
21598	5 G 1.5	16	9.6	72.0	145.0
21599	7 G 1.5	16	11.3	101.0	205.0
21600	12 G 1.5	16	13.7	173.0	320.0
21601	18 G 1.5	16	16.4	259.0	465.0
21602	20 G 1.5	16	17.2	288.0	510.0
21603	25 G 1.5	16	20.2	360.0	650.0
21604	30 G 1.5	16	20.7	432.0	750.0
21605	36 G 1.5	16	22.5	518.0	880.0
21606	42 G 1.5	16	24.4	628.0	1209.0

Part no.	No. cores x cross-sec. mm ²	AWG, approx.	Outer Ø mm, approx.	Cu-weight kg/km	Weight kg/km, approx.
21607	50 G 1.5	16	26.8	749.0	1449.0
21608	61 G 1.5	16	29.6	912.0	1712.0
21609	2 x 2.5	14	8.5	48.0	115.0
21610	3 G 2.5	14	9.0	72.0	162.0
21611	4 G 2.5	14	9.8	96.0	196.0
21612	5 G 2.5	14	10.7	120.0	230.0
21613	7 G 2.5	14	12.7	168.0	312.0
21614	12 G 2.5	14	15.5	288.0	532.0
21615	18 G 2.5	14	18.6	432.0	762.0
21616	20 G 2.5	14	19.8	480.0	858.0
21617	25 G 2.5	14	23.1	600.0	998.0
21618	4 G 4	12	11.2	154.0	283.0
21619	5 G 4	12	12.3	192.0	349.0
21620	7 G 4	12	15.0	269.0	498.0
11017371	3 G 6	10	11.6	173.0	350.0
21621	4 G 6	10	12.7	230.0	432.0
21622	5 G 6	10	14.1	288.0	529.0
21623	7 G 6	10	17.2	403.0	782.0
21624	4 G 10	8	16.7	384.0	685.0
21625	5 G 10	8	18.6	480.0	817.0
21626	7 G 10	8	22.8	672.0	1023.0
11017372	3 G 16	6	17.6	461.0	792.0
21627	4 G 16	6	19.6	614.0	1042.0
21628	5 G 16	6	21.9	768.0	1292.0
21629	7 G 16	6	26.8	1075.0	1709.0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Hook-up Wire](#) category:

Click to view products by [Helukabel](#) manufacturer:

Other Similar products are found below :

[8918-BRN-1000](#) [8920-DK-BLU-1000](#) [01776.38.01](#) [M22759/16-14-5-500FT](#) [7046-BLACK-100](#) [7053-RED-1000](#) [F25935-000](#) [F60898-000](#)
[82A0811-4-9-G110](#) [83004-ORG-1000](#) [83004-YEL-100](#) [83005-LT-BLU-1000](#) [83025-VIO-1000](#) [8523-RED-100](#) [8524-WHT-100](#) [8525-ORG-1000](#) [8530-BLK-1000](#) [8530-LT-BLU-100](#) [8538-009-1000](#) [8597-LT-BLU-100](#) [956298-4](#) [138498-000](#) [BFWUL3239-24-PINK](#) [C2016A.12.05](#)
[C2016A.12.07](#) [C2065A.12.02](#) [8916-GRY-500](#) [8918-RED-100](#) [8919-DK-BLU-1000](#) [8919-YEL-100](#) [8920-YEL-100](#) [933205-000](#) [2841/7-YELLOW-1000](#) [2842/7-ORANGE-100](#) [2842/7-RED-1000](#) [2843/19-BLUE-100](#) [2843/19-GREEN-100](#) [2843/7-GREEN-100](#) [2845/7-RED-100](#)
[2855/1-BLACK-100](#) [2855/1-BROWN-1000](#) [285750-010](#) [956299-4](#) [961473-000](#) [298-SILVER-100](#) [3047-YELLOW-100](#) [3048-BLUE-1000](#)
[3048-YELLOW-1000](#) [3049-RED-100](#) [3049-YELLOW-100](#)