



Technical data

- Special-silicone single core with higher heat-resistance range adapted to DIN VDE 0250 part 1 and part 502
- **Temperature range**
flexing -25°C to +180°C
fixed installation -60°C to +180°C
- Permissible conductor **operating temperature** +180°C
- **Nominal voltage**
U₀/U 300/500 V
- **Test voltage**
2000 V
- **Breakdown voltage**
min. 5000 V
- **Minimum bending radius**
flexing 12,5x core Ø
fixed installation 5x core Ø
- **Radiation resistance**
up to 20x10⁶ cJ/kg (up to 20 Mrad)

Cable structure

- Tinned copper conductor, to DIN VDE 0295 cl.6, extra fine wire, BS 6360 cl.6, IEC 60228 cl.6 (single wire Ø 0,07 mm)
- Core insulation of silicone

Properties

- **Resistant to**
high molecular oils, fats from vegetables and animals, alcohols, plasticizers and clophenes, diluted acids, lyes and salt dissolution, oxidation substances, lake water, oxygen, ozone
- High flash points
- For laying as a fixed installation only in open or ventilated pipe systems as well as in ducts. Otherwise the mechanical properties of the silicone are reduced by the enclosed air at temperatures exceeding 90°C.

Tests

- Halogen-free acc. to DIN VDE 0482-754-1 / DIN EN 60754-1 / IEC 60754-1
- Corrosiveness of combustion gases acc. to DIN VDE 0482-754-2 / DIN EN 60754-2 / IEC 60754-2
- Behaviour in fire
no flame propagation acc. to DIN VDE 0482-332-1-2 / DIN EN 60332-1-2 / IEC 60332-1-2

Application

Special single cores for use in high, resp. low temperature areas. They are used mainly in the steel producing industries, in aviation industries as well as in ship building, cement, glas and ceramic factories. As this single cores are halogen-free, especially suited for use in power stations.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

| Cross-sec. mm ² | Outer Ø app. mm | Cop. weight kg / km | Weight app. kg / km | BK | BU | BN | RD | WH | GY | VT | YE | PK | GN | OG | BEIGE | TRANS | 2-col. |
|----------------------------|-----------------|---------------------|---------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------|
| Part no. 0,25 | 1,9 | 2,4 | 6,0 | 45101 | 45103 | 45104 | 45102 | 45105 | 45106 | 45107 | 45108 | 45111 | 45100 | 45109 | 45112 | 45110 | 45113 |
| Part no. 0,5 | 2,2 | 4,8 | 10,0 | 45201 | 45203 | 45204 | 45202 | 45205 | 45206 | 45207 | 45208 | 45211 | 45200 | 45209 | 45212 | 45210 | 45213 |
| Part no. 0,75 | 2,5 | 7,2 | 13,0 | 45301 | 45303 | 45304 | 45302 | 45305 | 45306 | 45307 | 45308 | 45311 | 45300 | 45309 | 45312 | 45310 | 45313 |
| Part no. 1 | 2,6 | 9,6 | 15,0 | 45401 | 45403 | 45402 | 45404 | 45405 | 45406 | 45407 | 45408 | 45411 | 45400 | 45409 | 45412 | 45410 | 45413 |
| Part no. 1,5 | 3,1 | 14,4 | 19,0 | 45501 | 45503 | 45504 | 45502 | 45505 | 45506 | 45507 | 45508 | 45511 | 45500 | 45509 | 45512 | 45510 | 45513 |
| Part no. 2,5 | 3,7 | 24,0 | 32,0 | 45601 | 45603 | 45604 | 45602 | 45605 | 45606 | 45607 | 45608 | 45611 | 45600 | 45609 | 45612 | 45610 | 45613 |
| Part no. 4 | 4,4 | 38,0 | 50,0 | 45701 | 45703 | 45704 | 45702 | 45705 | 45706 | 45707 | 45708 | 45711 | 45700 | 45709 | 45712 | 45710 | 45713 |
| Part no. 6 | 5,2 | 58,0 | 73,0 | 45801 | 45803 | 45804 | 45802 | 45805 | 45806 | 45807 | 45808 | 45811 | 45800 | 45809 | 45812 | 45810 | 45813 |
| Part no. 10 | 6,8 | 96,0 | 125,0 | 45901 | 45903 | 45904 | 45902 | 45905 | 45906 | 45907 | 45908 | 45911 | 45900 | 45909 | 45912 | 45910 | 45913 |

Dimensions and specifications may be changed without prior notice. (RK01)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Hook-up Wire](#) category:

Click to view products by [Helukabel](#) manufacturer:

Other Similar products are found below :

[8918-BRN-1000](#) [8920-DK-BLU-1000](#) [CR6328-000](#) [01776.38.01](#) [M22759/16-14-5-500FT](#) [7053-RED-1000](#) [7053-SLATE-1000](#) [F25935-000](#)
[F60898-000](#) [8055](#) [81044/12-18-9CS3209](#) [82A0811-4-9-G110](#) [83004-ORG-1000](#) [83005-LT-BLU-1000](#) [83025-VIO-1000](#) [8523-RED-100](#)
[8524-WHT-100](#) [8525-ORG-1000](#) [8530-BLK-1000](#) [8530-LT-BLU-100](#) [8538-009-1000](#) [8597-LT-BLU-100](#) [8898-BLK-100](#) [138498-000](#)
[E76065-000](#) [EPD50886A-20-9](#) [BFWUL3239-24-PINK](#) [C2015A.12.05](#) [C2015A.12.08](#) [C2015A.12.10](#) [C2015A.12.19](#) [C2016A.12.05](#)
[C2016A.12.07](#) [C2065A.12.02](#) [C77653-000](#) [220368-001](#) [8916-GRY-500](#) [8918-RED-100](#) [8919-DK-BLU-1000](#) [8919-YEL-100](#) [8920-YEL-100](#)
[9242833001](#) [933205-000](#) [2841/7-YELLOW-1000](#) [2842/7-ORANGE-100](#) [2842/7-RED-1000](#) [2843/19-BLUE-100](#) [2843/1-YELLOW-100](#)
[2844/7-BLACK-1000](#) [2845/7-RED-100](#)