


TOPGEBER 511 PVC

Feedback cables according to Siemens-,
Lenze- or Bosch Rexroth Standard with PVC-sheath for fixed or not constantly
movements



Technical data

- Special PVC feedback cable acc. to UL AWM style 20233 and CSA
- **Temperature range**
flexing -0°C to +60°C
fixed installation -20°C to +80°C
- **Nominal voltage**
acc. to Siemens 30 V
acc. to Bosch Rexroth and Lenze 300 V
- **A.c. test voltage**, 50 Hz
core/core 1500 V
core/screen 1000 V
- **Minimum bending radius**
flexing 15x cable Ø
fixed installation 6x cable Ø
min. 100.000 cycles

Cable structure

- Copper-conductor bare or tinned to DIN VDE 0295 cl.6, extra fine-wire, IEC 60228 cl.6
- Core insulation of special polypropylene
- Core colours on request
- Overall screening of tinned copper wire braid with tinned drain wire, coverage approx. 85%
- Polyester foil
- Outer sheath of PVC
- Sheath colour green (RAL 6018) acc. to DESINA® or orange

Properties

- Outer sheath of PVC, oilresistant
- Optimum compliance with requirements for elect romagnetic compatibility (EMC) by approx. 85% coverage from the braided screen
- These cables are produced to high quality specifications and conform to the DESINA®-standard
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

Tests

- PVC sheath flame retardant acc. to DIN EN 60332-1-1 bis -1-3 (VDE 0482-332-1-1 bis -1-3)

Note

- For a corresponding motor- and servocables please check chapter **TOPSERV® PVC**
- For drag chain capable encoder cables please check chapter **TOPGEBER 512 PUR**
- Brackets () indicate screen.
- SIEMENS product designations 6FX 5008-... are registered trademarks of Siemens AG and are to be used only for purposes of comparison.
- INDRAMAT product designations INK- are registered trademarks of Bosch-Rexroth AG and are to be used only for purposes of comparison.
- LENZE product designations are registered trademarks of LENZE AG, and are to be used only for purposes of comparison.
- DESINA®: Explanation: see introduction.

Application

Low cost alternativ to Motorcables with PUR Sheath for fix instalation or occasional moving applications. These low-capacitance incremental encoder cables or position feedback cables transmit the control pulses for positioning and operating characteristics of servomotors. These cables are used as connecting cables for tachos, brakes and pulse generators in industrial equipment, machine tools, control and automation equipment.

EMC = Electromagnetic compatibility

To optimize the EMC features we recommend a large round contact of the copper braiding on both ends.

☑ The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Part no.	No.cores x cross-sec. mm²	for system	OEM Part no.	Sheath colour	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
707417	(4 x 2 x 0,34 + 4 x 0,5)	Siemens	6FX 5008-1BD21	Green	8,9	70,3	117,8	-
707389	(3 x (2 x 0,14) + 4 x 0,14 + 2 x 0,5)	Siemens	6FX 5008-1BD41	Green	8,8	58,0	118,9	-
707390	(3 x (2 x 0,14) + 4 x 0,14 + 4 x 0,25 + 2 x 0,5)	Siemens	6FX 5008-1BD51	Green	9,6	70,7	137,7	-
803672	(2 x 2 x 0,22 + 1 x 2 x 0,34)	Siemens	6FX 5008-2DC00	Green	6,9	38,0	61,0	-
802471	(2 x 2 x 0,22)	Siemens	6FX 5008-1DC00	Green	6,9	35,0	71,0	-
705461	(4 x 2 x 0,25 + 2 x 0,5)	Bosch Rexroth	INK-0448	Orange	8,4	50,0	99,0	-
707392	(4 x 2 x 0,25 + 2 x 1,0)	Bosch Rexroth	INK-0209	Orange	8,8	64,0	119,0	-
707394	(4 x 2 x 0,14 + 4 x 1,0 + (4 x 0,14))	Bosch Rexroth	INK-0532	Orange	9,7	86,0	149,0	-
707077	3 x (2 x 0,14) + (2 x 0,5)	Lenze	-	Green	9,3	54,0	95,0	-
707397	4 x (2 x 0,14) + (2 x 1,0)	Lenze	-	Green	11,0	70,0	145,0	-
707398	3 x (2 x 0,14) + (3 x 0,14)	Lenze	-	Green	9,2	41,0	102,0	-

Dimensions and specifications may be changed without prior notice. (RN07)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [AC Power Leads](#) category:

Click to view products by [Helukabel](#) manufacturer:

Other Similar products are found below :

[62500-1774](#) [1300000023](#) [312033-01](#) [YP-61+YC12](#) [P28818-M2](#) [YP21A+YC13](#) [FTP-629Y603](#) [1702002600](#) [1700001947](#) [J2014004L001-CC](#)
[SHELF](#) [IL13-EU1-H05-3100-300-S](#) [P28976-M45](#) [BB-3271V86](#) [HFE/C19UO](#) [MWOC-PCA-3-3-2](#) [P29844-M5](#) [P29844-M10](#) [3-100-354](#)
[S002020062](#) [S007220307](#) [P28818-M6](#) [1019123](#) [387005324](#) [387005325](#) [59903000000](#) [VL-0136-14-200](#) [387007040](#) [387006821](#) [387006827](#)
[387006823](#) [387006932](#) [387006822](#) [AC06C13EU](#) [1036702](#) [AC06C05UK](#) [P28984-M2](#) [50365](#) [W-97023](#) [W-01528](#) [W-01529](#) [W-01530](#) [W-](#)
[01531](#) [W-97020](#) [W-97022](#) [W-97021](#) [W-97025](#) [W-97057](#) [W-97288](#) [W-97292](#) [W-97370](#)