


# BUS Cables

Profibus L2 7-wire

**HELUKABEL®**

PVC



## Type

### Cable structure

Inner conductor diameter:  
Core insulation:  
Core colours:  
Stranding element:  
Separator:  
Shielding 1:  
Total shielding:  
Outer sheath material:  
Cable external diameter:  
Outer sheath colour:

## Mobile use

### 1x2x0.64 mm (stranded)

Copper, bare (AWG 24/7)  
Foam-skin-PE  
rd, gn  
2 cores + 2 fillers stranded together  
Polyester foil over stranded bundle  
Al-Foil  
Cu braid, tinned  
PVC  
app. 7,8 mm ± 0,3 mm  
Violet similar to RAL 4001

## Electrical data

Characteristic impedance: 150 Ohm ± 10 %  
Conductor resistance, max.: 80 Ohm/km  
Insulation resistance, min.: 2 GOhm x km  
Loop resistance: 160 Ohm/km max.  
Mutual capacitance: 30 nF/km nom.  
Test voltage: 1,5 kV  
Attenuation: 9,6 kHz < 2,9 dB/km  
38,4 kHz < 4,6 dB/km  
4 MHz < 25,0 dB/km  
16 MHz < 49,0 dB/km

## Technical data

Weight: app. 70 kg/km  
bending radius, repeated: 94 mm  
Operating temperature range min.: -30°C  
Operating temperature range max.: +80°C  
Caloric load, approx. value: 1,20 MJ/m  
Copper weight: 24,00 kg/km

## Norms

Applicable standards: Profibus acc. to DIN 19245 T3 and EN50170  
Flame-retardant acc. IEC 60332-2-1  
UL Style: UL Style 2571

## Application

HELUKABEL® Profibus L2 7-wire for mobile applications in Profibus industrial networks. With its core design and the special PVC sheath, the type described here is suitable for normal mobile applications.

## Part no.

**800648**, Profibus L2

Dimensions and specifications may be changed without prior notice.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Multi-Conductor Cables](#) category:*

*Click to view products by [Helukabel](#) manufacturer:*

Other Similar products are found below :

[8916-GRY-100](#) [8917-BLK-100](#) [8917-GRN/YEL-100](#) [8918-GRN/YEL-100](#) [8920-BRN-1000](#) [8920-RED-1000](#) [89907-LT-DEC/GRY-500](#)  
[CR3909-000](#) [CR3927-000](#) [01342.35T.01](#) [01364.35T.01](#) [CS2885-000](#) [CS8782-000](#) [CS9912-000](#) [6200UE-NAT-U1000](#) [CTC-0062-20-9/5-9](#)  
[CTC-0062-22-9/5-9](#) [6304FE-877-U500](#) [6309UE-877-1000](#) [6320UE-NAT-U1000](#) [644833-000](#) [6502FE 8771000](#) [6504UE-877-U1000](#)  
[CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#)  
[CXA-0140-16-6/9-9CS2405](#) [CY0660-000](#) [720451-000](#) [730859-000](#) [MCC-USB-4-250](#) [752687-000](#) [768146-000](#) [773159-000](#) [7934A-BLK-](#)  
[1000](#) [8125-CHR-100](#) [820457-000](#) [8205-CHR-1000](#) [8240-BLK-U1000](#) [82723-NAT-1000](#) [82907-NAT-500](#) [83003-YEL-500](#) [83005-WHT-500](#)  
[83006-DK-GRN-100](#) [83008-WHT-1000](#) [83009-BLK-100](#) [83009-VIO-100](#)