


BUS Cables

HMCB200 fixed installed

 **HELUKABEL®**

PVC



Type

Cable structure

Inner conductor diameter:
Core insulation:
Core colours:
Stranding element:
Separator:
Shielding 1:
Total shielding:
Outer sheath material:
Cable external diameter:
Outer sheath colour:

Fixed installation, indoor

2x2x0,22qmm

Copper, bare (AWG 24/7)
Foam-skin-PE
gn, ye, pk, bu
Double core
Polyester foil over stranded bundle
Al-Foil
AL-Foil + braid
PVC
app. 6,85 mm ± 0,15 mm
Green similar to RAL 6018

Electrical data

Characteristic impedance: 100 Ohm ± 15 Ohm at 1 to 100 MHz
Conductor resistance, max.: 94,2 Ohm/km
Insulation resistance, min.: 1 GOhm x km
Loop resistance: 188,4 Ohm/km max.
Mutual capacitance: 50 nF/km nom.
Test voltage: 0,5 kV

Typical values

Frequency (MHz)	10	16	62,5	100
Attenuation (db/100m)	8,0	10,0	20,0	27,0
Next (db)	56,0	53,0	43,0	40,0
ACR (db)	48,0	43,0	23,0	13,0

Technical data

Weight: app. 63 kg/km
bending radius, repeated: 70 mm
Operating temperature range min.: -20°C
Operating temperature range max.: +80°C
Caloric load, approx. value: 0,92 MJ/m
Copper weight: 35,00 kg/km

Norms

Applicable standards: Flame-retardant acc. to IEC 60332-1-2
UL Style: AWM Style 2502 AWM I/II A/B 80°C 30V FT1

Application

HELUKABEL® HMCB200 for fixed installation and slight occasional movement, range up to 100m. This cable is used in Siemens Systems. Typical plugs are RJ45 Industrial IP20 Siemens or Y-Con RJ45 Yamaichi or round M-Connectors from Molex.

Part no.

802471, HMCB200

Dimensions and specifications may be changed without prior notice.

* Drive Cliq is registered trademark from Siemens AG.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Conductor Cables](#) category:

Click to view products by [Helukabel](#) manufacturer:

Other Similar products are found below :

[01342.35T.01](#) [CS2885-000](#) [CTC-0062-20-9/5-9](#) [644833-000](#) [6500FE-877-1000](#) [CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CY0660-000](#) [730859-000](#) [MCC-USB-4-250](#) [768146-000](#) [773159-000](#) [820457-000](#) [82907-NAT-500](#) [83003-YEL-500](#) [83005-WHT-500](#) [83023-YEL-500](#) [83027-RED-100](#) [83029-GRN-100](#) [8302-CHR-500](#) [83046-RED-100](#) [8305-CHR-100](#) [83306E-WHT-100](#) [83333-WHT-100](#) [8334-060-1000](#) [83349E-WHT-100](#) [83652-RED-100](#) [8404-060-500](#) [8441-BLK-1000](#) [8450-BLK-1000](#) [8451-GRY-U500](#) [8459-CHR-500](#) [8465-CHR-1000](#) [8467-CHR-1000](#) [8469 060100](#) [8469-CHR-1000](#) [8471-CHR-1000](#) [8472-BLK-250](#) [8501-ORG-100](#) [8501-RED-100](#) [8503-WHT/BLU-100](#) [8520-BRN-100](#) [8520-GRY-100](#) [8523-GRY-100](#) [8523-GRY-1000](#) [8523-LT-BLU-25](#) [8523-ORG-1000](#) [8524-DK-BLU-100](#)