JUMBO-FP Flange connection



Protection class: IP 54

Temperature range: -40°C up to +115°C

JUMBO-FP

One-piece straight flange connection. Suitable for parallel-coiled JUMBO protection tubes.

Application

- Plant and machine construction
- Robotics
- Automation technology
- Vehicle construction and shipbuilding
- Railway technology
- Installation technology
- Control cabinet construction

Material

Polyamide PA 6

Flammability acc. to UL 94: V0

- halogen-free
- cadmium-free

Properties

Resistant to a multitude of

- Fuels
- Mineral oils
- Greases
- Weak bases
- Weak acids

Note

Additional seal increases protection classification to IP 65 JUMBO sealing set: Set contains 1 x o-ring and 1x cellular rubber

Flange connection

Part no.	Part no.	Suitable for ND	Unit	Net EUR/ 100 items at a purchase of			
grey	black			up to 100	101 - 500	501 - 1000	
90402	920368	70,0	1	o. r.	o. r.	o. r.	
90403	920369	95,0	1	o. r.	o. r.	o. r.	

Sealing set

Part no.	Colour	Suitable for ND	Unit	Net EUR/ 100 items at a purchase of						
				up to 100	101 - 500	501 - 1000				
90406	black	70,0	1	o. r.	o. r.	o. r.				
90407	black	95,0	1	o. r.	o. r.	o. r.				

Dimensions and specifications may be changed without prior notice.

o. r. = on request



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Conduit Fittings & Accessories category:

Click to view products by Helukabel manufacturer:

Other Similar products are found below:

M3231GAB M3231GAC M3231GAE M3231GL M3231GN M3231GT VC-937-16/RED VC-1125-16/RED DM0240-1/2A 3408B G6002 M4340GAE C2016-P C2012-P 3407B 1660-P 561-87BG11BLK 561-75BG11B 1.511.1601.14 1.533.1201.50 1.533.1601.51 1.533.2001.51 1.533.4001.50 1.533.5001.50 BVNV-P428 BVBV-P366 2276 2663-P 3405B C2070-P 3582V 2643-P 4975 2644-P 2955 M50 2404-P C2008-P 2723-P 2291 2133-P 3048F VC12516 RC156-0500 DM0523-1/2A 1035A DMS0250-1A DMS0313-1A 1040A 1050A R1/8A