

# HELUcond PA6-S corrugated tubes, polyamide

medium stress



## HELUcond PA6-S

Cable protection tube for medium to heavy-duty applications.

### Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

### Material

Mod. Polyamide PA 6

Flammability acc. to UL 94: V2

- halogen-free
- cadmium-free

### Properties

resistant to a multitude of

- fuels
- mineral oils
- greases
- weak bases
- weak acids

### Note

Suitable connection glands:  
HELUquick, HSSV.

### Technical data

Temperature range: -40°C up to +120°C  
Temperature range temporary up to +150°C

Capacity/100mm NW 17: approx. 350 N

### fine profile

Part no. grey	Part no. black	trade size mm	Inner Ø mm	Outer Ø mm	Per metres	Net EUR/100 metres at a purchase of		
						up to 100	101 - 500	501 - 1000
920154	920155	4,5	4,5	7,1	100	o. r.	o. r.	o. r.
92724	92723	7,5	6,6	10,0	50	o. r.	o. r.	o. r.
92676	92713	10,0	9,8	12,8	50	o. r.	o. r.	o. r.
92677	92714	12,0	12,3	15,7	50	o. r.	o. r.	o. r.
92678	92715	17,0	16,6	21,1	50	o. r.	o. r.	o. r.
92679	92716	23,0	23,1	28,4	50	o. r.	o. r.	o. r.
92685	92717	29,0	28,9	34,5	25	o. r.	o. r.	o. r.
92686	92718	37,0	34,0	42,2	25	o. r.	o. r.	o. r.
92687	92719	50,0	45,6	53,8	25	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Non-Heat Shrink Tubing and Sleeves](#) category:*

*Click to view products by [Helukabel](#) manufacturer:*

Other Similar products are found below :

[601203-000](#) [CTA-0053](#) [8429-9](#) [8445-7.5](#) [8450](#) [120-116-1-1-09BE](#) [120-116-1-1-09BF](#) [120-116-1-1-09BP](#) [120-116-1-1-12BE](#) [120-116-1-1-12BP](#) [120-123-06](#) [120-123-10](#) [120-125-12BL](#) [120-125-12R](#) [120-125-20R](#) [120-126-09](#) [120-126-09BL](#) [120-126-12](#) [120-126-12BL](#) [120-126-52](#) [120-126-52BL](#) [120-104-12](#) [120-105-1-1-06BE](#) [120-105-1-1-06CE](#) [120-108-10B](#) [120-116-1-1-06BP](#) [120-116-1-1-10BP](#) [120-116-1-1-12BF](#) [120-123-12](#) [120-125-09](#) [120-125-12](#) [120-125-12Y](#) [120-125-52BL](#) [120-S002-12](#) [HC1B-7008-0375-0](#) [120-S001-09](#) [120-S002-09](#) [121-101-1-1-56BFC](#) [121-101-1-1-64BFC](#) [121-103-1-1-12BFTTH](#) [RAY-90-3.0\(100\)](#) [20675-2](#) [8S42-100FR-CS8184](#) [SAS-115-1-1048-1X](#) [SAS-160-1-1048-1X](#) [RAY-103-10.0\(100\)](#) [RAY-103-4.0\(100\)](#) [4627-S](#) [3-1991136-0](#) [561-SL1000PP](#)