

HELUcond PA6-L Corrugated tubes, polyamide

Weak stress



HELUcond PA6-L

Cable protection tube for weak to medium stress applications.
Capacity/100mm NW 17: approx. 250 N

Application

- Plant and machine construction
- Automation technology
- Vehicle construction and shipbuilding
- Installation technology
- Control cabinet construction

Material

Mod. Polyamide PA 6
Flammability acc. to UL 94: V2

- halogen-free
- phosphor-free

Properties

Resistant to a multitude of

- Fuels
- Mineral oils
- Greases
- Weak bases
- Weak acids

Note

Suitable connection glands:
HELUquick, HSSV.

Technical data

Temperature range: -40°C up to +120°C
Temperature range temporary up to +150°C

Fine profile

| Part no. grey | Part no. black | Nominal size mm | Inner Ø mm | Outer Ø mm | Per metres | Net EUR/ 100 metres at a purchase of | | |
|------------------|-------------------|--------------------|---------------|---------------|---------------|--------------------------------------|-----------|------------|
| | | | | | | up to 100 | 101 - 500 | 501 - 1000 |
| 99610 | 99620 | 7,5 | 6,8 | 10,0 | 50 | o. r. | o. r. | o. r. |
| 99611 | 99621 | 10,0 | 10,0 | 12,8 | 50 | o. r. | o. r. | o. r. |
| 99612 | 99622 | 12,0 | 12,5 | 15,7 | 50 | o. r. | o. r. | o. r. |
| 99613 | 99623 | 14,0 | 14,4 | 18,5 | 50 | o. r. | o. r. | o. r. |
| 99614 | 99624 | 17,0 | 16,8 | 21,1 | 50 | o. r. | o. r. | o. r. |
| 99615 | 99625 | 23,0 | 23,4 | 28,4 | 50 | o. r. | o. r. | o. r. |
| 99616 | 99626 | 29,0 | 29,2 | 34,5 | 25 | o. r. | o. r. | o. r. |
| 99617 | 99627 | 37,0 | 34,0 | 41,8 | 25 | o. r. | o. r. | o. r. |
| 99618 | 99628 | 50,0 | 46,0 | 53,8 | 25 | o. r. | o. r. | o. r. |

Dimensions and specifications may be changed without prior notice.

o. r. = on request

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Spiral Wraps, Sleeves, Tubing & Conduit](#) category:

Click to view products by [Helukabel](#) manufacturer:

Other Similar products are found below :

[601203-000](#) [CTA-0053](#) [8426-11](#) [8429-9](#) [8445-7.5](#) [120-104-24](#) [120-113-16B](#) [120-116-1-1-09BE](#) [120-116-1-1-09BF](#) [120-116-1-1-09BP](#) [120-116-1-1-12BE](#) [120-116-1-1-12BP](#) [120-116-1-1-20BP](#) [120-116-1-1-32BE](#) [120-117-40](#) [120-123-06](#) [120-123-10](#) [120-123-14](#) [120-123-16](#) [120-125-12BL](#) [120-125-12R](#) [120-125-16](#) [120-125-16R](#) [120-125-16Y](#) [120-125-20R](#) [120-125-24Y](#) [120-125-28](#) [120-125-28R](#) [120-125-32](#) [120-125-32R](#) [120-125-40](#) [120-125-56](#) [120-126-09](#) [120-126-09BL](#) [120-126-12](#) [120-126-12BL](#) [120-126-14](#) [120-126-16](#) [120-126-16BL](#) [120-126-20](#) [120-126-20BL](#) [120-126-20R](#) [120-126-24](#) [120-126-28](#) [120-126-32](#) [120-126-40BL](#) [120-126-52](#) [120-126-52BL](#) [120-104-12](#) [120-104-20](#)