

# HELUcond PA6-L Corrugated tubes, polyamide

Weak stress



## HELUcond PA6-L

Cable protection tube for weak to medium stress applications.  
Capacity/100mm NW 17: approx. 250 N

### Application

- Plant and machine construction
- Automation technology
- Vehicle construction and shipbuilding
- Installation technology
- Control cabinet construction

### Material

Mod. Polyamide PA 6  
Flammability acc. to UL 94: V2

- halogen-free
- phosphor-free

### Properties

Resistant to a multitude of

- Fuels
- Mineral oils
- Greases
- Weak bases
- Weak acids

### Note

Suitable connection glands:  
HELUquick, HSSV.

### Technical data

Temperature range: -40°C up to +120°C  
Temperature range temporary up to +150°C

### Fine profile

| Part no.<br>grey | Part no.<br>black | Nominal size<br>mm | Inner Ø<br>mm | Outer Ø<br>mm | Per<br>metres | Net EUR/ 100 metres at a purchase of |           |            |
|------------------|-------------------|--------------------|---------------|---------------|---------------|--------------------------------------|-----------|------------|
|                  |                   |                    |               |               |               | up to 100                            | 101 - 500 | 501 - 1000 |
| 99610            | 99620             | 7,5                | 6,8           | 10,0          | 50            | o. r.                                | o. r.     | o. r.      |
| 99611            | 99621             | 10,0               | 10,0          | 12,8          | 50            | o. r.                                | o. r.     | o. r.      |
| 99612            | 99622             | 12,0               | 12,5          | 15,7          | 50            | o. r.                                | o. r.     | o. r.      |
| 99613            | 99623             | 14,0               | 14,4          | 18,5          | 50            | o. r.                                | o. r.     | o. r.      |
| 99614            | 99624             | 17,0               | 16,8          | 21,1          | 50            | o. r.                                | o. r.     | o. r.      |
| 99615            | 99625             | 23,0               | 23,4          | 28,4          | 50            | o. r.                                | o. r.     | o. r.      |
| 99616            | 99626             | 29,0               | 29,2          | 34,5          | 25            | o. r.                                | o. r.     | o. r.      |
| 99617            | 99627             | 37,0               | 34,0          | 41,8          | 25            | o. r.                                | o. r.     | o. r.      |
| 99618            | 99628             | 50,0               | 46,0          | 53,8          | 25            | o. r.                                | o. r.     | o. r.      |

Dimensions and specifications may be changed without prior notice.

o. r. = on request

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Spiral Wraps, Sleeves, Tubing & Conduit](#) category:*

*Click to view products by [Helukabel](#) manufacturer:*

Other Similar products are found below :

[601203-000](#) [CTA-0053](#) [8426-11](#) [8429-9](#) [8445-7.5](#) [120-104-24](#) [120-113-16B](#) [120-116-1-1-09BE](#) [120-116-1-1-09BF](#) [120-116-1-1-09BP](#) [120-116-1-1-12BE](#) [120-116-1-1-12BP](#) [120-116-1-1-20BP](#) [120-116-1-1-32BE](#) [120-117-40](#) [120-123-06](#) [120-123-10](#) [120-123-14](#) [120-123-16](#) [120-125-12BL](#) [120-125-12R](#) [120-125-16](#) [120-125-16R](#) [120-125-16Y](#) [120-125-20R](#) [120-125-24Y](#) [120-125-28](#) [120-125-28R](#) [120-125-32](#) [120-125-32R](#) [120-125-40](#) [120-125-56](#) [120-126-09](#) [120-126-09BL](#) [120-126-12](#) [120-126-12BL](#) [120-126-14](#) [120-126-16](#) [120-126-16BL](#) [120-126-20](#) [120-126-20BL](#) [120-126-20R](#) [120-126-24](#) [120-126-28](#) [120-126-32](#) [120-126-40BL](#) [120-126-52](#) [120-126-52BL](#) [120-104-12](#) [120-104-20](#)