

HELUcond CO-PA Corrugated tubes, polyamide

Dividable



HELUcond CO-PA

The dividable and reclosable cable protection tube for subsequent mechanical protection.

- Trouble-free retrofitting
- High mechanical strength
- Simple installation of pre-fabricated cables
- Repair of existing systems

Application

- Plant and machine construction
- Automation technology
- Vehicle construction and shipbuilding
- Railway technology
- Installation technology
- Control cabinet construction

Material

Polyamide 6
UV-resistant

Flammability acc. to UL 94: HB

- halogen-free

Properties

Resistant to a multitude of:

- Fuels
- Mineral oils
- Greases
- Weak bases
- Weak acids

Note

Suitable connection glands:
COV

Technical data

Temperature range: -40°C up to +120°C
Temperature range temporary up to +150°C

Part no. black	Nominal size mm	Inner Ø mm	Outer Ø mm	Per metres	Net EUR/ 100 metres at a purchase of		
					up to 100	101 - 500	501 - 1000
90061	10,0	8,8	13,5	50	o. r.	o. r.	o. r.
90062	14,0	13,2	18,7	50	o. r.	o. r.	o. r.
90063	20,0	20,2	25,7	50	o. r.	o. r.	o. r.
90064	23,0	23,9	31,3	50	o. r.	o. r.	o. r.
90065	37,0	32,5	43,2	25	o. r.	o. r.	o. r.
90066	45,0	43,1	54,2	25	o. r.	o. r.	o. r.
920179	70,0	67,0	79,8	10	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Spiral Wraps, Sleeves, Tubing & Conduit](#) category:

Click to view products by [Helukabel](#) manufacturer:

Other Similar products are found below :

[601203-000](#) [CTA-0053](#) [8426-11](#) [8429-9](#) [8445-7.5](#) [8450](#) [120-104-24](#) [120-113-16B](#) [120-116-1-1-09BE](#) [120-116-1-1-09BF](#) [120-116-1-1-09BP](#)
[120-116-1-1-12BE](#) [120-116-1-1-12BP](#) [120-116-1-1-20BP](#) [120-116-1-1-32BE](#) [120-117-40](#) [120-123-06](#) [120-123-10](#) [120-123-14](#) [120-123-16](#)
[120-125-12BL](#) [120-125-12R](#) [120-125-16](#) [120-125-16R](#) [120-125-16Y](#) [120-125-20R](#) [120-125-24Y](#) [120-125-28](#) [120-125-28R](#) [120-125-32](#)
[120-125-32R](#) [120-125-40](#) [120-125-56](#) [120-126-09](#) [120-126-09BL](#) [120-126-12](#) [120-126-12BL](#) [120-126-14](#) [120-126-16](#) [120-126-16BL](#) [120-](#)
[126-20](#) [120-126-20BL](#) [120-126-20R](#) [120-126-24](#) [120-126-28](#) [120-126-32](#) [120-126-40BL](#) [120-126-52](#) [120-126-52BL](#) [120-104-12](#)