



## Heyco® Original Strain Relief Bushings

Straight-Thru for Round Cables

.875" (22,2 mm) to 1.187" (30,1 mm) Mounting Holes


Fit 1/2" or 3/4" Electrical Knock-out Hole Sizes

- **Protects the lifeline of your electric/ electronic products** by absorbing the forces of pull, push, and twist that may be exerted on the flexible power cord.
- Securely anchors, insulates, and protects cables at panel entry points.
- Sizes SR 7-Series to SR 9-Series for mounting hole diameters from .875" (22,2 mm) to 1.187" (28,6 mm).
- Sizes for thin .062" (1,6 mm) panel available: SR 8N-2  
See chart for details.
- See page 4-38 for corresponding **Mounting Hole Plugs** which can be used to fill blank/unused Mounting Holes and thus allow for a single panel design for multiple applications.
- Consult Heyco for other wire types and sizes.
- See pages 4-27 & 4-28 for SR assembly tools.
- For Double D Mounting Hole Punches, see page 4-30.


WILL FIT THESE CABLES				PANEL DIMENSIONS						PART NO.		DESCRIPTION	PART DIM.		Mounting Hole Plug PART NO.						
UL Type	AWG/ Conductors	Approximate Size		A Mounting Hole Dia.		B To Prevent Rotation		Finished Fit Panel Thickness*		Black	White		C BODY LENGTH								
		in.	mm.	in.	mm.	in.	mm.	in.	mm.			in.	mm.								
SJ, SJT & SJO	16/2	.325	8,3	.875	22,2	.770	19,6	.125	3,2	1240	1241	SR 7K-2	.750	19,1	2509						
	18/3	.330	8,4																		
	14/2	.350	8,9																		
	16/3	.355	9,0																		
	18/4	.360	9,1																		
Same as SR 7K-2 above except								See Schematic		.125	3,2	1271	1272	SR 7KR-2	.750	19,1	2509				
SJT	14/3	.370	9,4	.875	22,2	.770	19,6	.125	3,2	1247	1248	SR 7W-2	.750	19,1	2509						
	12/3	.425	10,8																		
S, SO, & ST	18/2	.390	9,9																		
	18/3	.405	10,3																		
	16/2	.405	10,3																		
16/3	.430	10,9	Same as SR 7W-2 above except								.200	5,1	1250	1251	SR 7L-2	.750	19,1	consult Heyco			
SJT	12/3	.425-.475	10,8-12,1	.875	22,2	.840	21,3	.125	3,2	1497	1498	SR 31-2	.812	20,6	2509						
S & ST	14/2	.530	13,5																		
	14/3	.560	14,2																		
12/2	.600	15,3	Same as SR 8N-2 above except								.125	3,2	1260	1261	SR 8P-2	.812	20,6	2509			
S	12/2	.600	15,2	1.093	27,7	1.000	25,4	.281	7,1	1287	1288	SR 9P-2	1.000	25,4	2717						
	12/3	.635	16,1	1.093	27,7																
	10/2	.640	16,3	1.093	27,7																
S, SO & ST	10/3	.690	17,5	1.187	30,2	Same as SR 8N-2 above except								.187	4,8	1274	1275	SR 8L-1	.812	20,6	consult Heyco
						SRDT	10/4														

Standard color black. Consult Heyco for other colors.


\*Maximum Panel Thickness. Part has additional clearance. Consult Heyco for your Custom Finished Fit Panel Thickness.




FOR SR-7KR-2 ONLY



STANDARD MOUNTING HOLES



ELONGATED MOUNTING HOLE



Quick Specs

Material	Nylon 6/6
Certifications	Recognized under the Component Program of Underwriters' Laboratories File E15331 Certified by the Canadian Standards Association File 8919
Flammability Rating	94V-2
Temperature Range	-.04°F (-18°C) to 221°F (105°C)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Cable Glands, Strain Reliefs & Cord Grips](#) category:*

*Click to view products by [Heyco](#) manufacturer:*

Other Similar products are found below :

[1218](#) [1300980012](#) [1300980105](#) [DBZM-6828](#) [1498](#) [915](#) [300623](#) [5632NM](#) [1124](#) [1151](#) [561-MP6P4WH](#) [5534M](#) [9000005073](#) [52104486](#)  
[5315817](#) [N16 025 0112 1](#) [N16 020 0112 1](#) [M6106](#) [7422](#) [NG-9516 Gasket](#) [N16 016 0112 1](#) [NG-9514 Gasket](#) [52006151](#) [2704](#) [1.097.2012.50](#)  
[1.152.1300.01](#) [1.152.2000.50](#) [1.152.2100.01](#) [1.152.4000.50](#) [1.209.1218.70](#) [1.209.2100.15](#) [1.209.6400.71](#) [1.609.1100.01](#) [1.609.2900.15](#)  
[1.609.3200.52](#) [1.609.5000.51](#) [1.609.6300.50](#) [1.676.2500.50](#) [53112705](#) [53112715](#) [53112735](#) [53119073](#) [54115405](#) [52004120](#) [52001894](#)  
[53018160](#) [APGPG36BA](#) [1300990004](#) [1.033.0913.01](#) [1.033.1116.01](#)