





- **Smooth, glossy head** provides easy glide and shiny finish.
- Close unneeded panel openings.
- Locking fingers snap into holes with fingertip pressure for quick and easy installation.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Multiple sizes for use in .187” (4,7 mm) to 2.000” (50,8 mm) diameter holes.
- Lock firmly in panel up to .125” (3,2 mm) thick. (G parts)
- For use in panels thicker than .125” (3,2 mm). (GPT parts)
- Withstand a push back force of 35 pounds.



SINGLE PANEL THICKNESS DESIGN



MULTIPLE PANEL THICKNESS DESIGN

## Heyco® Glossy and Thick Panel Glossy Plugs

Mounting Hole Diameter Range: .187” (4,7 mm) to 2.000” (50,8 mm)

| MOUNTING HOLE DIAMETER  | PART NO. |       | DESCRIPTION | PART DIMENSIONS    |     |                     |  |
|---|----------|-------|-------------|--------------------|-----|---------------------|--|
|   | Black    | White |             | A<br>Head Diameter |     | B<br>Overall Height |  |
| in.   mm.   |          |       |             | in.   mm.          |     | in.   mm.           |  |
| Single Locking Step for Panel Thickness up to .062” (1,6 mm)    |          |       |             |                    |     |                     |  |
| .187   4,7  | 2590     | 2591  | DP 187*     | .25   6,4          |     | .23   5,9           |  |
| .250   6,4  | 2600     | 2601  | G 250       | .31   7,9          |     | .31   7,9           |  |
| .312   7,9  | 2610     | 2611  | G 312       | .38   9,5          |     |                     |  |
| Multiple Locking Steps for Panel Thickness up to .125” (3,2 mm) |          |       |             |                    |     |                     |  |
| .375   9,5  | 2620     | 2621  | G 375       | .47   11,9         | .41 | 10,3                |  |
| .437   11,1   | 2630     | 2631  | G 437       | .53   13,5         |     |                     |  |
| .500   12,7   | 2640     | 2641  | G 500       | .56   14,3         |     |                     |  |
| .562   14,3   | 2650     | 2651  | G 562       | .66   16,7         |     |                     |  |
| .625   15,9   | 2660     | 2661  | G 625       | .73   18,6         |     |                     |  |
| .750   19,1   | 2680     | 2681  | G 750       | .86   21,8         | .45 | 11,5                |  |
| .875   22,2   | 2700     | 2701  | G 875       | .95   24,2         |     |                     |  |
| 1.000   25,4  | 2710     | 2711  | G 1000      | 1.13   28,6        |     |                     |  |
| 1.093 - 1.125   27,8 - 28,6                                     | 2720     | 2721  | G 1093      | 1.22   30,9        |     |                     |  |
| 1.187   30,1  | 2730     | 2731  | G 1187      | 1.31   33,3        |     |                     |  |
| 1.375   34,9  | 2760     | 2761  | G 1375      | 1.49   37,7        | .56 | 14,3                |  |
| 1.500   38,1  | 2770     | 2771  | G 1500      | 1.61   40,8        |     |                     |  |
| 1.750   44,4  | 2780     | 2781  | G 1750      | 1.88   47,6        |     |                     |  |
| 2.000   50,8  | 2795     | 2796  | G 2000      | 2.13   54,8        |     |                     |  |
| Multiple Locking Steps for Panel Thickness up to .250” (6,4 mm) |          |       |             |                    |     |                     |  |
| .500   12,7   | 2430     | 2431  | GPT 500     | .56   14,3         | .52 | 13,1                |  |
| .625   15,9   | 3134     | 3135  | GPT 625**   | .72   18,3         |     |                     |  |
| .750   19,1   | 3136     | 3137  | GPT 750**   | .85   21,6         |     |                     |  |
| .875   22,2   | 3138     | 3139  | GPT 875     | .95   24,2         |     |                     |  |
| 1.000   25,4  | 3140     | 3141  | GPT 1000    | 1.13   28,6        |     |                     |  |
| 1.093 - 1.125   27,8 - 28,6                                     | 3142     | 3143  | GPT 1093    | 1.22   30,9        | .56 | 14,3                |  |
| 1.187   30,1  | 3144     | 3145  | GPT 1187    | 1.31   33,3        |     |                     |  |
| 1.375   34,9  | 2432     | 2433  | GPT 1375    | 1.49   37,7        |     |                     |  |
| 1.500   38,1  | 2428     | 2429  | GPT 1500    | 1.61   40,8        |     |                     |  |
| 1.750   44,4  | 2436     | 2437  | GPT 1750    | 1.88   47,6        |     |                     |  |
| 2.000   50,8  | 2438     | 2439  | GPT 2000    | 2.16   54,8        |     |                     |  |

Standard color black. Consult Heyco for other colors.

\*Convex, glossy finished head tapers to a thin edge.

\*\* Single locking steps for Panel Thickness up to .250” (6,4 mm)

Quick Specs

Material Certifications



Nylon 6/6  
Recognized under the Component Program of Underwriters' Laboratories, File E51579



Certified by Canadian Standards Association, File 8919

Flammability Rating  
Temperature Range

94V-2  
-40°F (-40°C) to 221°F (105°C)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Conduit Fittings & Accessories](#) category:*

*Click to view products by [Heyco](#) manufacturer:*

Other Similar products are found below :

[M3231GAB](#) [M3231GAC](#) [M3231GAE](#) [M3231GL](#) [M3231GN](#) [M3231GT](#) [VC-937-16/RED](#) [VC-562-16/RED](#) [VC-1125-16/RED](#) [DM0240-1/2A](#) [3408B](#) [G6002](#) [M4340GAE](#) [C2016-P](#) [C2012-P](#) [3407B](#) [1660-P](#) [561-87BG11BLK](#) [561-75BG11B](#) [BVNV-P428](#) [BVBV-P366](#) [2276](#) [2663-P](#) [3405B](#) [C2070-P](#) [3582V](#) [4975](#) [2644-P](#) [2955](#) [M50](#) [2404-P](#) [2291](#) [2133-P](#) [3048F](#) [VC12516](#) [RC156-0500](#) [DM0523-1/2A](#) [1035A](#) [DMS0250-1A](#) [DMS0313-1A](#) [1040A](#) [1050A](#) [R1/8A](#) [DMPC0490-1/2A](#) [DMPC0521-1/2A](#) [DMPC0552-1/2A](#) [1070A](#) [R1/2A](#) [E1-7/8B](#) [061A](#) [R3/4A](#)