




Heyco® Dome Plugs

Mounting Hole Diameter Range: .187" (4,7 mm) to 6.000" (152,4 mm)

- Close unneeded panel holes and electrical knockouts.
- Quick and easy installation.
- Convex, matte finish head tapers to thin edge (Except DP-187).
- Multiple sizes for use in .187" (4,7 mm) to 6.000" (152,4 mm) diameter holes.
- Lock firmly into panel up to .250" (6,4 mm) thick.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Approximate Head Thickness: .062" (1,6 mm). Thickness may vary.
- For Snap-In Metric Dome Plugs see page 6-28.

| MOUNTING HOLE DIAMETER in. mm. | PART NO. | | | DESCRIPTION | PART DIMENSIONS | | | | |
|---|----------------------------|----------------------------|------------------|-----------------------|---------------------------------|-------|----------------------------------|------|-----|
| | Black | White | Colors xx** | | A Head Diameter in. mm. | | B Overall Height in. mm. | | |
| Single Locking Step for Panel Thickness up to .062" (1,6 mm) | | | | | | | | | |
| .187 4,7 | 2590 | 2591 | 2592xx | DP 187* | .25 | 6,4 | .23 | 5,9 | |
| .250 6,4 | 2607 2603 | 2608 2604 | 2609xx 2605xx | DP 250-040† DP 250 | .31 | 7,9 | .31 | 7,9 | |
| .312 7,9 | 2613 | 2614 | 2615xx | DP 312 | .38 | 9,5 | | | |
| Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm) | | | | | | | | | |
| .375 9,5 | 2617 | 2618 | 2619xx | DP 375 | .47 | 11,9 | .41 | 10,3 | |
| .437 11,1 | 2633 | 2634 | 2635xx | DP 437 | .53 | 13,5 | | | |
| .500 12,7 | 2643 | 2644 | 2645xx | DP 500 | .56 | 14,2 | | | |
| .562 14,3 | 2653 | 2654 | 2655xx | DP 562 | .66 | 16,7 | | | |
| .625 15,9 | 2663 | 2664 | 2665xx | DP 625 | .72 | 18,2 | | | |
| .687 17,4 | 2673 | 2674 | 2675xx | DP 687 | .78 | 19,8 | | | |
| .750 19,1 | 2683 | 2684 | 2685xx | DP 750 | .92 | 23,4 | | | |
| .812 20,6 | 2693 | 2694 | 2695xx | DP 812 | .99 | 25,1 | | | |
| .875 22,2 | 2703 | 2704 | 2705xx | DP 875 | 1.02 | 25,8 | | | |
| 1.000 25,4 | 2713 | 2714 | 2715xx | DP 1000 | 1.20 | 30,6 | | | |
| 1.093 - 1.125 27,8 - 28,6 | 2723 | 2724 | 2725xx | DP 1093 | 1.22 | 30,9 | .45 | 11,5 | |
| 1.187 30,1 | 2733 | 2734 | 2735xx | DP 1187 | 1.33 | 33,8 | | | |
| 1.250 31,7 | 2740 | 2741 | 2742xx | DP 1250 | 1.38 | 34,9 | | | |
| 1.375 34,9 | 2753 | 2754 | 2755xx | DP 1375 | 1.50 | 38,1 | | | |
| 1.500 38,1 | 2763 | 2764 | 2765xx | DP 1500 | 1.67 | 42,4 | | | |
| 1.750 44,5 | 2773 | 2774 | 2775xx | DP 1750 | 1.92 | 48,7 | | | |
| 2.000 50,8 | 2783 | 2784 | 2785xx | DP 2000 | 2.17 | 55,1 | | | .47 |
| Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm) | | | | | | | | | |
| 2.093 - 2.125 53,2 - 54,0 | 2403 | 2404 | *** | DP 2.093 | 2.34 | 59,9 | .75 | 19,1 | |
| 2.250 57,2 | 2411 | 2412 | 2413xx | DP 2.25 | 2.48 | 63,0 | .75 | 19,1 | |
| 2.500 63,5 | 2790 | 2791 | 2792xx | DP 2.5 | 2.71 | 68,8 | | | |
| 3.000 76,2 | 2455 | 2456 | 2457xx | DP 3.0 | 3.16 | 80,3 | .74 | 18,8 | |
| 3.375 85,7 | 2482 | 2483 | *** | DP 3.375 | 3.66 | 92,9 | .75 | 19,1 | |
| 3.500 88,9 | 2464 | 2465 | 2466xx | DP 3.5 | 3.66 | 92,9 | | | |
| 4.000 101,6 | 2473 | 2474 | 2475xx | DP 4.0 | 4.17 | 105,8 | .71 | 18,0 | |
| 5.000 127,0 | 2451 | 2452 | *** | DP 5.0 | 5.24 | 133,0 | .75 | 19,1 | |
| 6.000 152,4 | 2453 | 2454 | *** | DP 6.0 | 6.22 | 157,9 | .78 | 19,8 | |



Standard colors black and white. Consult Heyco for other colors (see below)
 *Convex, glossy finish head.

** xx indicates that, following the color match process, Heyco adds a two letter suffix to the Root Part No. shown. This suffix will identify your particular CUSTOM Color selection. Consult Heyco for molded nylon color chips for accurate matching. For details as well as information regarding our Stock Colors, see page 6-51.

***Consult Heyco for root Part No.
 † Max panel thickness is .040" (1,0 mm)

Quick Specs

| | |
|---------------------|---|
| Material | Nylon 6/6 |
| Certifications | Recognized under the Component Program of Underwriters' Laboratories File E51579 Certified by the Canadian Standards Association File 8919 |
| Flammability Rating | 94V-2 |
| Temperature Range | -40°F (-40°C) to 221°F (105°C) |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Conduit Fittings & Accessories](#) category:

Click to view products by [Heyco](#) manufacturer:

Other Similar products are found below :

[M3231GAB](#) [M3231GAC](#) [M3231GAE](#) [M3231GL](#) [M3231GN](#) [M3231GT](#) [VC-937-16/RED](#) [VC-562-16/RED](#) [VC-1125-16/RED](#) [DM0240-1/2A](#) [3408B](#) [G6002](#) [M4340GAE](#) [C2016-P](#) [C2012-P](#) [3407B](#) [1660-P](#) [561-87BG11BLK](#) [561-75BG11B](#) [BVNV-P428](#) [BVBV-P366](#) [2276](#) [2663-P](#) [3405B](#) [C2070-P](#) [3582V](#) [4975](#) [2644-P](#) [2955](#) [M50](#) [2404-P](#) [2291](#) [2133-P](#) [3048F](#) [VC12516](#) [RC156-0500](#) [DM0523-1/2A](#) [1035A](#) [DMS0250-1A](#) [DMS0313-1A](#) [1040A](#) [1050A](#) [R1/8A](#) [DMPC0490-1/2A](#) [DMPC0521-1/2A](#) [DMPC0552-1/2A](#) [1070A](#) [R1/2A](#) [E1-7/8B](#) [061A](#) [R3/4A](#)