


a PennEngineering® Company


Heyco® Nylon D-Subminiature Mounting Hole Plugs


Clearance Fit for Panel Thickness up to .170" (4,3 mm)

MOUNTING H			SIZE B	PART NO.	DESCRIPTION	PART DIN C D Head				IENSIONS E F Body			=
in.	mm.	in.	mm.	Diack		in.	mm.	in.	mm.	in.	mm.	uy in.	mm.
		.81	20,6	2966	POP-DB9	1.25	31,8	.70	17,8	.69	17,5	.41	10,4
45	11,4	1.13	28,8	2968	POP-DB15	1.57	39,8	.70	17,8	1.05	26,7		
.45		1.67	42,5	2970	POP-DB25	2.12	51,0	.70	17,8	1.55	39,4		
		2.32	59,1	2972	POP-DB37	2.77	70,4	.70	17,8	2.23	56,6		

Standard color black. Consult Heyco for other colors.







Material Certifications

Flammability Rating Temperature Range

Nylon 6/6

- Recognized under the Component Program of Underwriters' Laboratories, File E51579
- (SF Certified by Canadian Standards Association, File 8919

-40°F (-40°C) to 221°F (105°C)




- Fit standard D-Subminiature Cutouts.
- Provide aesthetic improvement for unused D-subminiature connector mounting holes.
- Suitable for use as dust protection for unused parallel and serial ports on computers and other electrical equipment.
- Cover unwanted holes in panel and are easily removable.
- Quick and easy installation with fingertip pressure.


Heyco® IEC-14 Plug

For IEC-13 Female Connectors

PART NO. DESCRIPTION Black		į,	١	PART DIM	В	in	mm
		in.	mm.	in.	mm.	ın.	mm.
G5365	IECP C14	.96	24,4	.66	16.8	.38	9,7

Standard color black.









- Will keep your connector free of dust, moisture, and contaminants.
- The flanged Plug head provides ease of installation and removal.
- Consult Heyco for the IEC-20 Plug (for IEC-19 female connectors).

Material **LDPE**

Temperature Range -94°F (-70°C) to 150°F (66°C)



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Tools & Hardware category:

Click to view products by Heyco manufacturer:

Other Similar products are found below:

000-01-09-132 000-01-21-132 000-01-31-162 572019-00105-70 000-01-37-162 621-250-113-115 D110550-2 D20418-137 780-518-508G6-WS 86552009 86553115TLF 86553117TLF 1230032-1 1-5021101-2 1589283-4 160-000-005R031 16-000230 160-025-004R031 160-020-209R000 160X10909X 164C03939A 177-505-A-2-2 1-966830-8 21018-6 21028-2 2-1393560-9 JS-1000 L17D204182M3E L17D53018 300X10779X 160X10189X 160X10419X 162-000-050R000 21018-5 212561-3 248C21550X CF15P D110277 500-008NF1K-01 500-008NF3R3KS-01 500-017M09FN 500-017M15MHN 500-024M1 500-068M3 5-1393561-5 C115373-0001 C115373-0002 3342-4-KIT K1003 L17D4M68711