

a PennEngineering® Company

## Heyco-Flex™ II Liquid Tight Tubing


Flexible, Nonmetallic Liquid Tight Electrical Tubing

TRADE Size	PART NO. Black	DESCRIPTION	PART DII A Outside Diameter		MENSIONS B Inside Diameter		STANDARD COIL LENGTH ft/coil
			in.	mm.	in.	mm.	
1/4	8449	HF2 1/4	.57	14,4	.40	10,0	
3/8	8450	HF2 3/8	.70	17,8	.49	12,5	
1/2	8451	HF2 1/2	.83	21,1	.63	16,1	400
3/4	8452	HF2 3/4	1.04	26,4	.83	21,1	100
1	8453	HF2 1	1.30	33,1	1.05	26,8	
1-1/4	8454	HF2 1-1/4	1.65	41,8	1.40	35,4	
1-1/2	8455	HF2 1-1/2	1.88	47,8	1.59	40,3	F0
2	8456	HF2 2	2.36	59,9	2.03	51,6	50

Standard color black.

Consult Heyco for Cut to Length Availability.









- Maximum flexibility; can be used in extremely tight quarters.
- Smooth inside for easier wire pulling.
- Lightweight and lower installed cost.
- Integral rigid and flexible PVC construction.
- Use with nylon Heyco-Flex Connectors: Straight, Snap-in, or Sweep. See pages 2-9 to 2-11.
- Also use with Quick Twist Fittings. See pages 2-13 and 2-14.
- 1/4" thru 2" trade sizes.
- Resists corrosion, oil, and water.
- UV resistant.
- Suitable for use in high vibration or flexing applications:
  - Automotive Equipment
  - Computers and Peripherals
  - Fiber Optics
  - Lab Equipment
  - Lasers
  - Office Equipment
  - Processing Control and Monitoring Equipment
  - Robotics
  - White Goods
- Passes submersion test of 70 psi.
- Voltage Rating: 300V.
- Mounting brackets are available, see page 2-19.
- Order Part No. 8340, HF-28 Cutting Tool, for cutting Heyco-Flex tubing and conduit cleanly and evenly.

Material Certifications **PVC** 

Recognized under the Component Program of Underwriters' Laboratories File E121095

Certified by Canadian Standards Association File 233010 VW1

Flammability Rating Temperature Range

-.4°F (-18°C) to 158°F (70°C)



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Stripping & Cutting Tools category:

Click to view products by Heyco manufacturer:

Other Similar products are found below:

```
6-690504-4 693855-1 813066-2 844764-5 844765-5 1-240642-7 133900-001 1-356885-4 1424635-1 1424649-1 1424650-1 1440-0013-84

1-458031-5 1-458030-5 MT10-250Q 1755 2-539783-7 L-5211 1633578-3 F10-10Q 1-844765-9 251465-1 R282066100 313808-1

CST596711 458031-9 462839-1 467281-1 4-690504-2 406339-3 L-4994 45-265 453653-1 45-418 455177-1 455671-4 458144-8 462548-1 464661-1 224186-1 679746-1 809687-1 852080-2 856695-8 11-40-4082 458030-1 679326-7 605744-1 690784-2 844764-1
```