

| MOUNTING HOLE DIAMETER in.   mm. |     | SCREW<br>SIZE | PART DIMENSION A in.   mm.             |   | PART NO.   | DESCRIPTION   |  |  |  |  |  |
|----------------------------------|-----|---------------|--|---|--|---|--|--|--|--|--|
| Standard – "P Clamp" Design      |     |               |  |   |  |   |  |  |  |  |  |
| .203                             | 5,2 | 10            | .19<br>.25<br>.38<br>.50<br>.63<br>.75 | 4,7<br>6,3<br>9,5<br>12,7<br>15,9<br>19,1<br>22,2 | \$3373<br>\$3374<br>\$3376<br>\$3378<br>\$3380<br>\$3382<br>\$3384 | CC H 3/16 SS<br>CC H 1/4 SS<br>CC H 3/8 SS<br>CC H 1/2 SS<br>CC H 5/8 SS<br>CC H 3/4 SS<br>CC H 7/8 SS        |  |  |  |  |  |
| Standard – Coated                |     |               |  |   |  |   |  |  |  |  |  |
| .203                             | 5,2 | 10            | .19<br>.25<br>.38<br>.50<br>.63<br>.75 | 4,7<br>6,3<br>9,5<br>12,7<br>15,9<br>19,1<br>22,2 | \$3323<br>\$3324<br>\$3326<br>\$3328<br>\$3330<br>\$3332<br>\$3334 | CC H 3/16 SSC<br>CC H 1/4 SSC<br>CC H 3/8 SSC<br>CC H 1/2 SSC<br>CC H 5/8 SSC<br>CC H 3/4 SSC<br>CC H 7/8 SSC |  |  |  |  |  |





12335

12337

12338

12340

12341

12343

## Heyco® Steel Cuchion Clampo

.406

10.3

7/16

| пеус  |     |               |                     |      |             |              |  |  |  |  |  |
|---|-----|---------------|---------------------|------|-------------|--------------|--|--|--|--|--|
| MOUNTING<br>HOLE DIA.                                       |     | SCREW<br>SIZE | PART<br>DIMENSION A |      | PART<br>NO. | DESCRIPTION  |  |  |  |  |  |
| in.   | mm. |               | in.                 | mm.  |             |              |  |  |  |  |  |
| .650 (16,5 mm) Overall Width, .031 (0,8 mm) Steel Thickness |     |               |                     |      |             |              |  |  |  |  |  |
| .265  | 6,7 | 1/4           | .187                | 4,7  | 12300       | CCSC L 3/16  |  |  |  |  |  |
|   |     |               | .250                | 6,3  | 12301       | CCSC L 1/4   |  |  |  |  |  |
|   |     |               | .312                | 7,9  | 12302       | CCSC L 5/16  |  |  |  |  |  |
|   |     |               | .375                | 9,5  | 12303       | CCSC L 3/8   |  |  |  |  |  |
|   |     |               | .437                | 11,1 | 12304       | CCSC L 7/16  |  |  |  |  |  |
|   |     |               | .500                | 12,7 | 12305       | CCSC L 1/2   |  |  |  |  |  |
|   |     |               | .562                | 14,3 | 12306       | CCSC L 9/16  |  |  |  |  |  |
|   |     |               | .625                | 15,9 | 12307       | CCSC L 5/8   |  |  |  |  |  |
|   |     |               | .687                | 17,4 | 12308       | CCSC L 11/16 |  |  |  |  |  |
|   |     |               | .750                | 19,1 | 12309       | CCSC L 3/4   |  |  |  |  |  |
|   |     |               | .875                | 22,2 | 12310       | CCSC L 7/8   |  |  |  |  |  |
|   |     |               | 1.000               | 25,4 | 12311       | CCSC L 1     |  |  |  |  |  |
|   |     |               | 1.125               | 28,6 | 12312       | CCSC L 1-1/8 |  |  |  |  |  |
|   |     |               | 1.250               | 31,8 | 12313       | CCSC L 1-1/4 |  |  |  |  |  |
| .750 (19,1 mm) Overall Width, .047 (1,2 mm) Steel Thickness |     |               |                     |      |             |              |  |  |  |  |  |
|   |     |               | .250                | 6,3  | 12331       | CCSC H 1/4   |  |  |  |  |  |
|   |     |               | .312                | 7,9  | 12332       | CCSC H 5/16  |  |  |  |  |  |
|   |     |               | .375                | 9,5  | 12333       | CCSC H 3/8   |  |  |  |  |  |
|   |     |               | .437                | 11,1 | 12334       | CCSC H 7/16  |  |  |  |  |  |

Material 304 Stainless Steel (Stainless Steel Cable Clamps) Zinc Plated Steel with an EPDM Sleeve (Steel Cushion Clamps)

.500

.625

.687

.875

1.000

1.250

12,7

15,9

17,4

22,2

25,4

31,8



- For clamping cable or tubing securely into place, especially in harsh environments.
- Smooth "coined" clamp edges prevent damage to cable insulation.
- Constructed from corrosion resistant 304 stainless steel.
- Insulated parts are constructed from 304 stainless steel and coated with polyolefin, a thermoplastic co-polymer that provides a durable non-toxic, odorless coating that has very good low temperature flexibility and excellent electrical properties. This coating also has FDA food contact approval.
- Consult Heyco for larger sizes.
- Not for use in a marine salt water environment. Contact Heyco for alternative materials.
- All parts require a .203" (5,2 mm) mounting hole suitable for a #10 screw.
- DFARS Compliant.

**ALL NEW** 

**PRODUCTS** 

CCSC H 1/2

CCSC H 5/8


CCSC H 7/8 CCSC H 1

CCSC H 11/16

CCSC H 1-1/4



- Light to heavy duty steel clamp.
- E.P.D.M. cushion for electrical insulation and vibration absorption.
- Steel clamps are zinc electroplated for corrosion resistance.
- Color Silver with durable black cushion.





## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Mounting & Accessories category:

Click to view products by Heyco manufacturer:

Other Similar products are found below:

582603-1 009333-000 727844N003 747 809090N001 843188-000 8666 967279N002 DB-11 1300840039 1300900096 1301800416

1302264450 1300830184 1300830729 1300900039 1301580036 1301850553 1301860939 1302000074 1302261315 1302264431

1337706-2 APA18-AK 1724 1-787307-1 185491N001 1868 HP-6N C-202-C 202C221-13-0 CA7308-000 8S23-75FR-CS8184 2684 9648

3089 988382-000 A72821-000 AA401 173506-000 202C292-13-0 202C302-13-0 2109 300625 3330 3412 M9142 M9143 529732-000

561-50D1187