

3-TERMINAL 1.5A POSITIVE ADJUSTABLE VOLTAGE REGULATOR





DESCRIPTION

The LM317 is an adjustable 3-terminal positive voltage regulator designed to supply more than 1.5A of Output current with voltage adjustable from 1.3V-37V.

FEATURES

- Output current up to 1.5A
- Output voltage adjustable from 1.3V to 37V
- Internal short circuit protection
- Internal over temperature protection
- Safe-area compensation for output transistor

PIN DESCRIPTION



ABSOLUTE MAXIMUM RATINGS

(Ta=25°C, UNLESS OTHERWISE SPECIFIED)

PARAMETERS	SYMBOL	RATING	UNITS
Input-Output Voltage Difference	V_i-V_o	40	V
Lead Temperature	T_{LEAD}	260	°C
Power Dissipation	P_D	Internal Limited	-
Operating Temperature Range	T_{OPR}	0~+125	°C
Storage Temperature Range	T_{STG}	-60~+150	°C

ELECTRICAL CHARACTERISTICS

($V_i-V_o=5V, 0 < T_j < 125^\circ C, I_O=500mA, I_{max}=1.5A, P_{max}=20W$, UNLESS OTHERWISE SPECIFIED)

PARAMETER	SYMBOL	TEST CONDITLONS	MIN	TYP	MAX	UNIT
Line regulation	ΔV_o	Ta=25°C, 3V≤Vi-Vo≤40V		0.01	0.04	%V
		Ta=0-125°C, 3V≤Vi-Vo≤40V		0.02	0.07	
Load Regulation	ΔV_o	Ta=25°C 10mA≤IO≤Imax	Vo≤6V	18	25	mV
			Vo≤5V	0.4	0.5	%Vo
	ΔV_o	10mA≤IO≤Imax	Vo≤5V	40	70	mV
			Vo≤5V	0.8	1.5	%Vo
Adjustable Pin Current	IADJ			46	100	uA
Adjustable Pin Current Change	ΔI_{ADJ}	2.5V≤Vi-Vo≤40V, 10mA≤Io≤Imax,PD≤Pmax		2.0	5	uA
Reference Voltage	VREF	3V≤Vi-Vo≤40V, 10mA≤Io≤Imax,PD≤Pmax	1.2	1.25	1.3	V
Temperature Stability	STT			0.7		%Vo
Minimum Load Current for regulation	IL(MIN)	Vi-Vo=40V		3.5	10	mA
Maximum output Current	IO(MAX)	Vi-Vo=15V,PD≤Pmax	1.5	2.2		A
		Vi-Vo=15V,PD≤Pmax,Ta=25°C	0.15	0.4		
RMS Noise v.s.%of Vout	eN	Ta=25°C,10Hz≤F≤10KHz		0.003	0.01	%Vo
Ripple Rejection	RR	Vo=10V,F=120Hz,Cadj=0		60		dB
		Vo=10V,F=120Hz,Cadj=10uF	66	75		
Load-term Stability,Tj=THIGH	ST	Ta=25°C,1000 hr		0.3	1	%

Note:Testing with low duty pulse should be used to avoid heating effect.

Important statement:

Huaguan Semiconductor Co,Ltd. reserves the right to change the products and services provided without notice. Customers should obtain the latest relevant information before ordering, and verify the timeliness and accuracy of this information.

Customers are responsible for complying with safety standards and taking safety measures when using our products for system design and machine manufacturing to avoid potential risks that may result in personal injury or property damage.

Our products are not licensed for applications in life support, military, aerospace, etc., so we do not bear the consequences of the application of these products in these fields.

Our documentation is only permitted to be copied without any tampering with the content, so we do not accept any responsibility or liability for the altered documents.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Linear Voltage Regulators](#) category:

Click to view products by [HGSEMI](#) manufacturer:

Other Similar products are found below :

[LV56831P-E](#) [LV5684PVD-XH](#) [MCDTSA6-2R](#) [L4953G](#) [L7815ACV-DG](#) [PQ3DZ53U](#) [LV56801P-E](#) [TCR3DF13,LM\(CT](#)
[TCR3DF39,LM\(CT](#) [TLE42794G](#) [L78L05CZ/1SX](#) [L78LR05DL-MA-E](#) [L78MR05-E](#) [033150D](#) [033151B](#) [090756R](#) [636416C](#)
[NCV78M15BDTG](#) [702482B](#) [714954EB](#) [TLE42794GM](#) [TLE42994GM](#) [ZMR500QFTA](#) [BA033LBSG2-TR](#) [NCV78M05ABDTRKG](#)
[NCV78M08BDTRKG](#) [NCP7808TG](#) [NCV571SN12T1G](#) [LV5680P-E](#) [CAJ24C256YI-GT3](#) [L78M15CV-DG](#) [L9474N](#)
[TLS202B1MBV33HTSA1](#) [L79M05T-E](#) [NCP571SN09T1G](#) [MAX15006AASA/V+](#) [MIC5283-5.0YML-T5](#) [L4969URTR-E](#) [L78LR05D-MA-E](#)
[NCV7808BDTRKG](#) [L9466N](#) [NCP7805ETG](#) [SC7812CTG](#) [NCV7809BTG](#) [NCV571SN09T1G](#) [NCV317MBTG](#) [MC78M15CDTT5G](#)
[MC78M12CDTT5G](#) [L9468N](#) [LT1054IS8#TRPBF](#)