



Jul.1.2019 Copyright 2019 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.




| CODE No.        | PARTS No.          | NUMBER OF CONTACT | A     | B     | C     | D     | E     | F     |
|-----------------|--------------------|-------------------|-------|-------|-------|-------|-------|-------|
| CL536-0251-1-75 | DF13- 2P-1.25H(75) | 2                 | 1.25  | 3.15  | 4.15  | 7.15  | 3.35  | 5.65  |
| CL536-0252-4-75 | DF13- 3P-1.25H(75) | 3                 | 2.5   | 4.4   | 5.4   | 8.4   | 4.60  | 6.9   |
| CL536-0253-7-75 | DF13- 4P-1.25H(75) | 4                 | 3.75  | 5.65  | 6.65  | 9.65  | 5.85  | 8.15  |
| CL536-0254-0-75 | DF13- 5P-1.25H(75) | 5                 | 5.0   | 6.9   | 7.9   | 10.9  | 7.10  | 9.40  |
| CL536-0255-2-75 | DF13- 6P-1.25H(75) | 6                 | 6.25  | 8.15  | 9.15  | 12.15 | 8.35  | 10.65 |
| CL536-0256-5-75 | DF13- 7P-1.25H(75) | 7                 | 7.5   | 9.4   | 10.4  | 13.4  | 9.60  | 11.9  |
| CL536-0257-8-75 | DF13- 8P-1.25H(75) | 8                 | 8.75  | 10.65 | 11.65 | 14.65 | 10.85 | 13.15 |
| CL536-0258-0-75 | DF13- 9P-1.25H(75) | 9                 | 10.0  | 11.9  | 12.9  | 15.9  | 12.1  | 14.4  |
| CL536-0259-3-75 | DF13-10P-1.25H(75) | 10                | 11.25 | 13.15 | 14.15 | 17.15 | 13.35 | 15.65 |
| —               | DF13-11P-1.25H(75) | 11                | 12.5  | 14.4  | 15.4  | 18.4  | 14.6  | 16.9  |
| CL536-0261-5-75 | DF13-12P-1.25H(75) | 12                | 13.75 | 15.65 | 16.65 | 19.65 | 15.85 | 18.15 |
| CL536-0263-0-75 | DF13-14P-1.25H(75) | 14                | 16.25 | 18.15 | 19.15 | 22.15 | 18.35 | 20.65 |
| CL536-0264-3-75 | DF13-15P-1.25H(75) | 15                | 17.5  | 19.4  | 20.4  | 23.4  | 19.6  | 21.9  |

RECOMMENDED PATTERN



HRS DRAWING FOR REFERENCE

- NOTE
- 1: WHEN THIS CONNECTOR MATES WITH DF13-\*S-1.25C, THE MATED DEPTH IS 6mm.
  - 2: THERE SHALL BE STANDOFF MORE THAN FIVE CONTACTS.
  - 3: WHEN THIS CONNECTOR HAS TWO OR THREE CONTACTS, THE LOCK SHALL BE SET AT THE CENTER OF HOUSING. IF MORE THAN FOUR, THE TWO LOCKS SHALL BE SET AS SHOWN ON THIS DRAWING.
  - 4: FLATNESS OF LEAD WITH REINFORCED METAL FITTINGS SHALL BE WITHIN 0.1mm.
  - 5: WHEN THIS CONNECTOR HAS MORE THAN SEVEN CONTACTS, HRS MARKING AND POLARIZATION MARKING SHIFT TO THE PLACE INDICATING DOTTED LINES.




| NO. | MATERIAL  | FINISH . REMARKS   | NO. | MATERIAL        | FINISH . REMARKS                   |
|-----|-----------|--|-----|-----------------|------------------------------------|
| 2   | BRASS     | SURFACE PLATING:TIN PLATED 1µm min<br>UNDER PLATING:COPPER PLATE 1µm min | 5   | ELASTOMER       | GRAY, STOPPER                      |
| 1   | POLYAMIDE | BEIGE, UL94V-0   | 4   | R. PVC          | ANTI-ELECTIRICATION, CLEAR, STICK  |
|     |           |  | 3   | PHOSPHOR BRONZE | SURFACE PLATING:TIN PLATED 1µm min |

| UNITS                   | SCALE | COUNT | DESCRIPTION OF REVISIONS | DESIGNED                     | CHECKED | DATE |
|-------------------------|-------|-------|--------------------------|------------------------------|---------|------|
| mm                      | 5 : 1 | △     |                          |                              |         |      |
| APPROVED : HS. OKAWA    |       |       | 18.03.20                 | DRAWING NO. EDC-083662-75-00 |         |      |
| CHECKED : TS. FUKUSHIMA |       |       | 18.03.20                 | PART NO. DF13-*P-1.25H(75)   |         |      |
| DESIGNED : TS. KUMAZAWA |       |       | 18.03.19                 | CODE NO. CL536-              |         |      |
| DRAWN : MK. INOUE       |       |       | 18.03.08                 |                              |         |      |

Jul.1.2019 Copyright 2019 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



| CODE No.        | PARTS No.          | QUANTITY OF CONNECTOR |
|-----------------|--------------------|-----------------------|
| CL536-0251-1-75 | DF13- 2P-1.25H(75) | 67                    |
| CL536-0252-4-75 | DF13- 3P-1.25H(75) | 57                    |
| CL536-0253-7-75 | DF13- 4P-1.25H(75) | 49                    |
| CL536-0254-0-75 | DF13- 5P-1.25H(75) | 44                    |
| CL536-0255-2-75 | DF13- 6P-1.25H(75) | 39                    |
| CL536-0256-5-75 | DF13- 7P-1.25H(75) | 36                    |
| CL536-0257-8-75 | DF13- 8P-1.25H(75) | 33                    |
| CL536-0258-0-75 | DF13- 9P-1.25H(75) | 30                    |
| CL536-0259-3-75 | DF13-10P-1.25H(75) | 28                    |
| —               | DF13-11P-1.25H(75) | 26                    |
| CL536-0261-5-75 | DF13-12P-1.25H(75) | 24                    |
| CL536-0263-0-75 | DF13-14P-1.25H(75) | 21                    |
| CL536-0264-3-75 | DF13-15P-1.25H(75) | 20                    |

NOTES 6 : THE TUBE HAS ONE STOPPER AT EACH END.  
 7 : WARPAGE OF THE TUBE SHALL BE ALLOWED ±2mm PER 510mm.  
 8 : MINIMUM UNIT OF PURCHASE SHALL BE THE QUANTITY OF CONNECTORS IN TUBE.  
 (DIMENSION DELETION)

|            |             |                   |
|------------|-------------|-------------------|
| <b>HRS</b> | DRAWING NO. | EDC-083662-75-00  |
|            | PART NO.    | DF13-*P-1.25H(75) |
|            | CODE NO.    | CL536-            |

2/2

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Single Board Computers](#) category:*

*Click to view products by [Crowd Supply](#) manufacturer:*

Other Similar products are found below :

[MANO882VPGGA-H81](#) [SSD3200W-S-SLC-INN](#) [AmITX-SL-G-Q170](#) [IB100](#) [MVME61006E-2173R](#) [20-101-0738](#) [PCE-4128G2-00A1E](#)  
[RSB-4220CS-MCA1E](#) [SHB230DGGA-RC](#) [IB909AF-5650](#) [PICO841VGA-E3827](#) [IMB210VGGA](#) [MI981AF](#) [RSB-4221CS-MCA1E](#) [PCE-](#)  
[9228G2I-00A1E](#) [IB915F-3955](#) [IB909F-5010](#) [MI958F-16C](#) [UPS-P-8G-64GB-PACK](#) [S2600WFT](#) [IB915AF-6300](#) [S2600STB](#) [BBS2600BPS](#)  
[IB915F-6100](#) [Nit6QP\\_MAX](#) [MI990VF-X28-E](#) [MI990VF-6820](#) [MI991AF-C236](#) [94AC6636](#) [BANANA PI BPI-M4](#)  
[BLKNUC7I3DNHNC1978015](#) [BLKNUC7I5DNK1E 960791](#) [IOT-LS1012A-OXALIS](#) [NITX-300-ET-DVI](#) [94AC6633](#) [A33-OLINUXINO-](#)  
[N8G](#) [A64-OLINUXINO-1GE16GW](#) [A20-SOM-E16GS16M](#) [A20-SOM204-1G-M](#) [EMB-APL1-A10-3350-F1-LV](#) [PICO-APL1-A10-F001](#)  
[PICO-APL4-A10-F003](#) [ODYSSEY - STM32MP157C BOARD WITH SOM](#) [BEAGLEBONE GREEN GATEWAY DEV BOARD](#) [ODYSSEY](#)  
[- X86J4105864 8GB RAM 64GB EMMC](#) [ODYSSEY -X86J4105864 8GB/64GB ENTERPRISE](#) [VISIONDK-STM32MP1 V.1.0](#) [VISIONDK-](#)  
[6ULL V.2.0](#) [VISIONDK-8MMINI V.1.0](#) [VISIONDK-RT](#)