

USB from Hirose Electric: Standard connections, inspired solutions





Features

- 1 Excellent high-speed transmission characteristics and flexibility by using micro coaxial cable.
- 2 USB3.1.Gen2(10Gbps), High-speed transmission (TID No: 5,220,000,534)
- 3 Thin and soft cable for easy handling
- 4 Unique lock design provides a clear tactile click

	HRS Micro coaxial cable	STP
Softness (Flexibility)	◎	×
Flexural Strength	◎	×
Cable Outer Diameter	Φ3.8-4.8	Φ5 Min.
High-Speed Transmission Characteristics (Initial)	◎	△
High-Speed Transmission Characteristics (50,000 bends)	◎ (10Gbps)	×

*◎: Excellent ○: Good △: Satisfactory ×: Poor

	HRS Micro coaxial cable	STP
Design	 <ul style="list-style-type: none"> - A coaxial cable is used for the super-speed line. - Coaxial characteristic impedance is 45Ω - 4 sets of coaxial cable pairs (8 cables) 	 <ul style="list-style-type: none"> - STP used for the super-speed line. - STP's characteristic impedance is 90Ω - STP 4-cable configuration
Features	<ul style="list-style-type: none"> - The cable is soft. - The cable resists characteristic degradation caused by bending. - The coaxial cable has a rigid shield design. It has high frequency, low attenuation and high stability. 	<ul style="list-style-type: none"> - A collection of pairs of rigid cables. - The cable characteristics degrade when bended. - Electric properties have low stability due to the design. - The twin-core twisted pair design stabilizes the internal skew.

*STP: Shielded Twisted Pair

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Cables / IEEE 1394 Cables](#) category:

Click to view products by [Hirose](#) manufacturer:

Other Similar products are found below :

[68768-0173](#) [FNY-W6003-01](#) [88764-0800](#) [148700-1](#) [17-200621](#) [17-250051P](#) [954](#) [17-200261](#) [AC102012-1](#) [AC102012-2](#) [FTP-629Y601](#) [45-1345-15](#) [45-1358-15](#) [45-1363-15](#) [IP-USB1\(C10\)S-RW](#) [CABLE/RTP/USB/DT](#) [45-1351-15](#) [45-1357-15](#) [45-1433-1](#) [687680278](#)
[USBFTVX2SA2N03A](#) [USBFTV2SA2N03A](#) [USBFTV2SA2N05A](#) [MDM9PH004B](#) [MDM9PH004P](#) [FTP-629Y401](#) [FTP-628Y302](#) [FTP-628Y402](#) [CSMNB9MF-5](#) [FNY-W6022](#) [UA-30AMF-SD7B03](#) [UA-30AMFM-SL7B03](#) [USBAPSCC7202A](#) [UES-1001A160](#) [UES-1003A160](#)
[USBFTVX7SA2N20A](#) [USBFTV2PEMSA2N10A](#) [FTP-629Y602](#) [USBCAMCM100](#) [USB A/F*2 to 2.54 2*5P-SH L=400mm](#) [68784-0075](#)
[USB-29](#) [19800-010500-200-RS](#) [103-1092-BL-F0050](#) [103-1020-BL-00100](#) [103-1092-BL-F0200](#) [103-1092-BL-F0100](#) [105-1092-BL-00300](#)
[105-1092-BL-00200](#) [105-1031-BL-00200](#)