

### Features

- 1 Wide-ranging options to satisfy various customer requirements.  
Straight/Right angle, Single/Dual-row, Gold/Tin Plating etc.
- 2 Center Lock design enables high density mounting and easy operation
- 3 Lock damage prevention design
- 4 Secure mating with clear tactile click prevents incomplete insertion
- 5 High contact reliability with long effective mating length and 2-point contact design
- 6 Accepts Resin Sealing



Positive-Lock



P=2.0mm



Wide Variation


### Dimensions

#### Straight Type

##### Single-row (Ex : 6pos.)

Socket : DF51K-6S-2C


Header : DF51K-6P-2DSA



#### Right Angle Type

Socket : DF51K-6S-2C


Header : DF51K-6P-2DS



##### Dual-row (Ex : 16pos.)


Socket : DF51K-16DS-2C

Header : DF51K-16DP-2DSA



Socket : DF51K-16DS-2C

Header : DF51K-16DP-2DS



### Specifications

Rated Current	22 AWG	24 AWG	26 AWG	28 AWG	30 AWG
	2A	2A	1.5A	1A	0.5A
Rated Voltage	250V AC/DC				
Operating Temperature	-55 to 105°C*				
Contact Resistance	30mΩ Max. (20mV, 1mA)				
Insulation Resistance	1,000MΩ Min. (500V DC)				
Withstanding Voltage	650V AC for 1 min.				
Mating Durability	30 times (Sn) / 50 times (Au)				

\* Including the temperature rise by current flow

- Pin variations : Single-row (2 - 6pos.), Dual-row (4 - 30pos.)
- Applicable cable : 22-30 AWG
- UL/C-UL certified
- RoHS compliant

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Hirose](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)