

HR41A Series

IP68 Small Plastic Power Connector




Features

- 1. IP68* weather-resistant waterproof connector for outdoor use
- 2. Higher lightning surge protection (15 kV) and withstanding voltage
- 3. Snap-in mating with user-friendly push-on bayonet lock
- 4. Bayonet assembly eliminates torque management and re-tightening of screw
- 5. Easy field assembly
- 6. UL, TÜV pending

*Our test condition: No water intrusion, while submerged in 2 m water depth for 14 days in mated condition.

Small Size


- Plug (HR41A-17WBP-5SC)



Cable Size: ϕ 10.7 to 11.5


 ϕ 9.0 to 9.8 (Under development) ϕ 8.2 to 9.0 (Under development)

- Receptacle (HR41A-17WBRA-5PC)





- Jack (HR41A-17WBJ-5PC)



- Crimping Tool

Part No.: HT802/HR41A-11-16(AWG#16) HT802/HR41A-11-18(AWG#18) HT802/HR41A-11-20(AWG#20)

Component	Material	Finish / Remarks
Housing	PBT	UL94V-0, Black
Contact	Phosphor Bronze	Gold Plating
Clamp	Polyamide Resin	UL94V-0, White
O-ring, Gasket	Silicone Rubber	-
Washer	Stainless Steel	-

Rated Voltage	AC 250V, DC 350V	
Rated Current	10 Amps	
Operating Temperature	-40°C to +105°C	
Contact Resistance	5mΩ Max. (1A)	
Insulation Resistance	5000MΩ Min. (DC500V)	
Withstanding Voltage	AC 2200V, 1 minute	
Durability	500 times	
Water Resistance	IP68 (Our test condition: No water intrusion, while submerged in 2 m water depth for 14 days in mated condition.)	

- Contact Extraction Tool Part No.: HR41A-TP

Specifications herein are subject to change without notice. Contact Hirose for latest specifications, drawings or availabilities.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Crimpers category:

Click to view products by Hirose manufacturer:

Other Similar products are found below:

```
576771-1 576788-2 010-0041 010-0055 010-0096 604228-1 606718-1 M225202-37 CT150-2-D02 CT150-6-RH07 M322 63484-3701 63800-0140 63800-8355 63811-3275 63811-3376 63811-6375 63811-6475 63811-7875 63811-8175 63811-8875 63819-0475 63819-1875 63819-2875 63819-4375 63819-4475 63823-3475 63823-5175 63823-6375 63823-8375 63827-5375 64001-0975 64001-2175 64001-4175 662903-2 679513-1 690141-6 690142-4 690602-6 D38999/20WA98JB-LC 7-1633664-2 7-22278-0 7-22280-5 7-240641-1 7-240641-3 762637-1 808714-1 8-1633117-3 853721-6 91362-1
```