



CE

1/2



BSB 20 K

Product	BSB 20 K				
description	Multiple-spring wire plug with cable gland and 4 mm socket for onward connection cabability. Screw connection up to maximum cable cross-section of 2.5 mm ² and external diameter of 4 mm. Nickel-plated brass contact material.				
operating instruction	BA411				
article-no. / *colour	9307291xx 00 black	01 red	02 blue	03 yellow	04 green
					Ni
drawing					
technical data					
connection	screw terminal				
rated voltage ⁽¹⁾	30 VAC / 60 VDC				
measurement cat. acc. to IEC 61010	O ⁽³⁾				
rated current ⁽¹⁾ (consider derating curve)	30 A				
material plug	brass, nickel plated				
housing material	PP				
temperature range acc. To IEC61010 ⁽²⁾	-25 °C to +100 °C				
inflammability class acc. to UL 94 (only valid for basic material of housing)	НВ				
standard	IEC 61010				

 $^{(1)}$ for normal environmental conditions -5°C to +40°C

⁽²⁾ contact the manufacturer for applications at deviating temperature ranges





 $^{\rm (3)}$ without rated measurement category, for other circuits that are not directly connected to mains stand: 07.05.2019

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Control Switches category:

Click to view products by Hirschmann manufacturer:

Other Similar products are found below :

80887-99 80932-99 86855-00 88814-30 1424293-1 HW4S-2TC10 89721-12 89804-08 SSN RL01801 ASD2L20N-LVO 50051857-17 50099156-001-05 51.155R-15200 50058920-26 CP-FA51 CP-FA49 ACCU-SC/L-3000 PP9M PP87G PP86GA PP71G PP70G PP6G PP62G PP58BL PP56G PP86GB PP77GA PP76G PP4M PP47G PP46G PP41M PP40G PP32G RD-20 PP23M PP12G PORTAPRO POM-2708 PNB-2005 3057.0012 CV-075 CV-140SB CV-150 CV-150S 214X20XK CV-180 CV-200MB