



Plugs

BUELA 20 K



 ϵ

Product	BUELA 20 K					
description	Multiple-spring wire plug, shatter-proof, flexible insulated sleeve with transverse hole. The tapering sleeve end also serves as kinking protection for the lead. Screw connection up to maximum cable cross-section of 1.5 mm². Nickel-plated brass contact material.					
operating instruction	BA410					
article-no. / *colour	9307261xx	O1 red	02 blue	03 yellow	04 green	07 white
drawing						
	60					
technical data						
connection	screw terminal					
rated voltage ⁽¹⁾	30 VAC / 60 VDC					
measurement cat. acc. to IEC 61010	O ⁽³⁾					
rated current ⁽¹⁾ (consider derating curve)	16 A					
material plug	brass, nickel plated					
housing material	PVC-P					
temperature range acc. To IEC61010 ⁽²⁾	-25 °C to +70 °C					
standard	IEC 61010					
	•					

⁽¹⁾ for normal environmental conditions -5°C to +40°C (2) contact the manufacturer for applications at deviating temperature ranges

⁽³⁾ without rated measurement category, for other circuits that are not directly connected to mains stand: 07.05.2019

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Control Switches category:

Click to view products by Hirschmann manufacturer:

Other Similar products are found below:

80887-99 80932-99 86855-00 88814-30 1424293-1 HW4S-2TC10 89721-12 89804-08 SSN RL01801 ASD2L20N-LVO 50051857-17 50099156-001-05 51.155R-15200 CP-FA51 CP-FA49 ACCU-SC/L-3000 PP9M PP87G PP86GA PP74G PP73M PP73G PP70G PP6G PP62G PP58BL PP56G PP86GB PP77GA PP76G PP4M PP47G PP46G PP41M PP40G PP32G RD-20 PP23M PP14M PP12G 3057.0012 CV-075 214X20XK CV-180 CW1S-2E11 WEL.PT-E9 WEL.PT-C7 WEL.PT-AA9 WEL.PT-A8